US 20130321340A1

(19) **United States**

(12) **Patent Application Publication**

Seo et al.

(10) **Pub. No.: US 2013/0321340 A1**

(43) **Pub. Date: Dec. 5, 2013**

(54) **PORTABLE DEVICE COMPRISING A TOUCH-SCREEN DISPLAY, AND METHOD FOR CONTROLLING SAME**

(75) Inventors: **Joon-kyu Seo**, Seongnam-si (KR); **Kyung-A Kang**, Seoul (KR); **Ji-Yeon Kwak**, Seoul (KR); **Hyun-jin Kim**, Seoul (KR); **Hyun-Jung Song**, Seoul (KR); **Sung-Sik Yoo**, Yongin-si (KR); **Ju-youn Lee**, Seongnam-si (KR); **Dong-Seok Ryu**, Seoul (KR); **Min-Kyu Park**, Seongnam-si (KR)

(73) Assignee: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-si, Gyeonggi-do (KR)

(21) Appl. No.: **13/984,805**

(22) PCT Filed: **Feb. 7, 2012**

(86) PCT No.: **PCT/KR2012/000888**

§ 371 (c)(1),
(2), (4) Date: **Aug. 9, 2013**

Related U.S. Application Data

(60) Provisional application No. 61/441,491, filed on Feb. 10, 2011.


Publication Classification

(51) **Int. Cl.**
G06F 3/0484 (2006.01)

(52) **U.S. Cl.**
CPC ***G06F 3/0484*** (2013.01)
USPC **345/174**

(57) **ABSTRACT**

A method of controlling a portable device including at least one foldable panel and first and second touch screens is provided. The method includes displaying, on the first touch screen, a first page designated as a home screen and an icon related to at least one application, and a dock area, and displaying, on the second touch screen, first information in a state where the foldable panel is unfolded. The method also includes replacing the first page and the dock area with an outgoing call screen, receiving a phone number input, replacing the outgoing call screen with a dialing screen, and displaying, on the second touch screen, a guide message indicating to fold the portable device for a call. The method also includes replacing the dialing screen with a mid-call screen, and removing the guide message displayed on the second touch screen, and displaying the first information.





100
190a
FIRST TOUCH SCREEN
SECOND TOUCH SCREEN
190b
TOUCH SCREEN CONTROLLER
195
120
MOBILE COMMUNICATION MODULE
CONTROLLER
POWER SUPPLY UNIT
180
111
CPU
130
SUB-COMMUNICATION MODULE
131
WIRELESS LAN MODULE
SENSOR MODULE
170
112
ROM
110
INPUT/OUTPUT MODULE
160
132
NEAR-FIELD COMMUNICATION MODULE
113
RAM
BUTTON
161
140
MULTIMEDIA MODULE
MIC
162
141
BROADCAST COMMUNICATION MODULE
SPEAKER
163
142
AUDIO PLAY MODULE
VIBRATION MOTOR
164
143
VIDEO PLAY MODULE
CONNECTOR
165
KEYPAD
166
150
CAMERA MODULE
151
FIRST CAMERA
STORING UNIT
175
152
SECOND CAMERA
155
GPS MODULE

FIG.1




FIG.2




FIG.3A




FIG.3B




FIG.3C




FIG.3D




FIG.4




FIG.5A




FIG.5B




FIG.5C



12
14
206
1:28 AM
80%
208
202a
204a
widget 1
212
widget 2
widget 3
widget 4
218
Loading
202
214
204
200a
216

FIG.6A



12
14
206
1:28 AM
80%
208
232a
234a
widget 5
widget 6
widget 7
232
234
200b
216

FIG.6B



12
14
206
1:28 AM
80%
208
242
5
6
244a
242a
244
widget 6
widget 7
widget 8
widget 9
PM
234
+ 2010. Feb. 10.
Wed
216

FIG.6C



12
14
206
1:28 AM
80%
208
204a
232a
widget 4
widget 5
Loading
232
204
216

FIG.6D



12
14
206
1:28 AM
80%
208
202a
240
Song title - Artist
widget 1
widget 2
widget 3
202
200c
216

FIG.6E



12
14
206
1:28 AM
204a
2
widget 4
200d
Loading
204
200e
216
80%
208
240
Song title - Artist

FIG.6F



12
14
206
1:28 AM
232a
widget 5
232
200f
216
80%
208
240
Song title - Artist

FIG.6G



12
14
206
1:28 AM
208
80%
202a
204a
widget 1
202
widget 2
widget 3
210a
widget 4
Loading
204
216

FIG.7A



12
14
206
1:28 AM
80%
208
202a
204a
widget 1
202
widget 2
widget 4
widget 3
Loading
204
210c
250
Add
Wallpaper
Search
Notification
Edit
Settings
252
210b

FIG.7B



12
14
206
1:28 AM
80%
208
202a
252
204a
> Add to Home screen
~~~
~~~
Shortcuts
~~~
~~~
widget 4
Loading
202
210d
204
216

FIG.7C



12
14
206
1:28 AM
80%
208
202a
254
204a
> Add to Home screen
Applications
210e
202
widget 4
Loading
204
216

FIG.7D



12
14
206
1:28 AM
80%
208
202a
260a
260
widget 1
202
ICON 1
ICON 2
ICON 3
ICON 4
260b
widget 2
ICON 5
ICON 6
ICON 7
ICON 8
210d
widget 3
ICON 9
ICON 10
ICON 11
ICON 12
ICON 13
ICON 14
ICON 15
ICON 16
ICON 17
ICON 18
ICON 19
ICON 20
216

FIG.7E



12
14
206
1:28 AM
202a
widget 1
202
widget 2
widget 3
ICON 7
260c
216
80%
208
260a
260
ICON 1
ICON 2
ICON 3
ICON 4
260b
ICON 5
ICON 6
ICON 7
ICON 8
210e
ICON 9
ICON 10
ICON 11
ICON 12
ICON 13
ICON 14
ICON 15
ICON 16
ICON 17
ICON 18
ICON 19
ICON 20

FIG.7F



12
14
206
1:28 AM
80%
208
202a
1
2
262a
262
widget 1
ICON 21
ICON 22
ICON 23
ICON 24
202
262b
widget 2
ICON 7
210f
ICON 25
ICON 26
ICON 27
ICON 28
widget 3
260c
ICON 29
ICON 30
ICON 31
ICON 32
ICON 33
ICON 34
ICON 35
ICON 36
ICON 37
216

FIG.7G



12
14
206
1:28 AM
80%
208
202a
1
2
262a
262
widget 1
202
ICON 21
ICON 22
ICON 23
ICON 24
ICON 25
ICON 26
ICON 27
ICON 28
ICON 29
ICON 30
ICON 31
ICON 32
ICON 33
ICON 34
ICON 35
ICON 36
ICON 37
widget 2
ICON 23
ICON 7
262c
260c
widget 3
216

FIG.7H



12
14
206
1:28 AM
80%
208
202a
262a
262
widget 1
202
ICON 21
ICON 22
ICON 23
ICON 24
ICON 25
ICON 26
ICON 27
ICON 28
ICON 29
ICON 30
ICON 31
ICON 32
ICON 33
ICON 34
ICON 35
ICON 36
ICON 37
widget 2
widget 3
ICON 7
ICON 23
260c
262c
210h
256
Save
Discard
252
210g

FIG.7I



12
14
206
1:28 AM
80%
208
202a
204a
widget 1
202
widget 2
ICON 23
ICON 7
262c
260c
widget 3
widget 4
Loading
204
216

FIG.7J



12
14
206
1:28 AM
80%
208
272a
274b
272
274
280a
ICON 1
ICON 2
ICON 3
ICON 4
ICON 5
ICON 6
ICON 7
ICON 8
ICON 9
ICON 10
ICON 11
ICON 12
ICON 13
ICON 14
ICON 15
ICON 16
ICON 17
ICON 18
ICON 19
ICON 20
ICON 21
ICON 22
ICON 23
ICON 24
ICON 25
ICON 26
ICON 27
ICON 28
ICON 29
ICON 30
ICON 31
ICON 32
ICON 33
ICON 34
ICON 36
ICON 37

FIG.8A



12
14
206
1:28 AM
80%
208
276a
278a
276
278
ICON 41
ICON 42
ICON 43
ICON 44
ICON 45
ICON 46
ICON 47
ICON 48
ICON 49
ICON 50
ICON 51
ICON 52
ICON 53
ICON 54
ICON 55
ICON 56
ICON 61
ICON 62
ICON 63
ICON 64
ICON 65
ICON 66
ICON 67
ICON 68
ICON 69
ICON 70

FIG.8B



1:28 AM
206
282
12
282a
282b
2
80%
208
14
286
284
App 4
App 2
Application 1
App 3
App 5

FIG.8C



12
14
Mypho..
2
80%
302
SEARCH ENGINE
304
thumbnail 1
thumbnail 2
thumbnail 3
thumbnail 4
thumbnail 5
thumbnail 6
thumbnail 7
thumbnail 8
thumbnail 9
thumbnail 10
thumbnail 11
thumbnail 12
Login
Config
HELP

FIG.9A



12
14
Mypho..
2
80%
302
304
INE
mbnail 22
thumbnail 23
thumbnail 1
mbnail 2
thumbnail 3
306
mbnail 25
thumbnail 26
thumbnail 4
mbnail 28
thumbnail 29
thumbnail 7
mbnail 31
thumbnail 32
thumbnail 10
mbnail 11
thumbnail 12
IN
HELP

FIG.9B



12
14
Mypho..
302a
302b
thumbnail 21
thumbnail 22
thumbnail 23
thumbnail 24
thumbnail 25
thumbnail 26
thumbnail 27
thumbnail 28
thumbnail 29
thumbnail 30
thumbnail 31
thumbnail 32
thumbnail 1
thumbnail 2
thumbnail 3
thumbnail 4
thumbnail 5
thumbnail 6
thumbnail 7
thumbnail 8
thumbnail 9
thumbnail 10
thumbnail 11
thumbnail 12

FIG.9C



12
14
Mypho..
302a
302b
310
thumbnail 21
thumbnail 22
thumbnail 23
thumbnail 24
thumbnail 25
thumbnail 26
thumbnail 27
thumbnail 28
thumbnail 29
thumbnail 30
thumbnail 31
thumbnail 32
thumbnail 1
thumbnail 2
thumbnail 3
thumbnail 4
thumbnail 5
thumbnail 6
thumbnail 7
thumbnail 8
thumbnail 9
thumbnail 10
thumbnail 11
thumbnail 12

FIG.9D



12
14
Mypho..
1/8
302a
310
306
306a
thumbnail 21
thumbnail 22
thumbnail 23
thumbnail 24
thumbnail 25
thumbnail 26
thumbnail 27
thumbnail 28
thumbnail 29
thumbnail 30
thumbnail 31
thumbnail 32
Image 21

FIG.9E



12
14
Mypho..
2/8
302a
308a
thumbnail 21
thumbnail 22
thumbnail 23
312
thumbnail 24
thumbnail 25
thumbnail 26
308
thumbnail 27
thumbnail 28
thumbnail 29
thumbnail 30
thumbnail 31
thumbnail 32
Image 24

FIG.9F



12
14
Mypho..
2/8
320
308a
302a
thumbnail 21
thumbnail 22
thumbnail 23
thumbnail 24
thumbnail 25
thumbnail 26
thumbnail 27
thumbnail 28
thumbnail 29
thumbnail 30
thumbnail 31
thumbnail 32
Image 24

FIG.9G




FIG.9H




FIG.9I




FIG.9J



12
14
402
Wed. 15 Oct. 2010
09:00 .....
23:00 .....
404
Seoul
L:21° H:32°
29°c
406
Tell me - WG
408
Hyun Bin
Call
Message
410
Application #1
Application #2
Application #3
Application #4
Application #5
412
Gallery
414

FIG.10A



12
420
14
Wed. 15 Oct. 2010
09:00
23:00
402
Seoul
L:21° H:32°
29°c
404
Tell me - WG
406
Hyun Bin
Call
Message
408
410
Application #1
Application #2
Application #3
Application #4
Application #5
412
Gallery
414

FIG.10B



12
14
402a
404
406
408
410
412
414
Wed. 15 Oct. 2010
09:00
23:00
Sun Mon Tue Web Thu Fri Sat
31 1 2 3 4 5 6
Seoul
L:21° H:32°
29°c
Tell me - WG
Hyun Bin
Call
Message
Application #1
Application #2
Application #3
Application #4
Application #5
Gallery

FIG.10C



12
14
Wed. 15 Oct. 2010
09:00 .....
23:00 .....
402
Seoul
L:21° H:32°
29°c
404
422
Tell me
406
Hyun Bin
Call
Message
408
410
Application #1
Application #2
Application #3
Application #4
Application #5
412
Gallery
414

FIG.10D



12
14
Wed. 15 Oct. 2010
Seoul
L:21° H:32°
29°c
Mon Tue Web Thu Fri Sat
Tell
Hyun Bin
Call
Message
Application #1
Application #2
Application #3
Application #4
Application #5
Gallery
404a
424
406
408
410
412
414

FIG.10E



12
14
Wed. 15 Oct. 2010
09:00 .....
23:00 .....
402
Seoul
L:21° H:32°
29°c
404
Tell me - WG
406
Hyun Bin
Call
Message
h.p:010-1234-5678
office: .....
E-mail: .....
408b
408a
408c
426
410
Application #1
Application #2
Application #3
Application #4
Application #5
412
Gallery
414
408d
408e

FIG.10F



12
14
Wed. 15 Oct. 2010
09:00 .....
23:00 .....
402
Seoul
L:21° H:32°
29°c
404
Tell me - WG
406
Hyun Bin
408b
Call
428
Message
408c
408a
h.p:010-1234-5678
office: .....
E-mail: .....
410
Application #1
Application #2
Application #3
Application #4
Application #5
412
Gallery
414

FIG.10G



12
14
Mypho..
2
80%
408f
408g
Hyun Bin
010-1234-5678
f Since the last time.....
Add call
Dialpad
Call end
Speaker
Mute
Headset
If you fold the phone.
You can use the traditional method calling.
You can use speaker phone if you unfold the phone.

FIG.10H



12
416
14
Wed. 15 Oct. 2010
09:00 .....
23:00 .....
402
Seoul
L:21˚ H:32˚
29˚c
404
Tell me - WG
406
Hyun Bin
Call
Message
408
410
Application #1
Application #2
Application #3
Application #4
Application #5
412
Gallery
414

FIG.11A



12
14
Wed. 15 Oct. 2010
09:00 .....
23:00 .....
402
Seoul
L:21° H:32°
29°c
404
Tell me - WG
406
Hyun Bin
Call
Message
408
410
Application #1
New
Application #2
Application #3
Application #4
Application #5
Application #6
412a
430
Gallery
414

FIG.11B



12
14
402
Wed. 15 Oct. 2010
09:00 .....
23:00 .....
404
Seoul
L:21° H:32°
29°c
406
Tell me - WG
408
Hyun Bin
Call
Message
410
Application #1
New
Application #2
Application #3
Application #4
Application #5
Application #6
Application #7
432
412a
Gallery
414

FIG.11C



12
14
Wed. 15 Oct. 2010
09:00 .....
23:00 .....
Seoul
L:21° H:32°
29°c
Tell me - WG
Hyun Bin
Call
Message
Application #4
Application #5
Application #6
Application #7
Application #8
Application #9
Gallery
402
404
406
408
410
434
434
412b
414

FIG.11D



12
14
Wed. 15 Oct. 2010
09:00 .....
23:00 .....
402
Seoul
L:21° H:32°
29°c
404
Tell me - WG
406
Hyun Bin
Call
Message
408
410
Application #3
Application #4
Application #5
Application #6
Application #7
412c
Gallery
414

FIG.11E



12
14
Wed. 15 Oct. 2010
09:00 .....
23:00 .....
402
Seoul
L:21˚ H:32˚
29˚c
404
Tell me - WG
406
Hyun Bin
Call
Message
408
410
Application #1
Application #2
Application #4
Recent Uploads
Recent Activity
436
412d
Application #5
Gallery
414

FIG.11F



504a
1:28 AM
502
17
504b
504c
6
7
12
2
510
14
Gallery
Image #1
Image #2
Image #3
Image #4
Image #5
Image #6
Image #7
Image #8
Image #9
Image #10
Image #11
Image #12
506a

FIG.12A



1:28 AM
502a
504c
504d
10
504e
6
504b
512
12
7
12
14
Gallery
Image #7
Image #8
Image #9
Image #10
Image #11
Image #12
Image #13
Image #14
Image #15
Image #16
Image #17
Image #18
506b

FIG.12B



1:28 AM
504f
504g
3
8
504d
504c
504a
10
6
12
17
514
502b
14
Gallery
Image #1
Image #2
Image #3
Image #4
Image #11
Image #12
Image #13
Image #14
Image #15
Image #19
Image #20
Image #21
506c

FIG.12C



520a
1:28 AM
504g
3
A Castle
520
Image #2
#4
Image #1
#3
504c
504d
10
6
12
17
504a
502b
14
Gallery
Image #1
Image #2
Image #3
Image #4
Image #11
Image #12
Image #13
Image #14
Image #15
Image #19
Image #20
Image #21
506c

FIG.12D



522
504g
1:28 AM
504f
8
3
Image #22
#23
504a
B Cafe
10
6
12
17
504c
504d
502b
14
Frank...
506f
Image #1
A Castle(17)
Image #11
C Restaurant(6)
Image #19
D Church
Image #13
E Bridge(10)
Image #22
F Cafe(3)
506e

FIG.12E



1:28 AM
504f
504g
3
8
530b
530a
504c
Start
Arrival
10
530
6
17
504a
12
502b
504d
Frank...
14
Image #1
A Castle(17)
Image #11
C Restaurant(6)
Image #19
D Church
Image #13
E Bridge(10)
Image #22
F Cafe(3)
506e

FIG.12F



1:28 AM
532a
532b
3
504g
8
504f
Start
Arrival
532
504c
504a
10
504d
6
17
542
544
502b
12
546
17
Slide Show
Frank...
14
Image #1
A Castle(17)
Image #11
C Restaurant(6)
Image #19
D Church
Image #13
E Bridge(10)
Image #22
F Cafe(3)
506e

FIG.12G



1:28 AM
3
504g
8
504f
504c
504a
540
10
504d
6
17
542
502b
12
17
6
10
Slide Show
546
544
14
Frank...
Image #1
A Castle(17)
Image #11
C Restaurant(6)
Image #19
D Church
Image #13
E Bridge(10)
Image #22
F Cafe(3)
506e

FIG.12H



1:28 AM
Image #3
12
542
17
6
10
Slide Show
548
544
14
Frank...
Image #1
A Castle(17)
Image #11
C Restaurant(6)
Image #19
D Church
Image #13
E Bridge(10)
Image #22
F Cafe(3)
506e

FIG.12I




FIG.13A



12
14
1:28 AM
80%
Application #1
Application #2
610a
612a
604a
606
604b
606
App #1
App #2
App #3
App #4
App #5
App #6
App #7
App #8
610b
612b

FIG.13B



12
14
1:28 AM
80%
610a
Application #1
610a
Application #2
612a
612a
604a
604b
App #3
App #4
App #5
App #6
App #7
App #7
App #8
App #9
App #10
App #11
602a

FIG.13C



12
14
1:28 AM
80%
610a
Application #1
Application #2
612a
604a
602b
604b
App #4
App #5
App #6
App #7
App #8
App #9
App #10
App #11
614b

FIG.13D



12
14
1:28 AM
80%
Application #5
Application #2
614a
612a
604a
604b
App #4
App #5
App #6
App #7
App #8
App #9
App #10
App #11

FIG.13E



12
14
1:28 AM
80%
Application #11
Application #2
616a
612a
604a
602c
604b
App #9
App #10
App #11
App #12
App #13
App #14
App #15
App #16
616b

FIG.13F



12
14
1:28 AM
80%
Application #11
616a
Application #2
612a
602d
604a
612b
604b
App #9
App #10
App #11
App #12
App #13
App #2
App #14
App #15
App #16

FIG.13G



12
14
1:28 AM
80%
Application #11
Application #10
616a
618a
604a
604b
612b
App #9
App #10
App #11
App #12
App #13
App #2
App #14
App #15

FIG.13H



12
14
1:28 AM
80%
Application #11
Application #18
616a
620a
604a
604b
App #12
App #13
App #2
App #14
App #15
App #16
App #17
App #18
600b
602f

FIG.13I




FIG.13J



632
1:28 AM
Life
#5
634e
630
634d
634a
Image #1
634b
#4
634f
634c
#2
#3
12
14
Image #1
Title #1
Caster name #1
time | views
Image #2
Title #2
Caster name #2
time | views
Image #3
Title #3
Caster name #3
time | views
Image #4
Title #4
Caster name #4
time | views
Image #5
Title #5
Caster name #5
time | views
636a
636b
636c
636d
636e
636

FIG.14A



632
1:28 AM
Life
#5
634e
630
634d
634a
Image #1
#4
634f
634c
#2
640
#3
634b
12
14
Image #1
Title #1
Caster name #1
time | views
Image #2
Title #2
Caster name #2
time | views
Image #3
Title #3
Caster name #3
time | views
Image #4
Title #4
Caster name #4
time | views
Image #5
Title #5
Caster name #5
time | views
636a
636b
636c
636d
636e
636

FIG.14B



632
1:28 AM
Life
634h
634e
#7
634g
#8
634a
634d
#5
#1
#4
634b
#2
12
630a
14
#5
Caster name #5
time
views
636e
Image #6
Title #6
Caster name #6
636f
Image #7
Title #7
Caster name #7
636g
636
Image #8
Title #8
Caster name #8
636h
Image #9
Title #9
Caster name #9
636i
640a

FIG.14C



632
1:28 AM
Life
634h
634e
#7
634g
#8
634a
634d
#5
#1
634b
#4
#2
12
630a
14
#5
Caster name #5
time
views
636e
Image #6
Title #6
Caster name #6
636f
Image #7
Title #7
Caster name #7
636g
636
Image #8
Title #8
Caster name #8
636h
640b
Image #9
Title #9
Caster name #9
636i

FIG.14D



1:28 AM
Title #7 Caster name #7
638
Live
Broadcasting
12
14
Discussion
Viewer #1 I simply loved it!! Viva Britney 88
Viewer #2 wooow taht's so cool!
YAY FOR AMAZING BRITNEY-FANS :D
Viewer #3 whoahhhh.....here in philipines you have a lot
642
Enter message here
Send
644a
644
644b

FIG.14E



1:28 AM
Title #7 Caster name #7
638
Live
Broadcasting
12
14
Discussion
Viewer #1 I simply loved it!! Viva Britney 88
Viewer #2 wooow taht's so cool!
YAY FOR AMAZING BRITNEY-FANS :D
Viewer #3 whoahhhh.....here in philipines you have a lot
642
640c
646a
Enter message here
Send
644a
644
644b

FIG.14F



632
1:28 AM
Life
634h
634e
#7
634g
#8
634a
634d
#5
#1
634b
#4
#2
12
630a
14
#5
Caster name #5
time
views
636e
Image #6
Title #6
Caster name #6
time
views
636f
Image #7
Title #7
Caster name #7
time
views
636g
636
Image #8
Title #8
Caster name #8
time
views
636h
Image
Title #9
636i
646b
640d
?
640e
648a
648c
648c
648d
648e
648

FIG.14G



632
1:28 AM
Life
634h
634e
#7
634g
#8
634a
634d
#5
#1
#4
634b
#2
630a
12
14
Title
650a
Please show B-boy events in A park
650b
Category
Entertainment
650
Done
Cancel
650c
640f
650d

FIG.14H



652
1:28 AM
630b
652g
#7
#8
652b
#2
652h
652f
A PARK
652a
#1
#6
#4
#3
652c
#5
12
652d
652e
14
Request
Please show me B-boy events in Tuileries park
View
Ignore
654a
640f
654
654b

FIG.14I



652
1:28 AM
630b
652g
#7
#8
652b
#2
652h
652f
A PARK
652a
#1
#6
#4
#5
#3
652c
12
652d
652e
14
Please show me B-boy events in A park
Reguester Name
Reply
Time
640g
656a
656

FIG.14J



1:28 AM
Screen Layout
Scene Mode
Caster Mode
Mix Mode
660a
660b
660c
660
12
14
Title
Please show B-boy events in A park
662a
Category
Entertainment
662b
662
Done
Cancel
662c
640h
662d

FIG.14K



1:28 AM
Caster's image
Live Broadcasting
664
664b
664a
Discussion
Reguester name : You make an exciting Video. I love it.
Caster name : Thanx~!!
Reguester name : **WAOW**fantastic!<3
Caster name : the 2nd guy it's just a poser...
Viewer #1 : OH. Battle Born.
666
Enter message here
Send
668
668a
668b

FIG.14L



670
670b
Live Broadcasting
A
670a
Caster
Requester
672a
B
Live Broadcasting
672b
672

FIG.14M




FIG.15A




FIG.15B




FIG.15C




FIG.16A




FIG.16B




FIG.16C




FIG.16D



704
2
12
14
4
1:28 AM
80%
To : symoon@gmail.com
How are you?
download photo!
Send
www.google.com
Top Stories
Romney answers rivals' attacks on his Bain Capital record
Mitt Romeny >>
Heather Locklear Hospitalized After 911 Call
Mitt Romeny >>
Mormons feel rooted and happy, but marginalized, poll finds
702

FIG.17A



704
14
4
12
2
702
700
www.google.com
Top Stories
Romney answers rivals' attacks on his Bain Capital record
Mitt Romeny >>
Heather Locklear Hospitalized After 911 Call
Mitt Romeny >>
Mormons feel rooted and happy, but marginalized, poll finds
To : symoon@gmail.com
How are you?
download photo!
Send

FIG.17B



12
1:28 AM
To : symoon@gmail.com
How are you?
Send
download photo!
2
14
4
www.google.com
Top Stories
Romney ans attacks on his Capital record
Mitt Romeny >>
Heather Locklear Hospitalized After 911 Call
Mitt Romeny >>
Mormons feel rooted and happy, but marginalized, poll finds
Object #1
Object #2
Object #3
Object #4
Object #5
704
710
710a
710b
710c
710d
710e
702

FIG.17C



704
710
710a
710b
710c
710d
710e
4
14
12
2
702
700a
706
Object #1
Object #2
Object #3
Object #4
Object #5
www.google.com
Top Stories
Romney ans attacks on his Capital record
Mitt Romeny >>
Heather Locklear Hospitalized After 911 Call
Mitt Romeny >>
Mormons feel rooted and happy, but marginalized, poll finds
1:28 AM
To : symoon@gmail.com
How are you?
Send
download photo!

FIG. 17D



704
710
710a
710b
710c
710f
710d
710e
4
14
12
2
702
1:28 AM
www.google.com
Top Stories
Romney ans attacks on his Capital record
Mitt Romeny >>
Heather Locklear Hospitalized After 911 Call
Mitt Romeny >>
Mormons feel rooted and happy, but marginalized, poll finds
Object #1
Object #2
Object #3
Object #16
Object #4
Object #5
To : symoon@gmail.com
How are you?
Send
download photo!

FIG.17E



4
704
710
710a
710b
710c
710f
700b
710d
710e
Object #1
Object #2
Object #3
Object #16
Object #4
Object #5
Q
14
www.google.com
Top Stories
Romney ans attacks on his Capital record
Mitt Romeny >>
Heather Locklear Hospitalized After 911 Call
Mitt Romeny >>
Mormons feel rooted and happy, but marginalized, poll finds
12
1:28 AM
To : symoon@gmail.com
How are you?
Send
download photo!
2
702

FIG.17F



704
710
710c
710f
710d
710e
710g
710h
4
700c
Object #3
Object #16
Object #4
Object #5
Object #6
Object #7
Q
14
www.google.com
#4
Top Stories
Romney ans attacks on his Capital record
Mitt Romeny >>
Heather Locklear Hospitalized After 911 Call
Mitt Romeny >>
Mormons feel rooted and happy, but marginalized, poll finds
12
1:28 AM
To : symoon@gmail.com
How are you?
download photo!
Send
2
702

FIG.17G



704a
710
710c
710f
710e
710g
710h
710i
4
14
12
2
702
700d
Object #3
Object #16
Object #5
Object #6
Object #7
Object #8
http://mobile.nytimes
The New York
Oct 27,2010, 7:48 AM GMT
Weather 19℃
Search
LATEST NEWS
New Zealand Reaches De
'Hobbit' at Home
Prime Minister John Key
Wednesday the governm
offer additional financial
and clarify local labor law
union concerns.
Saudi Border With Yemen
Inviting for Al Qaeda
1:28 AM
To : symoon@gmail.com
How are you?
download photo!
Send

FIG.17H



712b
14
712a
4
712
704a
12
2
1:28 AM
To : symoon@gmail.com
How are you?
download photo!
Send
All
T
Object #1
Object #2
Object #3
Object #16
Object #5
Object #6
Object #7
Object #8
Object #9
Object #10
Object #11
Object #12
Object #13
Object #14
Object #15
Oct 7:4
LA
q w e r t y u i o p
a s d f g h j k l
z x c v b n m
123/SYM
K/E
.
702

FIG.17I



712b
14
712a
4
712
704a
12
2
712c
700e
702
Y
1:28 AM
To : symoon@gmail.com
How are you?
download photo!
Send
All
T
Object #1
Object #2
Object #3
Object #16
Object #5
Object #6
Object #7
Object #8
Object #9
Object #10
Object #11
Object #12
Object #13
Object #14
Object #15
Oct 7.4
LA
q w e r t y u i o p
a s d f g h j k l
z x c v b n m
123/SYM
K/E

FIG.17J



2
12
704a
712
4
712a
14
1:28 AM
To : symoon@gmail.com
How are you?
702a
Obama.jpg
459KB
710b
714
714a
700f
download photo!
Send
All
T
Object #1
Object #6
Object #11
Object #2
Object #7
Object #12
Object #3
Object #8
Object #13
Object #16
Object #9
Object #14
Object #5
Object #10
Object #15
712b

FIG.17K



2
12
14
4
1:28 AM
80%
802a
804a
Little Prince
802
804
The Art of Living is discussed, along with a system of values, and the train of thought behind them is the unifying element.
and the author was a Frenchman who illustrated the book himself; it was later translated by Kathryn Woods. The Little Prince is still very popular and has now been translated into many languages. Shortly after it was first written, the author died--disappearing together with his plane somewhere over the Mediterranean. This Gift edition contains all the original illustrations, plus some more original drawings that came to light later and have been published here for the first time.
800a

FIG.18A



2
12
14
4
1:28 AM
80%
802b
804b
802
804
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
They never say to you, "What does his voice sound like? What games does he love best? Does he collect butterflies?" Instead, they demand: "How old is he? How many brothers has he? How much does he weigh? How much money does his father make?" Only from these figures do they think they have learned anything about him.
800b
2
4

FIG.18B



2
12
14
4
1:28 AM
80%
802b
802
804b
806
804
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
They never say to you, "What does his voice sound like? What games does he love best? Does he collect butterflies?" Instead, they demand: "How old is he? How many brothers has he? How much does he weigh? How much money does his father make?" Only from these figures do they think they have learned anything about him.

FIG.18C



2
12
14
4
1:28 AM
80%
802b
802
804b
808
808a
804
800c
P105
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
They never say to you, "What does his voice sound like? What games does he love best? Does he collect butterflies?" Instead, they demand: "How old is he? How many brothers has he? How much does he weigh? How much money does his father make?" Only from these figures do they think they have learned anything about him.

FIG.18D



2
12
14
4
1:28 AM
80%
802b
804b
808b
808c
802
804
800d
P51
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
They never say to you, "What does his voice sound like? What games does he love best? Does he collect butterflies?" Instead, they demand: "How old is he? How many brothers has he? How much does he weigh? How much money does his father make?" Only from these figures do they think they have learned anything about him.

FIG.18E



2
12
14
4
1:28 AM
80%
802c
804c
802
Chapter 8
I soon learned to know this flower better. On the little prince's been very simple. They had only one ring of petals; they were a trouble to nobody. One morning they would appear in the grass, and by night they would have faded peacefully away. But one day, from a seed blown from no one knew where, a new flower had come up; and the little prince had watched very closely over this small sprout which was not like any other small sprouts on his planet.
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
810
10/23
810a
804

FIG.18F



2
12
14
4
1:28 AM
80%
802c
804c
Chapter 8
802
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
I soon learned to know this flower better. On the little prince's been very simple. They had only one ring of petals, they were a trouble to nobody. One morning they would appear in the grass, and by night they would have faded peacefully away. But one day, from a seed blown from no one knew where, a new flower had come up; and the little prince had watched very closely over this small sprout which was not like any other small sprouts on his planet.
10/23
810b
800e
804

FIG.18G



2
12
14
4
1:28 AM
80%
802c
804c
802
800f
810b
804
Chapter 8
812
812a
812b
812c
high
color
memo
I soon
flower
been very simple. They had only
one ring of petals, I
they were a trouble to nobody.
One morning they would appear
in the grass, and by night 10/23
they would have faded peacefully
away. But one day, from a seed
blown from no one knew where,
a new flower had come up;
and the little prince had watched
very closely over this small
sprout which was not like any
other small sprouts on his planet.
If I have told you these details
about the asteroid, and made
a note of its number for you,
it is on account of the grownups
and their ways. When you tell
them that you have made
a new friend, they never ask
you any questions about
essential matters.

FIG.18H



2
12
14
4
1:28 AM
80%
802c
804c
802
Chapter 8
I soon learned to know this flower better. On the little prince's been very simple. They had only
Done
They had only ring of petals; they were a trouble to nobody.
814
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
and the little prince had watched very closely over this small sprout which was not like any other small sprouts on his planet.
804

FIG.18I



2
12
14
4
1:28 AM
80%
802c
804c
802
Chapter 8
I soon learned to know this flower better. On the little prince's been very simple. They had only one ring of petals; they were a trouble to nobody. One morning they would appear in the grass, and by night 10/23 they would have faded peacefully away. But one day, from a seed blow a ne and t very sprou other
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
They had only ring of petals; they were a trouble to nobody.
810a
814a
804

FIG.18J



2
12
14
4
1:28 AM
80%
802c
804c
800g
Chapter 8
I soon learned to know this flower better. On the little prince's been very simple. They had only one ring of petals, they were a trouble to nobody. One morning they would appear in the grass, and by night they would have faded peacefully away. But one day, from a seed blow a ne
of petals;
uble to nobody.
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
814a
814b

FIG.18K



2
12
14
4
1:28 AM
80%
802c
804c
814b
814a
800h
Chapter 8
I soon learned to know this flower better. On the little prince's been very simple. They had only one ring of petals; they were a trouble to nobody. One morning they would appear in the grass, and by night they would have faded peacefully away. But one day, from a seed
blow
a ne
and t
very
sprou
other
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
They had only ring of petals; they were a trouble to nobody.

FIG.18L



2
12
14
804c
4
1:28 AM
80%
802c
814b
814a
They had only ring of petals;
they were a trouble to nobody.
If I have told you these details about the asteroid, and made a note of its number for you, it is on account of the grownups and their ways. When you tell them that you have made a new friend, they never ask you any questions about essential matters.
816
800i
2
4

FIG.18M




FIG.18N



2
12
14
4
1:28 AM
80%
802d
804d
And now six years have already gone by . . .
I have never yet told this story.
The companions who met me on my return were well content to see me alive.
800k
I was sad,
but I told them: "I am tired."
Now my sorrow is comforted a little. That is to say-not entirely.
But I know that he did go back to his planet, because I did not find his body at daybreak.
It was not such a heavy body..
and at night I love to listen to the stars. It is like five hundred million little bells . . .
thing . . when I drew the muzzle for the little prince, I forgot to add the leather strap to it.
He will never have been able to fasten it on his sheep.

FIG.18O



2
12
14
4
820
800l
1:28 AM
80%
Chapter 02
i
T
818
802d
818a
818b
804d
And now six years have already gone by . . .
I have never yet told this story.
The companions who met me on my return were well content to see me alive.
I was sad,
but I told them: "I am tired."
Now my sorrow is comforted a little. That is to say-not entirely.
But I know that he did go back to his planet, because I did not find his body at daybreak.
It was not such a heavy body..
and at night I love to listen to the stars. It is like five hundred million little bells . . .
thing . . when I drew the muzzle for the little prince, I forgot to add the leather strap to it.
He will never have been able to fasten it on his sheep.

FIG.18P



902
902b
Conference title #1
Attendance
902a
ME
LEE
Rob
Agnes
Jenni
Date
Tueseday 16 Nov 2010
Start
15:00
End
16:37
File
Dual Display.ppt
900a
Restart
900c
12
Create New Conference
902d
14
Conference Call List
Conference title #1
HOST : #
TIME
Conference title #2
HOST : #
TIME
Conference title #3
HOST : #
TIME
Conference title #4
HOST : #
TIME
904
Keypad
Favorites
Contacts
904a
904b
904c

FIG.19A



906
ME
LEE
Rob
Agnes
Jenni
906a
900b
12
Call Time
00:02:01
906b
Mic Off
End Call
906c
14
ppt
White Board
908a
Comparison of Soil Bacterial Community Structure in Rice Paddy Fields under Different Management Practices using Terminal Restriction Fragment Length Polymorphism (T-RFLP)
908

FIG.19B



906
Contacts
910
Jae
910a
James Brown
900c
910b
Add
Cancel
910c
12
14
ppt
White Board
908a
Comparison of Soil Bacterial Community Structure in Rice Paddy Fields under Different Management Practices using Terminal Restriction Fragment Length Polymorphism (T-RFLP)
908

FIG.19C



906d
ME
LEE
Rob
Agnes
Jenni
Jae
12
Call Time
00:04:25
906b
Mic Off
End Call
906c
14
ppt
White Board
908a
900d
Comparison of Soil Bacterial Community Structure in Rice Paddy Fields under Different Management Practices using Terminal Restriction Fragment Length Polymorphism (T-RFLP)
908

FIG.19D



906d
910f
ME
LEE
Rob
Agnes
Jenni
Jae
12
Call Time
00:04:25
906b
Mic Off
End Call
906c
908b
ppt
White Board
14
912
912b
912a
912c
912d
912e

FIG.19E



906e
900e
4
ME
Jenni
Rob
Agnes
Jae
LEE
ppt
White Board
912f
2
14
Attendance
Share Board
Mic Off
End Call
900f
914a
914b
914c
914d

FIG.19F



906f
14
ME
Jenni
Rob
Agnes
LEE
Jae
+
4
Attendance
Share Board
Mic Off
End Call
914a
914b
914c
914d

FIG.19G



4
1000
Shared screen. Please fold the phone.
14
1002a
1002b
1004
12
A
B
1000a
$ ~
$ ~
Ready
1002e
Ready
C
$ ~
B : ~~
D : ~~
C : ~~
B : ~~
B : ~~
C : ~~
2
1002d
1002
1002c
1004a

FIG.20A



4
1000
Shared screen. Please fold the phone.
14
1002a
1002b
1004
12
Ready
A
B
$ ~
$ ~
Ready
1002e
Ready
Ready
D
C
$ ~
$ ~
B : ~~
D : ~~
C : ~~
B : ~~
B : ~~
C : ~~
D : ~~
2
1002d
1002
1002c
1004a

FIG.20B



1008c
1008a
4
1008
Game start
14
$ 15,925,000
1008d
1008b
1008e
1000b
12
Total : $40,000
Call : $10
1006c
A
$ 15,925,000
1006d
1006e
2
1006a
1006
1006b

FIG.20C



1008e
1008d
14
1008b
$ 15,925,000
1008
1008a
Game start
A
1008c
12
1006c
1006e
1006d
Total : $40,000
Call : $10
A
$ 15,925,000
4
2
1006a
1006
1006b

FIG.20D




FIG.20E



14
1008b
1008e
1008d
$ 15,925,000
1008a
A
1008
12
1006c
1006e
1012a
Total : $40,000
Call : $10
A
$ 15,925,000
1006d
4
1
8
6
Q
2
1006a
1010a
1000c
1010b

FIG.20F



14
1008b
1008e
1008d
Pin
$ 15,925,000
1008a
A
Q
1008
1012a
12
1006c
1006e
1006d
Total : $40,000
Call : $10
A $ 15,925,000
D : ~~
B : ~~
1006a
1
8
6
Q
1010b
1010a
4
2
1010c
Check
Pin
Call
Raise
Half
Fold
X
1000d

FIG.20G



14
1008b
1008e
1008d
Pin
$ 16,550,000
Winner!
A
Flush
1018a
1018b
12
1006c
1006e
Total : $1,040,000
Call : $260,000
A $ 16,550,000
1006d
4
Winner!
1006a
8
6
Flush
1016b
2
1016a

FIG.20H



12
14
1:28 AM
80%
1102
Month
Week
Day
List
January 2009
W S M T W T F S
23 28 29 30 31 1 2 3
24 4 5 6 7 8 9 10
25 11 12 13 14 15 16 17
26 18 19 20 21 22 23 24
27 25 26 27 28 29 30 31
1102a
1106a
1100a
A's Birthday
Mom's Birthday
Midterm Period
Event 4
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
Event 5
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
1104a
Create new Event
1104

FIG.21A



1100d
12
14
1:28 AM
80%
1102
Month
Week
Day
List
Midterm Period
Event 1
07:00AM 12 Jan. 2009 ~ 01:00PM 16 Jan. 2009
1104b
January 2009
W S M T W T F S
23 28 29 30 31 1 2 3
24 4 5 6 7 8 9 10
1018a
1102a
25 11 12 13 14 15 16 17
26 18 19 20 21 22 23 24
27 25 26 27 28 29 30 31
1106b
Create new Event
1104
1104c
Create
Go to
Today
Search
Delete
Setting
Setting
Delete
1104d
1100b
1100c

FIG.21B



12
14
1100e
1:28 AM
80%
1102
Month
Week
Day
List
Midterm Period
Event 1
07:00AM 12 Jan. 2009 ~ 01:00PM 16 Jan. 2009
1104e
3rd week Jan, 2009
S11 M12 T13 W14 T15 F16 S17
7am
8am
9am
10am
11am
12am
1am
2am
3am
1102c
Create new Event
1104

FIG.21C



12
14
1:28 AM
80%
1102
Month
Week
Day
List
Midterm Period
Event 1
07:00AM 12 Jan. 2009 - 01:00PM 16 Jan. 2009
1104f
1100f
Thu, 1/13/2009
1102d
07:00
08:00
09:00
10:00
11:00
12:00
Appointment title
13:00
14:00
15:00
Create new Event
1104

FIG.21D



12
14
1108
1:28 AM
80%
Midterm Period
Event 1
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
Event 1
Tue, 15/8.2009 8:00 AM
~ Tue, 15/8/2009 3:00 PM
My calendar
D-day 14
Palo Alto, Avenue 13th
Stanford
Palo Alto
Stanford University
Jason , Thomas
Create new Event
1104g
1104
1108a
1108b
1108c
1108d

FIG.21E



12
1100g
14
1:28 AM
80%
1102
Month
Week
Day
List
Today, Mon, 1/8/2009
Mom's Birthday
TF meeting
10:30am ~ 11:00am
Touchwiz 3.0 meeting
11:00am ~ 12:00am
Tue, Aug 15, 2009
1102e
A's Birthday
B's Birthday
TF meeting
10:30am ~ 11:00am
Touchwiz 3.0 meeting
11:00am ~ 12:00am
1100h
Event 1
Tue, 15/8.2009 8:00 AM
~ Tue, 15/8/2009 3:00 PM
1108e
My calendar
D-day 14
1108f
Palo Alto, Avenue 13th
Stanford
Palo Alto
Stanford
University
1108g
Jason , Thomas
1108h
1100i
1104c
Create
Go to
Today
Search
Delete
Setting
Edit
Delete
Send via
Search
Send to participants
Export
1104g

FIG.21F



12
14
1:28 AM
80%
1102
Month
Week
Day
List
January 2009
W S M T W T F S
23 28 29 30 31 1 2 3
24 4 5 6 7 8 9 10
25 11 12 13 14 15 16 17
26 18 19 20 21 22 23 24
27 25 26 27 28 29 30 31
1102a
A's Birthday
Mom's Birthday
Midterm Period
Event 4
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
Event 5
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
1104a
1106a
1100j-1
1100j-2
Create new Event
1104
1100j-3
1100j-4
1104c
Create
Go to
Today
Search
Delete
Setting

FIG.21G



12
14
1:28 AM
80%
Create event
Event
Event name
From
To
All day
Calendar
My calendar
Location
Event Location
Map
Participants
Participants
Alarm
None
Repeat
One time event
Description
Event description
Save
Cancel
1110a
1110b

FIG.21H



12
14
1:28 AM
80%
Create event
Event
Event name
From
Tue, 13 Jan, 2009
To
Tue, 13 Jan, 2009
All day
Calendar
My calendar
Location
Event Location
Map
Participants
Participants
Alarm
None
Repeat
One time event
Description
Event description
Save
Cancel
1110c
1110b

FIG.21I



12
14
1:28 AM
80%
1102
Month
Week
Day
List
January 2009
W S M T W T F S
23 28 29 30 31 1 2 3
24 4 5 6 7 8 9 10
25 11 12 13 14 15 16 17
26 18 19 20 21 22 23 24
27 25 26 27 28 29 30 31
1102a
A's Birthday
Mom's Birthday
Midterm Period
Event 4
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
Event 5
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
1104a
Create new Event
1104
1104c
Create
Go to
Today
Dual Zoom
Search
Delete
Setting
1120
1120a

FIG.21J



12
14
1:28 AM
Delete
All this month
New year's Day
Mom's Birthday
Midterm period
A's Birthday
Mom's Birthday
Midterm Period
1112a
1120c
1120b
1112b
Delete
Cancel
80%
A's Birthday
Mom's Birthday
Midterm Period
Event 4
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
Event 5
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
1104a
Create new Event
1104

FIG.21K



12
14
1:28 AM
80%
1102
Month
Week
Day
List
January 2009
W S M T W T F S
23 28 29 30 31 1 2 3
24 4 5 6 7 8 9 10
25 11 12 13 14 15 16 17
26 18 19 20 21 22 23 24
27 25 26 27 28 29 30 31
1102a
1106a
A's Birthday
Mom's Birthday
Midterm Period
Event 4
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
Event 5
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
1104h
Create new Event
1104

FIG.21L



12
14
1:28 AM
80%
1102
Month
Week
Day
List
1102a
January 2009
W S M T W T F S
23 28 29 30 31 1 2 3
24 4 5 6 7 8 9 10
25 11 12 13 14 15 16 17
26 18 19 20 21 22 23 24
27 25 26 27 28 29 30 31
1106a
A's Birthday
Mom's Birthday
Midterm Period
Event 4
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
Event 5
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
1104a
1104
Setting
Delete
1104d
1120d
1120e

FIG.21M



12
14
1:28 AM
80%
1102
Month
Week
Day
List
January 2009
W S M T W T F S
23 28 29 30 31 1 2 3
24 4 5 6 7 8 9 10
25 11 12 13 14 15 16 17
26 18 19 20 21 22 23 24
27 25 26 27 28 29 30 31
1102a
1106a
Delete
All this day
New year's Day
Mom's Birthday
Midterm period
Event 4
Event 5
1112c
1120f
1120g
1112d
Delete
Cancel

FIG.21N



12
14
1:28 AM
80%
1102
Month
Week
Day
List
January 2009
W S M T W T F S
23 28 29 30 31 1 2 3
24 4 5 6 7 8 9 10
25 11 12 13 14 15 16 17
26 18 19 20 21 22 23 24
27 25 26 27 28 29 30 31
1102a
1106a
A's Birthday
Mom's Birthday
Event 4
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
Event 5
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
1104i
Create new Event
1104

FIG.21O



12
14
1:28 AM
80%
1202
Month
Week
Day
List
January 2009
W S M T W T F S
23 28 29 30 31 1 2 3
24 4 5 6 7 8 9 10
25 11 12 13 14 15 16 17
26 18 19 20 21 22 23 24
27 25 26 27 28 29 30 31
1202a
A's Birthday
Mom's Birthday
Midterm Period
Event 4
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
Event 5
07:00AM 12 Jan. 2009 ~ 01:00PM 15 Jan. 2009
1206a
1200a
1204a
Create new Event
1200a
1200b
1202b
Create
Go to
Today
Dual Zoom
1200c
Search
Delete
Setting

FIG.22A



12
14
1:28 AM
80%
January 2009
Create new Event
1206
W S M T
W T F S
23 28 29 30
31 1 2 3
24 4 5 6
7 8 9 10
25 11 12 13
14 15 16 17
B's Birthday
Alice Birthday
26 18 19 20
21 22 23 24
27 25 A's Birthday 26 27
28 29 30 31
1208a
1208b
1204b
1200d

FIG.22B



12
14
1:28 AM
80%
1202
Month
Week
Day
List
Midterm Period
Event 1
07:00AM 12 Jan. 2009 ~ 01:00PM 16 Jan. 2009
1206b
3rd week Jan, 2009
S11 M12 T13 W14 T15 F16 S17
7am
8am
9am
10am
11am
12am
1am
2am
3am
1202c
Create new Event
1206
1200e

FIG.22C



12
14
1:28 AM
80%
January 2009
Create new Event
1206
Son
Mon
Tue
Wed
Thu
Fri
Sat
8am
9am
10am
11am
12pm
1pm
2pm
3pm
Meeting
Seminar
B's Birthday
1208c
1208d
1200f

FIG.22D



12
14
1:28 AM
80%
January 2009
Create new Event
1206
W S M T
W T F S
23 28 29 30
31 1 2 3
24 4 5 6
7 8 9 10
1200g
25 11 12 B's Birthday 13
14 15 Alice Birthday 16 17
1204c
26 18 19 20
21 22 23 24
27 25 A's Birthday 26 27
28 29 30 31
1208a
1208b

FIG.22E



12
14
1:28 AM
80%
January 2009
Create new Event
1206
W
S
M
T
W
Alice Birthday
Tue, 15/1/2009 8:00 AM
~Tue, 15/1/2009 3:00 PM
Location : Mars
1210a
Stanford
Palo Alto
1208a
1208b
23
28
29
30
24
4
5
6
25
11
12
B's Birthday
13
14
15
Alice Birthday
16
17
1204e
26
18
19
20
21
22
23
24
1204d
27
25
A's Birthday
26
27
28
29
30
31
1200h
1200i

FIG.22F



12
14
1:28 AM
80%
January 2009
Create new Event
1206
W S M T
W T F S
23 28 29 30
31 1 2 3
24 4 5 6
7 8 9 10
25 11 12 B's Birthday 13
14 15 Alice Birthday 16 17
26 18 19 20
21 22 23 1204f 24
27 25 A's Birthday 26 27
28 29 30 31
1208a
1208b

FIG.22G



12
14
1:28 AM
80%
2009월 1월
Create new Event
1206
W S M T
W T F S
23 28 29 30
31 1 2 3
24 4 5 6
1200k-2
7 8 9 10
25 11 12
B's Birthday
13
14 15
Alice Birthday
16
1204c
17
1208a
1208b
26 18
A's Birthday
19 20
21 22 23 24
28 29 30 31
1208e
Create
Go to
Today
Search
Delete
Setting
1200k-1
1200j

FIG.22H



12
14
1:28 AM
Create event
Event
Event name
From
To
All day
Calendar
My calendar
80%
Location
Event Location
Map
Participants
Participants
Alarm
None
Repeat
One time event
Description
Event description
Save
Cancel
1210a
1210b

FIG.22I


12
14
1:28 AM
80%
Create event
Event
Event name
From
Tue, 13 Jan, 2009
To
Tue, 13 Jan, 2009
All day
Calendar
My calendar
Location
Event Location
Map
Participants
Participants
Alarm
None
Repeat
One time event
Description
Event description
Save
Cancel
1210c
1210b

FIG.22J



12
14
1:28 AM
80%
2009월 1월
Create new Event
1206
W
S
M
T
W
T
F
S
23
28
29
30
31
1
2
3
24
4
5
6
7
8
9
10
25
11
12
B's Birthday
13
14
15
Alice Birthday
16
17
26
18
A's Birthday
19
20
21
22
23
24
28
29
30
31
Create
Go to
Today
Search
Delete
Setting
1208a
1208b
1208e
1214a
1214b

FIG.22K



12
14
1:28 AM
80%
Delete
All this month
New year's Day
Mom's Birthday
Midterm period
A's Birthday
Alice Birthday
B's Birthday
1212a
1214d
1214c
1212b
Delete
Cancel
Create new Event
1206
W
T
F
S
31
1
2
3
7
8
9
10
14
15
Alice
Birthday
16
17
21
22
23
24
28
29
30
31
1208b

FIG.22L



12
14
1:28 AM
80%
2009월 1월
Create new Event
1206
W S M T
W T F S
23 28 29 30
31 1 2 3
24 4 5 6
7 8 9 10
25 11 12 13
14 15 Alice Birthday 16 17
26 18 19 20
21 22 23 24
27 25 A's Birthday 26 27
28 29 30 31
1208a
1208b

FIG.22M



2
12
14
4
1:28 AM
80%
Home Screen 1page
App A
1302a
1302b
1302
1300a

FIG.23A



2
12
14
4
1:28 AM
80%
1304f
Keypad
Logs
Favorites
Contacts
1304a
123456789
Benny Bena
123456789
19
1304
1304b
1 ∞
2 ABC
3 DEF
4 GHI
5 JKL
6 MNO
7 PQRS
8 TUV
9 WXYZ
*
0 +
#
Call
Video Call
Messa ge
X
App A
1300b
1304c
1304d
1304e
1302b

FIG.23B



2
12
14
4
1:28 AM
80%
Dialing...
Caller Name
Phone Number
1306
1306a
f
Vacation with snow ...
Add call
Dialpad
Call end
Speaker
Mute
Headset
You con call with speaker phone.
If You want private call.
Fold the phone
1302c
1306b

FIG.23C



1300b
2
12
1308a
14
4
1:28 AM
80%
Caller Name
Phone Number
1308
1308b
Hold
00:00:01
Add call
Dialpad
Call end
Speaker
Mute
Headset
App A
1302b
1308c

FIG.23D



2
1308a
12
14
4
1:28 AM
Caller Name
Phone Number
1308b
1308
Hold
00:00:05
Add call
Dialpad
Call end
Speaker
Mute
Headset
1308c

FIG.23E



2
12
14
4
1:28 AM
80%
Home Screen 1page
Home Screen 2page
1302a
1302d
1302
1300c

FIG.23F



2
12
14
1302d
4
1:28 AM
80%
1304f
Keypad
Logs
Favorites
Contacts
1304a
123456789
Benny Bena
123456789
19
1304
1304b
1 ∞
2 ABC
3 DEF
4 GHI
5 JKL
6 MNO
7 PQRS
8 TUV
9 WXYZ
*
0 +
#
Call
Video Call
Messa ge
X
Home Screen 2page
Phone
Contacts
Message
Main Menu
1300d
1304c
1304d
1304e
1302

FIG.23G



2
12
14
4
1:28 AM
80%
Dialing...
Caller Name
Phone Number
1306
1306a
f
Vacation with snow ...
Add call
Dialpad
Call end
Speaker
Mute
Headset
You con call with speaker phone.
If You want private call, Fold the phone.
1302c
Phone
Contacts
Message
Main Menu
1302
1306b

FIG.23H



1300e
2
12
1308a
14
4
1:28 AM
80%
Caller Name
Phone Number
1308b
1308
Hold
00:00:01
Add call
Dialpad
Call end
Speaker
Mute
Headset
Home
Screen
2page
1302d
Phone
Contacts
Message
Main Menu
1302
1308c

FIG.23I



2
12
1308a
1:28 AM
Caller Name
Phone Number
1300f
1308
1300f
Hold
00:00:01
Add call
Dialpad
Call end
Speaker
Mute
Headset
1308c
12
1302d
2
1:28 AM
Home
Screen
2page
Phone
Contacts
Message
Main
Menu
1302e

FIG.23J



2
12
14
4
1:28 AM
Tommy
tonight? (...more)
10:30AM
1322a
Iron man
Iron man2 was open yesterday. Would you like to go with me??
10:39AM
Enter message here
Send
Gallery
Album 1
1322b
thumbnail #1
thumbnail #2
thumbnail #3
thumbnail #4
thumbnail #5
thumbnail #6
thumbnail #7
thumbnail #8
thumbnail #9
thumbnail #10
thumbnail #11
thumbnail #12

FIG.23K



2
12
14
4
1:28 AM
Voice call
Caller Name
Phone Number
1324a
f
Vacation with snow ...
1324b
1310a
Reject with message
1324
1324c
Gallery
Album 1
1322b
You con call with speaker phone.
If You want private call, Fold the phone.
1326

FIG.23L



2
12
1324a
14
4
1:28 AM
Gallery
Album 1
1322b
thumbnail #1
thumbnail #2
thumbnail #3
thumbnail #4
thumbnail #5
thumbnail #6
thumbnail #7
thumbnail #8
thumbnail #9
thumbnail #10
thumbnail #11
thumbnail #12
1324b
Caller Name
Phone Number
1320b
1324
Hold
00:00:01
Add call
Dialpad
Call end
Speaker
Mute
Headset
1324c

FIG.23M



2
12
14
4
Gallery
Album 1
1326a
thumbnail #1
thumbnail #2
thumbnail #3
thumbnail #4
thumbnail #5
thumbnail #6
thumbnail #7
thumbnail #8
thumbnail #9
thumbnail #10
thumbnail #11
thumbnail #12
55/128
+
-
1326b
Image #5
Slide show
2 Image view

FIG.23N



2
12
14
1326b
4
1:28 AM
55/128
Voice call
Caller Name
Phone Number
1328a
f
Vacation with snow ...
1328b
1320c
Reject with message
1328
1328c
You can call with speaker phone.
If You want private call, Fold the phone.
Image #6
Slide show
2 Image view
1330

FIG.23O



2
12
1332a
14
4
1:28 AM
55/128
1326b
1332
1332b
Caller Name
Phone Number
1320d
Image
#5
Hold
00:00:01
Add call
Dialpad
Call end
Speaker
Mute
Headset
Slide show
2 Image view
1332c

FIG.23P



2
12
14
4
1:28 AM
To: Tommy
1402b
1402a
I L I
Send
1402c
KEY PAD
80%
Tommy
tonight? (...more)
10:30AM
1402d
Iron man
Iron man2 was open yesterday. Would you like to go with me??
10:39AM

FIG.24A



2
12
14
4
1:28 AM
80%
Voice call
Caller Name
Phone Number
1404
1404a
f
Vacation with snow ...
1404b
1400a
Reject with message
1404c
1402d
You con call with speaker phone.
If You want private call.
Fold the phone
1402e

FIG.24B



2
1406a
12
14
4
1:28 AM
80%
Voice call
Caller Name
Phone Number
To: Tommy
1402b
1402a
Send
1406b
1400b
1406
Hold
00:00:01
Add call
Dialpad
Call end
Speaker
Mute
Headset
KEY PAD
1402c
1406c

FIG.24C



2
12
14
4
Gallery
Album 1
1410a
thumbnail #1
thumbnail #2
thumbnail #3
thumbnail #4
thumbnail #5
thumbnail #6
thumbnail #7
thumbnail #8
thumbnail #9
thumbnail #10
thumbnail #11
thumbnail #12
55/128
+
-
1410b
Image #5
Slide show
2 Image view

FIG.24D



2
12
1412a
14
1410b
4
55/128
+
-
Voice call
Caller Name
Phone Number
You can call with speaker phone.
If You want private call, Fold the phone.
1412
1414
f
Vacation with snow ...
1412b
1400c
Reject with message
Slide show
2 Image view
1412c

FIG.24E



2
1416a
12
14
4
1:28 AM
55/128
+
-
Voice call
1410b
Caller Name
Phone Number
1416b
1416
Image
#5
Hold
00:00:01
Add call
Dialpad
Call end
Speaker
Mute
Headset
Slide show
2 Image view
1416c
1400d

FIG.24F



2
1416a
12
14
4
1:28 AM
80%
Voice call
Caller Name
Phone Number
1416b
1400e
1416
Hold
00:00:01
Add call
Dialpad
Call end
Speaker
Mute
Headset
1418a
Home
Screen
1page
1418b
1416c

FIG.24G



2
12
14
4
55/128
+
-
1410b
Image
#5
Slide show
2 Image view
80%
1418a
Home
Screen
1page
1418b

FIG.24H



2
12
1404a
14
1410b
4
80%
Voice call
Caller Name
Phone Number
You con call with speaker phone.
If You want private call. Fold the phone
1404
1406
f
Vacation with snow ...
1400f
1404b
Reject with message
1404c

FIG.24I



2
12
14
4
1:28 AM
Reject with message
I'll call later
Send
I'm in meeting
Send
I'm in class now
Send
In a cinema
Send
While driving
Send
1420
80%
To: Caller Name
1422a
I'm busy
Send
1422c
1422b
KEY PAD

FIG.24J



2
1406a
12
14
4
1:28 AM
Voice call
AAA
Phone Number
1406b
1406
Hold
00:03:01
Add call
Dialpad
Call end
Speaker
Mute
Headset
55/128
1410b
Image
#5
Slide show
2 Image view
1416c

FIG.24K



2
1426a
12
14
4
1:28 AM
55/128
+
-
Voice call
BBB
01788889999
1328a
1410b
1426
f
Vacation with snow ...
1426b
Image
#5
1400g
Reject with message
Slide show
2 Image view
1426c

FIG.24L



2
1426a
12
14
4
1:28 AM
55/128
Voice call
BBB
01788889999
1410b
Image
#5
1426
1400h
1428a
Hold AAA
End AAA
1428b
1428
Reject with message
Slide show
2 Image view
1426c

FIG.24M



2
12
14
4
1:28 AM
BBB
01788889999
00:00:01
AAA
Phone Number
00:00:01
1430a
Swap
Merge
1430b
1430c
1430
Add call
Dialpad
Call end
Speaker
Mute
Headset
1430d
55/128
+
-
1410b
Image
#5
Slide show
2 Image view

FIG.24N



2
12
Gallery
Album 1
1432
thumbnail #1
thumbnail #2
thumbnail #3
thumbnail #4
thumbnail #5
thumbnail #6
thumbnail #7
thumbnail #8
thumbnail #9
thumbnail #10
thumbnail #11
thumbnail #12

FIG.24O



2
1434a
12
1400i
1:28 AM
Voice call
BBB
01788889999
1434
f
Vacation with snow ...
1434b
Reject with message
1434c

FIG.24P



4
14
1400j
1:28 AM
Reject with message
Create new message
I'll call later
Send
I'm in meeting
Send
I'm in class now
Send
In a cinema
Send
While driving
Send
1436

FIG.24Q



2
12
14
4
1:28 AM
80%
Reject with message
I'll call later
Send
I'm in meeting
Send
I'm in class now
Send
In a cinema
Send
While driving
Send
To: Caller Name
1438a
I'm busy
Send
KEY PAD
1438b
1436

FIG.24R



2
12
24
14
4
1502b
0.0
10m
150
1502a
5
300
1502b
Please select camera mode
1504
Basic Camera
Self Camera
1504a
1504b
Dual Camera
Baby Camera
1504c
1504d

FIG.25A




FIG.25B




FIG.25C



2
12
24
14
4
1502b
0.0
10m
150
1502a
5
300
1502b
Please select camera mode
1504
Basic Camera
Self Camera
1504a
1504b
Dual Camera
Baby Camera
1504c
1504d

FIG.25D



1500b
4
2
12
24
14
1502b
Turn off
10m
150
0.0
5
300
1502a
1502b
2
1500b
4

FIG.25E




FIG.25F



2
12
24
14
4
1502b
0.0
1502a
10m
150
5
300
1502b
Please select camera mode
1504
Basic Camera
Self Camera
1504a
1504b
Dual Camera
Baby Camera
1504c
1504d

FIG.25G



1500c
4
2
12
24
14
1502c
1502b
0.0
1502a
10m
150
5
300
1502b
2
1500c
4

FIG.25H




FIG.25I



2
12
24
14
4
1502b
0.0
10m
150
1502a
5
300
1502b
Please select camera mode
1504
Basic Camera
Self Camera
1504a
1504b
Dual Camera
Baby Camera
1504c
1504d

FIG.25J



1500d
4
14
24
2
12
1502d
1502b
0.0
1502a
10m
150
5
300
1502b
2
1500d
4

FIG.25K




FIG.25L



2
12
1508
1510a
24
14
4
1502b
1502a
1502b
Basic Camera
0.0
10m
150
5
300
Turn off

FIG.26A



2
12
1508
1510a
24
14
4
1502b
0.0
Basic Camera
1512
Camera Mode
1512a
Basic Camera
1512b
Self Camera
1510b
1512c
Dual Camera
1512d
Baby Camera
1502a
300
1502b
Turn off

FIG.26B




FIG.26C



2
12
1508
1510a
24
14
4
1502b
1502a
1502b
Basic Camera
0.0
10m
150
5
300
1510c

FIG.26D



2
12
1502b
0.0
1502a
10m
150
5
300
1502b
24
14
1504
4
Please select camera mode
1510d
Basic Camera
Self Camera
1504a
1504b
Dual Camera
Baby Camera
1504c
1504d

FIG.26E




FIG.26F



2
1504
12
24
14
4
Please select camera mode
Basic Camera
Self Camera
1504a
1504b
Dual Camera
Baby Camera
1504c
1504d
+/-
0.0
1502b
10m
150
5
300
1502a
1502b

FIG.26G



2
12
24
14
4
1502b
0.0
10m
150
1502a
1514
5
300
1502b
Turn off
1516
1510f

FIG.26H



2
12
24
14
4
1502b
0.0
10m
150
1502a
1514
1518a
5
1518b
300
1502b
1502e

FIG.26I



2
12
1502b
+/-
0.0
1502a
10m
150
1514
5
1518a
1
300
1502b
24
14
4
1518b
1
1502e

FIG.26J




2
12
24
14
4
1502b
0.0
10m
150
1502a
1514
5
1518b
300
1502b
1502f
1502e

FIG.26K






FIG.27A




FIG.27B





FIG.27C


2
12
14
4
1:28 AM
80%
1604a
Playlist
Song title 1
Song title 2
Song title 3
Song title 4
Song title 5
Song title 6
Song title 7
Song title 8
Song title - Artist
1604




60°
2
4
1600b

FIG.27D







FIG.27E






FIG.27F




FIG.27G




FIG.27H



1604
1:28 AM
Jack Johnson
Better together
In Between
Dreams
5.1ch
List
4
14
12
2
1602
4
2

FIG.27I




FIG.27J




FIG.27K



1602
2
12
2
80%
Jack Johnson
Better together
In Between
Dreams
5.1ch
14
List
4
4
1604

FIG.27L




FIG.27M



80%
In between dreams
Jack Johnson
Better together
Never know
Banana Pancakes
1:28 AM
Jack Johnson
Better together
In Between
Dreams
5.1ch
List
4
1600f
14
12
2
1604
4
1600f
2

FIG.27N



4
Turn off
14
12
1:28 AM
Jack Johnson
Better together
In Between
Dreams
5.1ch
List
2
4
2
1604

FIG.27O



1604
4
1:28 AM
Jack Johnson
Better together
In Between
Dreams
5.1ch
14
List
12
2
1602
4
1600g
2

FIG.27P




FIG.27Q

PORTABLE DEVICE COMPRISING A TOUCH-SCREEN DISPLAY, AND METHOD FOR CONTROLLING SAME

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a National Stage of International Application No. PCT/KR2012/000888, filed on Feb. 7, 2012, and claims priority from U.S. Provisional Application No. 61/441,491, filed on Feb. 10, 2011, the disclosure of which is incorporated herein in its entirety by reference.

BACKGROUND

[0002] 1. Field

[0003] Methods and apparatuses consistent with exemplary embodiments relate to a portable device, and more particularly, to a portable device displaying a plurality of task screens through a touch screen display and executing an application according to a touch gesture of a user detected on the plurality of task screens, and a method of controlling the same.

[0004] 2. Description of Related Art

[0005] An electronic device directly controlled by a user includes at least one display device, and the user controls the electronic device through an input device while viewing an operation of an application executed on the display device of the electronic device. Particularly, a portable electronic device (hereinafter, referred to as a portable device) manufactured to be carried by the user is developed to include a display device using a user interface in a form of a touch screen due to a limited size thereof in many cases.

[0006] A Graphical User Interface (GUI) used in a touch screen display should provide an optimized form to allow the user to intuitively recognize an operation of a running application and also allow the user to more easily, quickly, and variously control the portable device and the running application. Accordingly, various user interfaces have been developed according to forms of the applied application or display device.

[0007] Particularly, as a Central Processor Unit (CPU) and a software technology are developed, the portable device can provide a plurality of task screens displaying one or a plurality of applications. The plurality of task screens may be provided through one or more touch screens which are physically or graphically divided. Accordingly, the portable device providing the plurality of task screens requires a graphic user interface for a touch screen which can allow the user to more intuitively and conveniently use the portable device.

[0008] Further, a more advanced portable device can detect a touch gesture, a motion or a pose of the portable device, and a motion or a shape of the user as an input, as well as an input of a hard or soft key. Accordingly, a user interface for allowing the user to more conveniently use the portable device through various inputs is also required.

SUMMARY

[0009] One or more exemplary embodiments provide a portable device including a touch screen display and a control method thereof.

[0010] One or more exemplary embodiments also provide a portable device including a plurality of touch screen displays providing a plurality of task screens by one or a plurality of applications, and a control method thereof.

[0011] One or more exemplary embodiments also provide a portable device which detects a touch gesture of a user from a plurality of connected touch screen displays and displays information in response to the detection, and a control method thereof.

[0012] One or more exemplary embodiments also provide a portable device which provides an optimized user interface corresponding to a portrait view mode or a landscape view mode to at least one touch screen display, and a control method thereof.

[0013] One or more exemplary embodiments also provide a portable device which provides a plurality of task screens for a plurality of applications or one application to at least one touch screen display, and a control method thereof.

[0014] One or more exemplary embodiments also provide a portable device which displays some information on a plurality of applications to be partially hidden in a form of received cards, and expands more detailed information on a corresponding application according to a touch motion of the user and displays the expanded information, and a control method thereof.

[0015] One or more exemplary embodiments also provide a portable device which displays maps according to a map application in a first touch screen display and displays at least one image corresponding to a position or path selected by a touch gesture of the user on the maps in a second touch screen display, and a control method thereof.

[0016] One or more exemplary embodiments also provide a portable device which displays a task management area listing a shortcut icon of at least one application in a designated position and displays an application selected by a touch gesture of the user in one of a plurality of touch screen displays, and a control method thereof.

[0017] One or more exemplary embodiments also provide a portable device which displays positions of a plurality of personal broadcasters in a map of a first touch screen display, lists and displays simple information on the personal broadcasters in a second touch screen display, and makes a request for broadcasting to a desired personal broadcaster in response to a touch gesture of the user, and a control method thereof.

[0018] One or more exemplary embodiments also provide a portable device which displays a clipboard in a designated position in response to folding of dual displays connected by a hinge or bending of a flexible display, and a control method thereof.

[0019] One or more exemplary embodiments also provide a portable device which sets a bookmark of an e-book displayed in a display, or moves pages and then displays the e-book in response to folding of dual displays connected by a hinge or bending of a flexible display, and a control method thereof.

[0020] One or more exemplary embodiments also provide a portable device which provides a video for a video conference to a first touch screen display and displays a document file or a white board shared by participants of the video conference in a second touch screen display, and a control method thereof.

[0021] One or more exemplary embodiments also provide a portable device which provides a game interface for a first user to a first touch screen display and displays game information for another user in a second touch screen display, and a control method thereof.

[0022] One or more exemplary embodiments also provide a portable device which provides a user interface for a calendar application through a dual touch screen display, and a control method thereof.

[0023] One or more exemplary embodiments also provide a portable device which provides a user interface for a call application through a dual touch screen display, and a control method thereof.

[0024] One or more exemplary embodiments also provide a portable device which provides a user interface for a camera application through a dual touch screen display, and a control method thereof.

[0025] One or more exemplary embodiments also provide a portable device which controls a view mode through a motion of the portable device in a dual touch screen display, and a control method thereof.

[0026] One or more exemplary embodiments also provide a portable device for navigating information displayed in two touch screens of a dual touch screen display, and a control method thereof.

[0027] One or more exemplary embodiments also provide a portable device for modifying a home screen by using lists displayed in a sub touch screen in a dual touch screen display, and a control method thereof.

[0028] One or more exemplary embodiments also provide a portable device for displaying a virtual keypad by using a touch screen located in a lower part in a landscape view mode of a dual touch screen display, and a control method thereof.

[0029] In accordance with an aspect of an exemplary embodiment, there is provided a method of controlling a portable device including at least one foldable panel and first and second touch screens arranged on the at least one foldable panel, the method including displaying, on the first touch screen, a first page including at least one of a widget area designated as a home screen and an icon related to at least one application, and a dock area including a call icon of a call application, displaying, on the second touch screen, first information in a state where a first panel of the at least one foldable panel includes the first touch screen, a second panel of the at least one foldable panel includes the second touch screen, and the first panel and second panel are unfolded, detecting a first tap gesture that selects the call icon. The method also includes, in response to a detection of the first tap gesture, replacing the first page and the dock area displayed on the first touch screen with an outgoing call screen provided by the call application by displaying the outgoing call screen on the first touch screen, wherein the outgoing call screen includes at least one of a number display area, a keypad area, a call key, a video call key, and a message sending key, and the second touch screen maintains the first information while the outgoing call screen is displayed on the first touch screen, receiving a phone number input through the keypad area and detecting a second tap gesture from the call key, replacing the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen on the first touch screen in response to a detection of the second tap gesture, and displaying, on the second touch screen, a guide message screen indicating to fold the portable device for a call, wherein the dialing screen includes a call participant identification area indicating a counterpart call participant and a function key area providing mid-call functions, replacing the dialing screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the call being connected with the counterpart call participant, and removing the guide message screen displayed on the second touch screen, and displaying the first information, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0030] In accordance with an aspect of another exemplary embodiment, there is provided a method of controlling a portable device including a first touch screen and a second touch screen, the method including, displaying first information on the first touch screen and detecting an outgoing call request while second information is displayed on the second touch screen, replacing the first information displayed on the first touch screen with an outgoing call screen by displaying the outgoing call screen in response to the detecting the outgoing call request, wherein the outgoing call screen includes at least one of a number display area displaying a dialed number, a call key, a video call key, and a message sending key, and the second touch screen maintains the second information while the outgoing call screen is displayed on the first touch screen, receiving a phone number input through the keypad area and detecting a first tap gesture from the call key, replacing the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen in response to the detecting the first tap gesture, wherein the dialing screen includes a call participant identification area indicating a counterpart call participant corresponding to the input phone number and a function key area providing mid-call functions. The method also includes deactivating the second information displayed on the second touch screen and displaying, on the second touch screen, a guide message indicating to fold the portable device for the call while the outgoing call screen is displayed, replacing the dialing screen on the first touch screen with a mid-call screen by displaying the mid-call screen in response to the call being connected with the counterpart call participant, and removing the guide message displayed on the second touch screen, and displaying the first information, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0031] In accordance with an aspect of another exemplary embodiment, a portable device including at least one foldable panel, a first touch screen and a second touch screen arranged on the at least one foldable panel, and at least one processor that is configured to: display, on the first touch screen, a first page including at least one of a widget area designated as a home screen and an icon related to at least one application, and a dock area including a call icon of a call application, display, on the second touch screen, first information in a state where a first panel of the at least one foldable panel includes the first touch screen, a second panel of the at least one foldable panel includes the second touch screen, and the first panel and second panel are unfolded, detect a first tap gesture that selects the call icon, and replace the first page and the dock area displayed on the first touch screen with an outgoing call screen provided by the call application by displaying the outgoing call screen on the first touch screen in response to a detection of the first tap gesture, wherein the outgoing call screen includes at least one of a number display area, a keypad area, a call key, a video call key, and a message sending key, and the second touch screen maintains the first information while the outgoing call screen is displayed in the first touch screen. The processor is also configured to receive a phone

number input through the keypad area and detect a second tap gesture from the call key, replace the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen on the first touch screen in response to the detection of the second tap gesture, and display, on the second touch screen, a guide message indicating to fold the portable device for a call, wherein the dialing screen includes a call participant identification area indicating a counterpart call participant and a function key area providing mid-call functions, replace the dialing screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the call being connected with the counterpart call participant, and remove the guide message displayed on the second touch screen, and display the first information, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0032] In accordance with an aspect of another exemplary embodiment, there is provided a portable device including a first touch screen and a second touch screen, and at least one processor that is configured to display first information on the first touch screen and detect an outgoing call request while second information is displayed on the second touch screen, replace the first information displayed on the first touch screen with an outgoing call screen by displaying the outgoing call screen on the first touch screen in response to the detection of the outgoing call request, wherein the outgoing call screen includes at least one of a number display area displaying a dialed number, a call key, a video call key, and a message sending key, and the second touch screen maintains the second information while the outgoing call screen is displayed on the first touch screen, receive a phone number input through the keypad area and detect a first tap gesture from the call key, and replace the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen on the first touch screen in response to the detection of the first tap gesture, and display, on the second touch screen, a guide message indicating to fold the portable device for a call, wherein the dialing screen includes a call participant identification area indicating a counterpart call participant corresponding to the input phone number and a function key area providing mid-call functions. The processor is also configured to replace the dialing screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the call being connected with the counterpart call participant, and remove the guide message on the second touch screen, and displaying the first information, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0033] In accordance with an aspect of another exemplary embodiment, there is provided a non-transitory computer-readable medium storing a program executable by a computer to perform a method of controlling a portable device including at least one foldable panel and first and second touch screens arranged on the at least one foldable panel, the method including, displaying, on the first touch screen, a first page including at least one of a widget area designated as a home screen and an icon related to at least one application, and a dock area including a call icon of a call application, displaying, on the second touch screen, first information in a state where a first panel of the at least one foldable panel includes the first touch screen, a second panel of the at least one foldable panel includes the second touch screen, and the first panel and second panel are unfolded, detecting a first tap gesture that selects the call icon, and replacing the first page and the dock area displayed on the first touch screen with an outgoing call screen provided by the call application by displaying the outgoing call screen on the first touch screen in response to the detecting the first tap gesture, wherein the outgoing call screen includes at least one of a number display area, a keypad area, a call key, a video call key, and a message sending key, and the second touch screen maintains the first information while the outgoing call screen is displayed in the first touch screen. The method also includes receiving a phone number input through the keypad area and detecting a second tap gesture from the call key, replacing the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen on the first touch screen in response to the detecting the second tap gesture, and displaying, on the second touch screen, a guide message indicating to fold the portable device for a call, wherein the dialing screen includes a call participant identification area indicating a counterpart call participant and a function key area providing mid-call functions, replacing the dialing screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the call being connected with the counterpart call participant, and removing the guide message displayed on the second touch screen, and displaying the first information, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0034] In accordance with an aspect of another exemplary embodiment, there is provided a non-transitory computer-readable medium storing a program executable by a computerto perform a method of controlling a portable device including a first touch screen and a second touch screen, the method including, displaying first information on the first touch screen and detecting an outgoing call request while second information is displayed on the second touch screen, replacing the first information displayed on the first touch screen with an outgoing call screen by displaying the outgoing call screen in response to the detecting the outgoing call request, wherein the outgoing call screen includes at least one of a number display area displaying a dialed number, a call key, a video call key, and a message sending key, and the second touch screen maintains the second information while the outgoing call screen is displayed on the first touch screen, receiving a phone number through the keypad area and detecting a first tap gesture from the call key, replacing the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen on the first touch screen in response to the detecting the first tap gesture, and display, on the second touch screen, a guide message indicating to fold the portable device for a call, wherein the dialing screen includes a call participant identification area indicating a counterpart call participant corresponding to the input phone number and a function key area providing mid-call functions, replacing the dialing screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the call being connected with the counterpart call participant, and removing the guide message displayed on the second touch screen, and displaying the first information, wherein the mid-

call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0035] In accordance with an aspect of another exemplary embodiment, there is provided a method of controlling a portable device including a first touch screen and a second touch screen arranged on at least one foldable panel, the method including, displaying first information on the first touch screen and detecting a generation of a first incoming call while second information is displayed on the second touch screen in a state where a first panel of the at least one foldable panel includes the first touch screen and a second panel of the at least one foldable panel includes the second touch screen are unfolded, replacing the first information displayed on the first touch screen with a first incoming call screen related to the first incoming call provided by a call application by displaying the first incoming call screen on the first touch screen in response to the generation of the first incoming call, wherein the first incoming call screen includes at least one of a call participant identification area indicating a counterpart call participant, an incoming key, and a rejection message key, deactivating the second information displayed on the second touch screen and displaying a guide message indicating to fold the portable device for a call while displaying the first incoming call screen, detecting a pre-designated first touch gesture from the incoming key within the first incoming call screen, replacing the incoming call screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the detecting the first touch gesture, and removing the guide message displayed the second touch screen, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions, and replacing the mid-call screen displayed on the first touch screen with the first information by displaying the first information on the first touch screen in response to the first incoming call ending.

[0036] In accordance with an aspect of another exemplary embodiment, there is provided a method of controlling a portable device including a first touch screen and a second touch screen, the method including, detecting a first incoming call while displaying first information on the first touch screen and displaying second information on the second touch screen, replacing the first information displayed on the first touch screen with a first incoming call screen related to the first incoming call by displaying the first incoming call screen on the first touch screen in response to the detecting the first incoming call, wherein the first incoming call screen includes at least one of a call participant identification area indicating a counterpart call participant corresponding to the first incoming call, an incoming key, and a rejection message key, deactivating the second information displayed on the second touch screen and displaying a guide message indicating to fold the portable device for a call while displaying the first incoming call screen, detecting a pre-designated first touch gesture from the incoming key within the first incoming call screen, and replacing the first incoming call screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the detecting the first touch gesture, and removing the guide message displayed on the second touch screen, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0037] In accordance with an aspect of another exemplary embodiment, there is provided a portable device including at least one foldable panel, a first touch screen and a second touch screen arranged on at least one foldable panel, and at least one processor that is configured to display, on the first touch screen, a first page including at least one of a widget area designated as a home screen and an icon related to at least one application and a dock area including a call icon of a call application, display, on the second touch screen, first information in a state where a first panel of the at least one foldable panel includes the first touch screen, a second panel of the at least one foldable panel includes the second touch screen, and the first and second panels are unfolded, detect a first tap gesture that selects the call icon, replace the first page and the dock area displayed on the first touch screen with an outgoing call screen provided by the call application by displaying the outgoing call screen on the first touch screen in response to a detection of the first tap gesture, wherein the outgoing call screen includes at least one of a number display area, a keypad area, a call key, a video call key, and a message sending key, and the second touch screen maintains the first information while the outgoing call screen is displayed in the first touch screen, receive a phone number through the keypad area and detect a second tap gesture from the call key, replace the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen on the first touch screen in response to the detection of the second tap gesture, and display, on the second touch screen, a guide message indicating to fold the portable device for a call, wherein the dialing screen includes a call participant identification area indicating a counterpart call participant and a function key area providing mid-call functions, replace the dialing screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the call being connected with the counterpart call participant, and remove the guide message displayed on the second touch screen, and display the first information, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0038] In accordance with an aspect of another exemplary embodiment, there is provided a portable device including at least one foldable panel, a first touch screen and a second touch screen arranged on the at least one foldable panel, and at least one processor that is configured to display, on the first touch screen, first information and detect a generation of a first incoming call while second information is displayed on the second touch screen in a state where a first panel of the at least one foldable panel includes the first touch screen, a second panel of the at least one foldable panel includes the second touch screen, and the first and second touch screens are unfolded, replace the first information displayed on the first touch screen with a first incoming call screen related to the first incoming call provided by a call application by displaying the first incoming call screen on the first touch screen in response to the generation of the first incoming call, wherein the first incoming call screen includes at least one of a call participant identification area indicating a counterpart call participant, an incoming key, and a rejection message key, deactivate the second information displayed on the sec-

ond touch screen and display a guide message indicating to fold the portable device for a call while displaying the first incoming call screen, detect a pre-designated first touch gesture from the incoming key within the first incoming call screen, replace the incoming call screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the detection of the first touch gesture, and remove the guide message screen on the second touch screen, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions, and replace the mid-call screen on the first touch screen with the first information by displaying the first information on the first touch screen in response to the first incoming call ending.

[0039] In accordance with an aspect of another exemplary embodiment, there is provided a portable device including a first touch screen and a second touch screen, and at least one processor that is configured to detect a first incoming call while first information is displayed on the first touch screen and second information is displayed on the second touch screen, replace the first information displayed on the first touch screen with a first incoming call screen related to the first incoming call by displaying the first incoming call screen on the first touch screen in response to the detection of the first incoming call, wherein the first incoming call screen includes at least one of a call participant identification area indicating a counterpart call participant corresponding to the first incoming call, an incoming key, and a rejection message key, deactivate the second information on the second touch screen and display a guide message screen indicating to fold the portable device for a call while the first incoming call screen is displayed, detect a pre-designated first touch gesture from the incoming key within the first incoming call screen, and replace the first incoming call screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the detection of the first touch gesture, and remove the guide message screen displayed on the second touch screen, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0040] In accordance with an aspect of another exemplary embodiment, there is provided a non-transitory computer-readable medium storing a program executable by a computer to perform a method of controlling a portable device including a first touch screen and a second touch screen arranged on at least one foldable panel, the method including displaying, on the first touch screen, a first page including at least one of a widget area designated as a home screen and an icon related to at least one application or and displaying a dock area a call icon of a call application, displaying, on the second touch screen, first information in a state where a first panel of the at least one foldable panel includes the first touch screen, a second panel of the at least one foldable panel includes the second touch screen are unfolded, detecting a first tap gesture that selects the call icon, replacing the first page and the dock area on the first touch screen with an outgoing call screen provided by the call application by displaying the outgoing call screen on the first touch screen in response to a detection of the first tap gesture, wherein the outgoing call screen includes at least one of a number display area, a keypad area, a call key, a video call key, and a message sending key, and the second touch screen maintains the first information while the outgoing call screen is displayed in the first touch screen, receiving a phone number through the keypad area and detecting a second tap gesture from the call key, replacing the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen on the first touch screen in response to the detecting the second tap gesture, and displaying, on the second touch screen, a guide message indicating to fold the portable device for a call, wherein the dialing screen includes a call participant identification area indicating a counterpart call participant and a function key area providing mid-call functions, replacing the dialing screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the call being connected with the counterpart call participant, and removing the guide message displayed on the second touch screen, and displaying the first information, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0041] In accordance with an aspect of another exemplary embodiment, there is provided a non-transitory computer-readable medium storing a program executable by a computer to perform a method of controlling a portable device including a first touch screen and a second touch screen arranged on at least one foldable panel, the method including displaying first information on a first touch screen and detecting a generation of a first incoming call while second information is displayed on a second touch screen in a state where a first panel of the at least one foldable panel includes the first touch screen, a second panel of the at least one foldable panel includes the second touch screen, and the first and second panels are unfolded, replacing the first information displayed on the first touch screen with a first incoming call screen related to the first incoming call provided by a call application by displaying the first incoming call screen on the first touch screen in response to the generation of the first incoming call, wherein the first incoming call screen includes at least one of a call participant identification area indicating a counterpart call participant, an incoming key, and a rejection message key, deactivating the second information displayed on the second touch screen and displaying a guide message indicating to fold the portable device for a call while displaying the first incoming call screen, detecting a pre-designated first touch gesture from the incoming key within the first incoming call screen, replacing the incoming call screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the detecting the first touch gesture, removing the guide message screen displayed on the second touch screen, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions, and replacing the mid-call screen displayed on the first touch screen with the first information by displaying the first information on the first touch screen in response to the first incoming call ending.

[0042] In accordance with an aspect of another exemplary embodiment, there is provided a non-transitory computer-readable medium storing a program executable by a computer to perform a method of controlling a portable device including a first touch screen and a second touch screen arranged on at least one foldable panel, the method including detecting a first incoming call while displaying first information on the

first touch screen and displaying second information on the second touch screen, replacing the first information displayed on the first touch screen with a first incoming call screen related to the first incoming call by displaying the first incoming call screen on the first touch screen in response to the detecting the first incoming call, wherein the first incoming call screen includes at least one of a call participant identification area indicating a counterpart call participant corresponding to the first incoming call, an incoming key, and a rejection message key, deactivating the second information displayed on the second touch screen and displaying a guide message indicating to fold the portable device for a call while displaying the first incoming call screen, detecting a predesignated first touch gesture from the incoming key within the first incoming call screen, and replacing the first incoming call screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the detecting the first touch gesture, and removing the guide message screen displayed on the second touch screen, wherein the mid-call screen includes a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

[0043] Other aspects and advantages of the invention will be apparent from the following description and the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0044] The foregoing and other aspects will become more apparent from the following detailed description of exemplary embodiments taken in conjunction with the accompanying drawings in which:

[0045] FIG. **1** is a block diagram illustrating a schematic configuration of a portable device according to an exemplary embodiment;

[0046] FIG. **2** is a perspective view of a portable device according to an exemplary embodiment;

[0047] FIGS. **3**A to **3**D are diagrams illustrating screen modes according to a relative angle between a first panel and a second panel of a portable device according to one or more exemplary embodiments;

[0048] FIG. **4** is a perspective view of a portable device according to another exemplary embodiment;

[0049] FIGS. **5**A to **5**C are perspective views of a portable device according to one or more exemplary embodiments;

[0050] FIGS. **6**A to **6**G are diagrams illustrating a user interface of a home screen according to one or more exemplary embodiments;

[0051] FIGS. **7**A to **7**J are diagrams illustrating a scenario of adding an icon of an application to a home screen displayed in first and second touch screens **12** and **14** according to one or more exemplary embodiments;

[0052] FIGS. **8**A and **8**B are diagrams illustrating a user interface of an application menu according to one or more exemplary embodiments;

[0053] FIGS. **9**A to **9**J are diagrams illustrating a change in a view mode according to a touch gesture according to one or more exemplary embodiments;

[0054] FIGS. **10**A to **10**H are diagrams illustrating a user interface of a pocket mode home screen according to one or more exemplary embodiments;

[0055] FIGS. **11**A to **11**F are diagrams illustrating a user interface of a pocket mode home screen according to one or more exemplary embodiments;

[0056] FIGS. **12**A to **12**I are diagrams illustrating a user interface of a gallery map application according to one or more exemplary embodiments;

[0057] FIGS. **13**A to **13**J are diagrams illustrating a user interface of a task manager panel according to one or more exemplary embodiments;

[0058] FIGS. **14**A to **14**M are diagrams illustrating a user interface of a personal broadcasting application according to one or more exemplary embodiments;

[0059] FIGS. **15**A to **15**C are diagrams describing a detection of a folding back command according to one or more exemplary embodiments;

[0060] FIGS. **16**A to **16**D are diagrams describing a detection of a folding hold command according to one or more exemplary embodiments;

[0061] FIGS. **17**A to **17**K are diagrams illustrating a user interface for a clipboard function according to one or more exemplary embodiments;

[0062] FIGS. **18**A to **18**P are diagrams illustrating a user interface for an electronic book function according to one or more exemplary embodiments;

[0063] FIGS. **19**A to **19**G are diagrams illustrating a user interface of a video conference application according to one or more exemplary embodiments;

[0064] FIGS. **20**A to **20**H are a diagrams illustrating a user interface of a collaborative game application according to one or more exemplary embodiments;

[0065] FIGS. **21**A to **21**O are diagrams illustrating a user interface of a schedule management application according to one or more exemplary embodiments;

[0066] FIGS. **22**A to **22**M are diagrams illustrating scenarios of expanding a calendar area and displaying the expanded calendar area in a schedule management application according to one or more exemplary embodiments;

[0067] FIGS. **23**A to **23**P are diagrams illustrating a user interface of a call application according to one or more exemplary embodiments;

[0068] FIGS. **24**A to **24**R are diagrams illustrating a user interface of a call application according to one or more exemplary embodiments;

[0069] FIGS. **25**A to **25**L and FIGS. **26**A to **26**K are diagrams illustrating a user interface of a camera application according to one or more exemplary embodiments; and

[0070] FIGS. **27**A to **27**Q are diagrams illustrating a change in a view mode according to a physical motion of the portable device according to one or more exemplary embodiments.

DETAIL DESCRIPTION OF EXEMPLARY EMBODIMENTS

[0071] Hereinafter, an operation principle of one or more exemplary embodiments will be described in detail with reference to the accompanying drawings. In the following description of one or more exemplary embodiments, a detailed description of known functions and configurations incorporated herein will be omitted when it may make the subject matter of one or more exemplary embodiments rather unclear. Further, terms described below are defined in consideration of the functions of one or more exemplary embodiments, and may have different meanings according to the intention of a user or operator or the convention. Therefore, its definition will be made based on the overall contents of this specification.

[0072] Throughout the drawings and the detailed description, unless otherwise described, the same drawing reference

numerals will be understood to refer to the same elements, features, and structures. The relative size and depiction of these elements may be exaggerated for clarity, illustration, and convenience.

[0073] The term " . . . unit" used in the embodiments indicates a component including software or hardware, such as a Field Programmable Gate Array (FPGA) or an Application-Specific Integrated Circuit (ASIC), and the " . . . unit" performs certain roles. However, the " . . . unit" is not limited to software or hardware. The " . . . unit" may be configured to be included in an addressable storage medium or to reproduce one or more processors. Therefore, for example, the " . . . unit" includes components, such as software components, object-oriented software components, class components, and task components, processes, functions, attributes, procedures, subroutines, segments of program code, drivers, firmware, microcode, circuits, data, a database, data structures, tables, arrays, and variables. A function provided inside components and " . . . units" may be combined into a smaller number of components and " . . . units", or further divided into additional components and " . . . units".

[0074] The term "module" as used herein means, but is not limited to, a software or hardware component, such as an FPGA or ASIC, which performs certain tasks. A module may advantageously be configured to reside on an addressable storage medium and configured to execute on one or more processors. Thus, a module may include, by way of example, components, such as software components, object-oriented software components, class components and task components, processes, functions, attributes, procedures, subroutines, segments of program code, drivers, firmware, microcode, circuitry, data, databases, data structures, tables, arrays, and variables. The functionality provided for in the components and modules may be combined into fewer components and modules or further separated into additional components and modules.

[0075] Although the terms used herein are generic terms which are currently widely used and are selected by taking into consideration functions thereof, the meanings of the terms may vary according to the intentions of persons skilled in the art, legal precedents, or the emergence of new technologies. Furthermore, some specific terms may be randomly selected by the applicant, in which case the meanings of the terms may be specifically defined in the description of the exemplary embodiment. Thus, the terms should be defined not by simple appellations thereof but based on the meanings thereof and the context of the description of the exemplary embodiment. As used herein, expressions such as "at least one of," when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list.

[0076] It will be understood that when the terms "includes," "comprises," "including," and/or "comprising," when used in this specification, specify the presence of stated elements and/or components, but do not preclude the presence or addition of one or more elements and/or components thereof. As used herein, the term "module" refers to a unit that can perform at least one function or operation and may be implemented utilizing any form of hardware, software, or a combination thereof.

[0077] The portable device in this specification has a display including one or more touch screens and corresponds to a device configured to execute an application or display contents, for example, a tablet Personal Computer (PC), a Portable Multimedia Player (PMP), Personal Digital Assistant (PDA), a smart phone, a mobile phone, or a digital frame. Hereinafter, although a portable device corresponding to a cellular phone or a smart phone will be described with reference to exemplary embodiments, it should be noted that the present invention is not limited thereto.

[0078] FIG. **1** is a block diagram illustrating a schematic configuration of a portable device according to an exemplary embodiment. The portable device **100** illustrated in FIG. **1** may be connected to an external device (not shown) by using at least one of a cellular communication module **120**, a sub communication module **130**, and a connector **165**. The "external device" includes at least one of a different device from the portable device **100**, a mobile phone, a smart phone, a tablet Personal Computer (PC), and a computer server.

[0079] Referring to FIG. **1**, the portable device **100** includes at least one of touch screen displays **190***a* and **190***b* and a touch screen controller **195**. Also, the portable device **100** includes a controller **110**, the cellular communication module **120**, the sub communication module **130**, a multimedia module **140**, a camera module **150**, a Global Positioning System (GPS) module **155**, an input/output module **160**, a sensor module **170**, a storage unit **175**, and a power supplier **180**. The sub communication module **130** includes at least one of a wireless LAN module **131** and a near field communication module **132**, and the multimedia module **140** includes at least one of a broadcasting communication module **141**, an audio reproduction module **142**, and a video reproduction module **143**. The camera module **150** includes at least one of a first camera **151** and a second camera **152**, and the input/output module **160** includes at least one of a button set **161**, a microphone **162**, a speaker **163**, a vibration motor **164**, the connector **165**, and a keypad **166**.

[0080] The controller **110** may include a CPU **111**, a Read-Only Memory (ROM) **112** for storing a control program for controlling the portable device **100**, and a Random Access Memory (RAM) **113** for storing a signal or data input from an outside of the portable device **100** or used as a storage area for an operation performed in the portable device **100**. The CPU **111** may include at least one of a single core processor, a dual core processor, a triple core, processor and a quad core processor. The CPU **111**, the ROM **112**, and the RAM **113** may be mutually connected through an internal bus.

[0081] The controller **110** may control the cellular communication module **120**, the sub communication module **130**, the multimedia module **140**, the camera module **150**, the GPS module **155**, the input/output module **160**, the sensor module **170**, the storage unit **175**, the power supplier **180**, the touch screens **190***a* and **190***b*, and the touch screen controller **195**.

[0082] The cellular communication module **120** connects the portable device **100** with the external device (particularly, a base station of a cellular system) through at least one of or a plurality of antennas (not shown) by using a wireless access technology according to a cellular communication protocol under a control of the controller **110**. The cellular communication module **120** transmits/receives a wireless signal for voice phone communication, video phone communication, a Short Messaging Service (SMS), or a Multimedia Messaging service (MMS) to/from other communicable devices such as a mobile phone, a smart phone, a tablet PC, or another device having a phone number input into the portable device **100**.

[0083] The sub communication module **130** may include at least one of the wireless LAN module **131** and the near field communication module **132**. For example, the sub communication module **130** may include only the wireless LAN

module **131**, only the near field communication module **132**, or both the wireless LAN module **131** and the near field communication module **132**.

[0084] The wireless LAN module **131** may be connected to an Internet in a place where a wireless Access Point (AP) (not shown) is installed, according to a control of the controller **110**. The wireless LAN module **131** supports a wireless LAN standard (IEEE802.11x) of the Institute of Electrical and Electronics Engineers (IEEE). The near field communication module **132** may wirelessly perform near field communication between the portable device **100** and the external device according to a control of the controller **110**. Near field communication techniques may include Bluetooth, Infrared Data Association (IrDA) and the like.

[0085] The portable device **100** may include at least one of the cellular communication module **120**, the wireless LAN module **131**, and the near field communication module **132**. For example, the portable device **100** may include a combination of the cellular communication module **120**, the wireless LAN module **131**, and the near field communication module **132** according to a capability of the display device **100**.

[0086] The multimedia module **140** may include at least one of the broadcasting communication module **141**, the audio reproduction module **142**, and the video reproduction module **143**. The broadcasting communication module **141** may receive a broadcasting signal (for example, a TV broadcasting signal, a radio broadcasting signal, or a data broadcasting signal) and broadcasting additional information (for example, Electric Program Guide (EPS) or Electric Service Guide (ESG)) broadcasted from a broadcasting station through a broadcasting communication antenna (not shown) according to a control of the controller **110**. The audio reproduction module **142** may reproduce a digital audio file (for example, a file having an extension of mp3, wma, ogg or way) stored or received according to a control of the controller **110**. The video reproduction module **143** may reproduce a digital video file (for example, a file having an extension of mpeg, mpg, mp4, avi, mov or mkv) stored or received according to a control of the controller **110**. The video reproduction module **143** may reproduce the digital audio file.

[0087] The multimedia module **140** may include the audio reproduction module **142** and the video reproduction module **143** except for the broadcasting communication module **141**. Further, the audio reproduction module **142** or the video reproduction module **143** of the multimedia module **140** may be included in the controller **110**.

[0088] The camera module **150** may include at least one of the first camera **151** and the second camera **152** for photographing a still image or a video according to a control of the controller **110**. The first camera **151** and the second camera **152** may be arranged in a housing of the portable device **100** or connected to the portable device **100** by using a separate connection means. At least one of the first camera **151** or the second camera **152** may include an auxiliary light source (for example, a flash (not shown)) for providing an amount of light required for the photographing. In one embodiment, the first camera **151** may be disposed in a front surface of the portable device **100**, and the second camera **152** may be disposed in a rear surface of the portable device **100**. In another embodiment, the first camera **151** and the second camera **152** may be disposed to be adjacent to each other (for example, an interval between the first camera **151** and the second camera **152** is larger than 1 cm or smaller than 8 cm), and thus a three-dimensional still image or a three-dimensional video may be photographed.

[0089] The camera module **150** can detect a motion or a shape of the user through at least one of the first camera **151** and the second camera **152** and transmit the detected motion or shape to the controller **110** as an input for executing or controlling the application. In one embodiment, the motion of the user refers to a motion of a hand of the user detected through the first camera or the second camera, and the shape of the user refers to a shape of a face of the user detected through the first camera or the second camera. In another embodiment, the portable device **100** can detect a motion of the user by using another means such as a infrared ray detector and execute or control the application in response to the motion.

[0090] The GPS module **155** may receive a radio wave from a plurality of GPS satellites (not shown) in Earth orbit and calculate a position of the portable device **100** by using Time of Arrival from the GPS satellites (not shown) to the portable device **100** and GPS parameters.

[0091] The input/output module **160** may include at least one of at least one physical button **161**, the microphone **162**, the speaker **163**, the vibration motor **164**, the connector **165**, and the keypad **166**. The at least one physical button **161** may be formed in a front surface, a side surface, or a rear surface of the housing of the portable device **100** in a push type or touch type, and may include at least one of a power/lock button, a volume control button, a menu button, a home button, a back button, and a search button. The microphone **162** receives a voice or sound according to a control of the controller **110** and generates an electrical signal.

[0092] The speaker **163** may output sounds corresponding to various signals (for example, a wireless signal, a broadcasting signal, a digital audio file, a digital video file, photographing a picture or the like) of the cellular communication module **120**, the sub communication module **130**, the multimedia module **140**, or the camera module **150** to an outside of the display device **100** according to a control of the controller **110**. The speaker **163** may output sounds (for example, a button control sound or a ring back tone corresponding to phone communication) corresponding to functions performed by the portable device **100**. One or more speakers **163** may be formed in a proper position or positions of the housing of the portable device **100**. For example, the speaker **163** includes an internal speaker module disposed in a position suitable for approaching ears of the user during phone communication and an external speaker module having a higher output suitable for being used during a reproduction of an audio/video file or watching of broadcasting and disposed in a proper position of the housing of the portable device **100**.

[0093] The vibration motor **164** may convert an electrical signal to a mechanical vibration according to a control of the controller **110**. For example, when the portable device **100** in a vibration mode receives voice phone communication from another device (not shown), the vibration motor **164** operates. One or more vibration motors **164** may be formed within the housing of the portable device **100**. The vibration motor **164** may operate in response to a touch gesture of the user detected on the touch screens **190***a* and **190***b* and continuous touch motions detected on the touch screens **190***a* and **190***b*.

[0094] The connector **165** may be used as an interface for connecting the portable device **100** with an external device or a power source. The connector **165** may transmit data stored

in the storage unit **175** of the portable device **100** to the external device through a wired cable connected to the connector **165** or receive the data from the external device according to a control of the controller **110**. Power may be input or a battery (not shown) may be charged from the power source through the wired cable connected to the connector **165**.

[0095] The keypad **166** may receive a key input from the user to control the portable device **100**. The keypad **166** includes a physical keypad formed in the portable device **100** and/or a virtual keypad displayed on the touch screens **190***a* and **190***b*. The physical keypad formed in the portable device **100** may be omitted according to a capability or a structure of the portable device **100**.

[0096] The sensor module **170** includes at least one sensor for detecting a state of the portable device **100**. For example, the sensor module **170** may include a proximity sensor for detecting whether the user is close to the portable device **100**, an illumination sensor for detecting an amount of light adjacent to the portable device **100**, and a motion sensor for detecting an operation of the portable device **100** (for example, a rotation of the portable device **100**, an absolute/relative movement of at least one panel included in the portable device **100**, or an acceleration or vibration applied to the portable device **100**). Each sensor of the sensor module **170** may detect the state, generate a signal corresponding to the detection, and transmit the generated signal to the controller **110**. The sensor of the sensor module **170** may be added or omitted according to a capability of the portable device **100**.

[0097] The storage unit **175** may store signals, information, or data input/output in accordance with operations of the cellular communication module **120**, the sub communication module **130**, the multimedia module **140**, the camera module **150**, the GPS module **155**, the input/output module **160**, the sensor module **170**, and the touch screens **190***a* and **190***b* according to a control of the controller **110**. The storage unit **175** may store a control program for controlling the portable device **100** or the controller **110** and applications. Hereinafter, the term "storage unit" includes a memory card (for example, an SD card or a memory stick) removable from/mounted to the storage unit **175**, the ROM **112**, the RAM **113**, or the portable device **100**. Further, the storage unit may include a nonvolatile memory, a volatile memory, a Hard Disk Drive (HDD), or a Solid State Drive (SSD).

[0098] The power supplier **180** may supply power to one battery or a plurality of batteries disposed within the housing of the portable device **100** according to a control of the controller **110**. The one battery or the plurality of batteries supply power to the controller **110** of the portable device **100** and each component module. Further, the power supplier **180** may supply power input from an external power source through the wired cable connected to the connector **165** to the portable device **100**.

[0099] The touch screens **190***a* and **190***b* are display devices of displaying various applications (for example, phone communication, data transmission, broadcasting, camera and the like) which can be executed by the controller **110** and providing a user interface configured to adapt the various applications, and may receive at least one touch gesture through a user's body (for example, fingers including a thumb) or a detectable input means (for example, a stylus pen). The user interface may include a predetermined touch area, a soft key, and a soft menu. The touch screens **190***a* and **19***b* may transmit an electrical signal corresponding to the at least one touch gesture input through the user interface to the touch screen controller **195**. Further, the touch screens **190***a* and **190***b* may detect continuous touch motions and transmit electrical signals corresponding to continuous or discontinuous touch motions to the touch screen controller **195**. The touch screens **190***a* and **190***b* may be implemented in, for example, a resistive type, a capacitive type, an infrared type, or an acoustic wave type.

[0100] The touch screen controller **195** converts the electrical signal received from the touch screens **190***a* and **190***b* to a digital signal (for example, X and Y coordinates) and transmits the digital signal to the controller **110**. The controller **110** may control the touch screens **190***a* and **190***b* by using the digital signal received from the touch screen controller **195**. For example, the controller **110** may allow a soft key displayed on the touch screens **190***a* and **190***b* to be selected or an application corresponding to the soft key to be executed in response to the touch gesture. Further, the touch screen controller **195** may be included in the controller **110**.

[0101] The touch gesture according to the specification is not limited to a direct contact between the touch screens **190***a* and **190***b* and a user's body or a touchable input means and may include a non-contact (for example, a case where a detectable interval between the touch screens **190***a* and **190***b* and the user's body or the touchable input means is 1 cm or shorter). The detectable interval of the touch screens **190***a* and **190***b* may be changed according to a capability or a structure of the portable device **100**.

[0102] In an exemplary embodiment, the touch gesture may include all types of user gestures which can be detected by the portable device through a direct contact or a close approach to the touch screen. For example, the touch gesture corresponds to a user's action of selecting one position or a plurality of continuous positions on the touch screen by using a finger of a right hand or left hand (particular, an index finger), a thumb, or an object (for example, a stylus pen) which can be detected by the touch screen, and may include actions such as a touch, a contact, a release of the touch, a tap, a contact and rotate, a pinch, a spread, a touch drag and the like. Here, the touch drag corresponds to a gesture of moving a finger or a thumb in a predetermined direction in a state where the finger, the thumb, or a stylus pen contacts the touch screen, and may include, for example, gestures such as a touch and drag, a flick, a swipe, a slide, a sweep and the like. A contact state with the touch screen may include a state where the finger, the thumb, or the stylus pen directly contacts the touch screen or closely approaches the touch screen without a direct contact.

[0103] The portable device **100** is a device for executing an application, a widget, and a function which is stored in the storage unit and can be executed by the controller **110** through the touch screen. In general, the touch screen provides application, widgets, functions, and graphic objects (that is, soft key or short-cut icon) corresponding to a group thereof, and the portable device executes a corresponding application, widget, or function in response to the detection of the touch gesture of the user on each graphic object.

[0104] Here, the widget refers to a mini application which is downloaded and used by the user or can be generated by the user, and includes, for example, a weather widget, a stock widget, a calculator widget, an alarm clock widget, a dictionary widget and the like. A short-cut icon for executing the widget may provide simple advance information through a corresponding widget application. For example, an icon of the weather widget simply provides a current temperature and

a weather symbol and a widget application executed through a touch of the icon provides much more information such as weather in each period/area. The application in this specification includes a widget based application and a non-widget based application.

[0105] In one embodiment, the touch screen is implemented by one panel (or tablet) and displays one or a plurality of task screens corresponding to one or a plurality of applications under a control of the controller. In another embodiment, the touch screen display is implemented by two panels which are physically separated and mutually connected with each other by a predetermined connector, and the panels may be folded in or folded out by a predetermined angle with respect to the connector. Here, the connector may be a hinge, a flexible connector, or a part of a flexible touch screen. In another embodiment, the touch screen display may be implemented by a flexible touch screen which can be folded or bent at least one or more times. The touch screen display displays one or a plurality of task screens related to one or a plurality of applications under a control of the controller.

[0106] FIG. **2** is a perspective view of the portable device according to an exemplary embodiment. FIG. **2** shows a configuration in a case where the portable device includes a display device including two touch screens which are connected by a hinge.

[0107] Referring to FIG. **2**, the portable device **100** includes a first panel **2** and a second panel **4**, and the first panel **2** and the second panel **4** are connected by a hinge **6** to be relatively movable. One surface of the first panel **2** has a first touch screen **12**, and at least one physical button **5** may be disposed in a lower end of the first touch screen **12**. One surface of the second panel **4** has a second touch screen **14** disposed in parallel with the first touch screen **12**, and at least one physical button **5'** may be disposed in a lower end of the second touch screen **14**. The physical buttons **5** and **5'** include at least one of a push button and a touch button. As one embodiment, the first touch screen **12** arranged on the first panel **2** having a speaker **20** and a microphone **22** operates as a main screen, and the second touch screen **14** arranged on the second panel **4** operates as a sub screen. As one embodiment, the first panel **2** includes a front camera **24**, and the second panel **4** includes a rear camera **26**. As another example, as the front camera **24** is disposed in the same surface as that of the second screen **14**, in a state where the first panel **2** and the second panel **4** are unfolded, the front camera **24** may work as a front camera, and in a state where the first panel **2** and the second panel **4** are folded, the front camera **24** may work as a rear camera.

[0108] As long as the first panel **2** and the second panel **4** are connected by the hinge **6** to be relatively movable, the portable device **100** can be any device such as a mobile phone, a notebook, a tablet PC, a PMP or the like. Although a case where the first touch screen **12** and the second touch screen **14** are included in the first panel **2** and the second panel **4**, respectively has been described, the case can be applied to a device in which the touch screen display is provided to only one of the two panels. Further, at least one of the function buttons **5** and **5'** in lower ends of the touch screens may be omitted. Furthermore, although a case where the first panel **2** and the second panel **4** are connected by the hinge **6** has been described as an example, the hinge **6** may be replaced with another component as long as the first panel **2** and the second panel **4** can be folded through a relative movement.

[0109] The portable device includes a display device having a first touch screen and a second touch screen which are physically or graphically separated, and supports various screen modes as shown in FIG. **3** by using the two touch screens.

[0110] FIGS. **3**A to **3**D are diagrams illustrating screen modes according to a relative angle between the first panel **2** and the second panel **4** of the portable device **100**. The relative angle θ is a rotation angle at which the second panel **4** rotates with respect to the first panel **2** in a predetermined direction (for example, counterclockwise).

[0111] FIG. **3**A is a perspective view of the folded portable device **100**, which shows a state where the first panel **2** and the second panel **4** contact each other while each of the touch screens **12** and **14** of the first panel **2** and the second panel **4** faces outward, that is, a state where the portable device **100** is completely folded outward. The state corresponds to a dual screen. At this time, the relative angle θ is 0 degrees. For example, when the relative angle between the first and second panels **2** and **4** ranges from 0 to 60 degrees, the portable device recognizes a dual screen mode. The dual screen mode is useful when the portable device is in a locked state in which the portable device is not used and useful in a call application. The touch screen **12** in a front surface may display a task screen of at least one application and the touch screen **14** in a rear surface may be turned off in the dual screen mode. Some applications can turn on the touch screen **14** in the rear surface by using an option menu.

[0112] FIG. **3**B shows a state where the first panel **2** and the second panel **4** are parallel in which the relative angle θ is 180 degrees or close to 180 degrees within a predetermined range, that is, an unfolded state. The state corresponds to a double screen. **7** For example, when the relative angle θ between the first and second panels **2** and **4** ranges from 175 to 185 degrees, the portable device may consider that the first and second panels **2** and **4** are unfolded. The double screen mode may provide various view modes of displaying two task screens for two applications in the two touch screens **12** and **14**, respectively, displaying two task screens for one application in the two touch screens **12** and **14**, or widely displaying one task screen for one application in the two touch screens **12** and **14**. When there is no application executed within one touch screen, the corresponding touch screen may display a home screen.

[0113] FIG. **3**C shows a state where the relative angle θ of the second panel **4** with respect to the first panel **2** exceeds 180 degrees, that is, a state where the two touch screens **12** and **14** are slightly folded inward. That state corresponds to an in-folded screen. For example, when the relative angle θ between the first and second panels **2** and **4** ranges from 180 to 210 degrees, the portable device recognizes an in-folded screen mode. The in-folded screen mode corresponds to the state where the two touch screens **12** and **14** are slightly folded inward and is useful when the portable device is used as a similar form to that of a notebook or an electric book. The in-folded screen mode may be used similarly to the double screen mode.

[0114] FIG. **3**D shows a state where the relative angle θ of the second panel **4** with respect to the first panel **2** is smaller than 180 degrees, that is, a state where the two touch screens **12** and **14** are nearly completely folded outward in opposite directions. The state corresponds to an out-folded screen. For example, when the relative angle θ between the first and second panels **2** and **4** ranges from 30 to 90 degrees, the portable device recognizes an out-folded screen mode. The out-folded screen mode has a structure in which the two touch

screens **12** and **14** are folded outward and is useful when the portable device is charged because the portable device can stand on the floor in a triangle shape, when the portable device is used as a digital clock or frame, and when personal broadcasting, a movie, a video or the like is watched for a long time. As another embodiment, the out-folded screen mode may be applied to an application requiring cooperation or interaction between two or more users, for example, a video conference, a collaborative game or the like. Some applications may display a task screen in only the touch screen **12** of the front surface in the dual screen mode and turn off the touch screen **14** of the rear surface. Some applications may turn on the touch screen **14** of the rear surface by using an option menu.

[0115] FIG. **4** is a perspective view of the portable device according to another exemplary embodiment. As illustrated in FIG. **4**, the portable device **100** includes a display having two flexible touch screens **12** and **14**. The two touch screens **12** and **14** may be mutually connected by a flexible connector **18** and freely folded or bent by a flexible connector **20**.

[0116] FIGS. **5**A, **5**B, and **5**C are perspective views of the portable device according to another exemplary embodiment. FIGS. **5**A, **5**B, and **5**C illustrate a configuration in which the display device of the portable device **100** is unfolded, a configuration in which the display device is partially closed, and a configuration in which the display device is closed, respectively. Here, although it is illustrated that the portable device **100** has a tri-folded configuration, the portable device **100** may have a bi-folded configuration, a tri-folded configuration or more, or partially folded configuration. In FIGS. **5**A, **5**B, and **5**C, the display device of the portable device **100** may be implemented by two or more foldable touch screens **12**, **14**, and **16** which are divided by one or more foldable boundaries **12***a* and **12***b*.

[0117] When the portable device is turned on and completely booted, the portable device provides a home screen through the touch screen. Further, the portable device provides the home screen when there is no application which is being executed or by an input of an external home button. The home screen can be designated basically by a manufacturer and edited by the user and guides the portable device to easily move to various executable applications, widgets, and functions.

[0118] The portable device includes a home screen function which provides two pages designated as the home screen through a touch screen display device including a first touch screen and a second touch screen arranged on at least one foldable panel and navigates pages in response to a touch gesture of the user on the home screen.

[0119] FIGS. **6**A to **6**G illustrate a user interface of the home screen according to one or more exemplary embodiments.

[0120] Referring to FIG. **6**A, the first touch screen **12** displays a first page **202** of the home screen and the second touch screen **14** displays a second page **204** of the home screen. The first and second touch screens **12** and **14** may be physically or graphically separated.

[0121] The first page **202** of the home screen includes a first group including at least one widget area **212** designated as the home screen and/or at least one shortcut icon **214** and the second page **204** includes a second group including at least one widget area **218** designated as the home screen and/or at least one short icon. The first page **202** and the second page **204** can display the widget areas **212** and **218** and/or the shortcut icon **214** in a common background image or respective background images designated as a background screen. As a selectable embodiment, one background image may be displayed over the first and second touch screens **12** and **14**.

[0122] Each shortcut icon corresponds to each application or each application group, and the corresponding application is executed or shortcut icons included in the corresponding application group are displayed through a detection of a user's touch. Each widget area or each shortcut icon may be basically provided when the portable device is manufactured or may be formed by the user.

[0123] In addition, the first touch screen **12** can further display a counter **202***a* indicating a page of the home screen, frequently used applications, for example, a call application, a contact information application, a message application, a dock area **216** including short icons of an application menu providing application lists, and a status bar **206** providing signal intensity indicator(s) for wireless communication such as cellular or WiFi communication, a Bluetooth connection mode, a received message, a battery status indicator, and a current time together with the first page **202**. The second touch screen **14** can further display a page counter **204***a* and a status bar **208**. The status bar on the second touch screen **14** can provide information different from that of the first touch screen **12**. The status bars **206** and **208** may be displayed together with the home screen or the application or may be omitted. The status bars **206** and **208** are maintained within the first and second touch screens **12** and **14** regardless of switching of pages. In the following description, description of whether the status bars **206** and **208** are displayed will be omitted.

[0124] The home screen may further provide additional pages including one or more widget areas and/or one or more icons within a predetermined maximum number of pages, and the pages are switched by a pre-designated touch gesture.

[0125] The portable device detects a pre-designated touch gesture **200***a* to switch a page of the home screen in at least one of the first touch screen **12** and the second touch screen **14** and proceeds to FIG. **6**B.

[0126] Referring to FIG. **6**B, the first and second touch screens **12** and **14** display the following two pages designated as the home screen, that is, third and fourth pages **232** and **234** and page counters **232***a* and **234***a* in response to the detection of the touch gesture **200***a*.

[0127] The third and fourth pages **232** and **234** may include a widget area and/or an icon different from those of the first and second pages **202** and **204**. The third and fourth pages **232** and **234** are displayed in the second touch screen **14** together with the page counters **232***a* and **234***a* while sliding in a direction from the second touch screen **14** to the first touch screen **12**, and the third page **232** and the page counter **232***a* may be displayed over both the first and second touch screens **12** and **14** during the sliding. As an embodiment, the dock area **216** providing lists of frequently used applications may be fixedly displayed in a designated position within the first touch screen **12** regardless of the page switching (that is, independently).

[0128] As an example, the touch gesture **200***a* includes a touch drag in a direction from one position of the second touch screen **14** to the first touch screen **12** (or opposite direction). As another example, the touch gesture **200***a* includes a touch drag in a direction from one position of the second touch screen **14** to one position of the first touch screen **12** (or opposite direction). As still another example, the touch gesture **200***a* includes a touch drag of passing though a

hinge or connector between the first and second touch screens **12** and **14**. As a selectable embodiment, it is possible that the touch drag **200***a* for switching the page of the home screen moves by a predetermined distance or more. As another example, the touch gesture **200***a* includes a flick on the first or second screen **12** or **14** in a direction from the second touch screen **14** to the first touch screen **12**.

[0129] When a pre-designated touch gesture **200***b* is detected from one of the first touch screen **12** and the second touch screen **14** while the third and fourth pages **232** and **234** are displayed in the first and second touch screens **12** and **14**, the portable device proceeds to FIG. **6**C.

[0130] Referring to FIG. **6**C, the first and second touch screens **12** and **14** display the following two pages, that is, fifth and sixth pages **242** and **244** and page counters **242***a* and **244***a*, respectively, in response to the touch gesture **200***b*. Similar to FIG. **6**, the fifth and six pages **242** and **244** may be displayed while sliding in a direction from the second touch screen **14** to the first touch screen **12** according to the touch gesture **200***b*, and the dock area **216** is fixed on a designated position within the first touch screen **12** regardless of the touch gesture **200***b*.

[0131] Although not illustrated, when a touch drag in a direction from one position of the first touch screen **12** to the second touch screen **14** is detected while the fifth and sixth pages **242** and **244** are displayed, the portable device **100** displays the previous pages, that is, the third pate **232** and the fourth page **234** in the first and second touch screens in response to the touch drag. Similarly, the third and fourth pages **232** and **234** may be displayed while sliding through the hinge in a direction from the touch screen **12** to the second touch screen **14** according to the touch drag.

[0132] When the first and second touch screens **12** and **14** are connected to be discontinuous by the hinge or a separate connector, pages of the home screen may be displayed over both the first and second touch screens **12** and **14** when sliding through the hinge or connector as illustrated in FIG. **6**C.

[0133] The portable device switches the home screen in the unit of one page or two pages by two touch gestures which are differently defined. For example, in FIG. **6**A, the touch gesture **200***a* is defined as a touch drag of moving on the home screen by a predetermined distance or more, and the portable device switches the first and second pages **202** and **204** of the first and second touch screens **12** and **14** to the third and fourth pages **232** and **234**, that is, in the unit of two pages in response to the detection of the touch drag **200***a*. Further, the home screen may be switched in the unit of one page by a touch gesture of moving by a short distance. That is, in FIG. **6**A, when a pre-designated touch gesture, for example, a flick in a direction from the second touch screen **14** to the first touch screen **12** is detected from one of the first touch screen **12** and the second touch screen **14** to shortly switch the home screen, the portable device proceeds to FIG. **6**D.

[0134] Referring to FIG. **6**D, in response to the flick detected from one of the first and second touch screens **12** and **14** displaying the first and second pages **202** and **204**, the portable device displays the second page **204** in the first touch screen **12** and displays the third page **232** in the second touch screen **14**. The second and third pages **204** and **232** are displayed while sliding in a direction from the second touch screen **14** to the first touch screen **12** according to a flick and, and the second page **202** may be displayed over both the first and second touch screens **12** and **14**.

[0135] FIGS. **6**E to **6**G illustrate a scenario of switching the page of the home screen while an application different from the home screen is displayed in the first and second touch screens **12** and **14**.

[0136] Referring to FIG. **6**E, the first touch screen **12** displays the first page **202**, the page counter **202***a*, and the dock area **216** of the home screen, and the second touch screen **14** displays another application **240**. In the shown example, the application **240** is a music play application. When a pre-designated touch gesture **200***c* for switching the page of the home screen is detected from the first touch screen **12**, the portable device proceeds to FIG. **6**H. As an example, the touch gesture **200***c* is generated within the first touch screen **12** and corresponds to a flick or a touch drag which moves in a direction from the second touch screen **14** to the first touch screen **12**.

[0137] Referring to FIG. **6**F, the portable device replaces the first page **202** and the page counter **202***a* of the first touch screen **12** with the second page **204** and the page counter **204***a* of the second page **204** and then displays the replaced second page **204** and page counter **204***a* in response to the detection of the touch gesture **200***c*. Here, the dock area **216** of the first touch screen **12** and the application **240** of the second touch screen **14** are maintained in spite of the touch gesture **200***c*. As one embodiment, the second page **204** may be displayed while sliding in a direction from the second touch screen **14** to the first touch screen **12** according to a motion direction and a speed of the touch gesture **200***c*.

[0138] When a touch gesture **200***e* in a direction of the second touch screen **14** is detected from the first touch screen **12** displaying the second page **204**, the portable device returns to FIG. **6**E to display the first page **202** corresponding to a previous page in the first touch screen **12** and maintain the dock area **216** of the first touch screen **12** and the application **240** of the second touch screen **14**. When a touch gesture **200***d* in a direction from the second touch screen **14** to the first touch screen **12** is detected from the first touch screen **12** displaying the second page **204**, the portable device moves to FIG. **6**G to display a next page.

[0139] Referring to FIG. **6**G, the portable device replaces the second page **204** and the page counter **204***a* of the first touch screen **12** with the third page **232** and the page counter **232***a* of the home screen and displays the replaced third page **232** and page counter **232***a* in response to the detection of the touch gesture **200***d*. Similarly, the dock area **216** of the first touch screen **12** and the application **240** of the second touch screen **14** are maintained in spite of the touch gesture **200***d*. When a touch gesture **200***f* in a direction of the second touch screen **14** is detected from the first touch screen **12** displaying the third page **232**, the portable device returns to FIG. **6**F to display the second page **204**.

[0140] FIGS. **7**A to **7**J illustrate scenarios of adding an icon of an application to the home screen displayed in the first and second touch screens **12** and **14**.

[0141] Referring to FIG. **7**A, the first touch screen **12** displays the first page **202** of the home screen, and the second touch screen **14** displays the second page **204** of the home screen. Although not illustrated, even when another application or information, other than the home screen is displayed in the second touch screen **14**, the following scenario of adding the icon may be similarly applied. When a predetermined touch gesture **210***a*, for example, a touch which is maintained for a predetermined effective time or more, that is, a long-tap is detected from one of the first and second touch screens **12**

and **14** displaying the home screen, for example, from the first touch screen **12** in the shown example, the portable device proceeds to FIG. **7**C.

[0142] As a selectable embodiment, an icon may be added using a menu button **252** which is one of physical buttons arranged in the first panel having the first touch screen **12** as illustrated in FIG. **7**B. The portable device detects an input **210***b* of the menu button **252** arranged in the first panel, for example, a tap gesture or a touch-and-hold on a touch detection type menu button and displays a menu window **250** for the home screen in a lower end of the first touch screen **12**. The menu window **250** includes at least one of an icon addition key, a background screen setting key, a search key, a notification setting key, an icon editing key, and a home screen setting key. When a predetermined touch gesture **210***c*, for example, a tap gesture is detected from the icon addition key within the menu window **250**, the portable device proceeds to FIG. **7**C.

[0143] Referring to FIG. **7**C, the first touch screen **12** displays an item addition popup window **252** for adding items of the home screen to the first page **202** in response to detections of the touch gestures **210***a* and **210***c*. The popup window **252** includes at least a shortcut icon item. When a tap gesture **210***d* is detected from the shortcut icon item, the portable device proceeds to FIG. **7**D.

[0144] Referring to FIG. **7**D, the portable device replaces the icon addition popup window **252** with a shortcut icon selection window **254** and displays the replaced shortcut icon selection window **254** in response to the detection of the tap gesture **210***d*. As another embodiment, the shortcut icon selection window **254** may be displayed to be overwritten on the icon addition popup window **252**. The shortcut icon selection window **254** includes at least an application menu item. When a tap gesture **120***e* is detected from the application menu item, the portable device proceeds to FIG. **7**E.

[0145] Referring to FIG. **7**E, the portable device displays existing information, that is, the first page **202** of the home screen in the first touch screen **12** and displays a first page **260** of the application menu in the second touch screen **14** in response to the detection of the tap gesture **210***e*. The application menu is configured to provide lists of applications which are stored and executable in the portable device, and the first page **260** includes at least some of shortcut icons of applications registered in the application menu. When the application menu includes a plurality of pages, the second touch screen **14** can display a page counter **260***a* together with the first page **260**.

[0146] When the touch gesture **210***d* which starts at one **260***b* of the icons included in the first page **260** of the application menu displayed in the second touch screen **14**, that is, "ICON7" in the shown example and is released on the first touch screen **12**, for example, a touch drag and drop is detected, the portable device proceeds to FIG. **7**F.

[0147] Referring to FIG. **7**F, the portable device displays an icon **260***c* which is a copy of the icon **260***b* selected by the touch gesture **210***d* in the first touch screen **12** in response to the detection of the touch gesture **210***d*. For example, the icon **260***c* may be disposed in a position where the touch gesture **210***d* is released.

[0148] When the predetermined touch gesture **210***e* for switching the page, for example, a flick which starts at one position of the second touch screen **14** and moves in a direction of the first touch screen **12** is detected while the first page **260** of the application menu is displayed in the second touch screen **14**, the portable device proceeds to FIG. **7**G. The touch gesture **210***e* starts and is released within the second touch screen **14**.

[0149] Referring to FIG. **7**G, the portable device displays a second page **262** of the application menu in the second touch screen **14** in response to the detection of the touch gesture **210***e*. The first page **260** is replaced with the second page **262** and the second page **262** may be displayed while sliding in a direction of the first touch screen **12**. When the application menu includes a plurality of pages, the second touch screen **14** can display a page counter **262***a* together with the second page **262**. When one **262***b* of the icons included in the second page **262** of the application menu displayed in the second touch screen **14**, that is, the touch gesture **210***f* which starts at "ICON23" and is released on the first touch screen **12**, for example, a touch drag and drop is detected, the portable device proceeds to FIG. **7**H.

[0150] Referring to FIG. **7**H, the portable device displays an icon **262***c* which is a copy of the icon **262***b* selected by the touch gesture **210***f* in the first touch screen **12** in response to the detection of the touch gesture **210***f*. For example, the icon **262***c* may be disposed in a position where the touch gesture **210***f* is released.

[0151] When the home screen is displayed in the first touch screen **12** and the back button or the home button which is one of the physical buttons arranged in the first panel is input while the application list is displayed in the second touch screen **14** as illustrated in FIGS. **7**F to **7**H, the portable device stores icons displayed in the first touch screen **12** as the home screen and displays the next page **204** of the home screen instead of removing the application list from the second touch screen **14** as illustrated in FIG. **7**I.

[0152] As another embodiment, when the home screen is displayed in the first touch screen **12** and the menu button which is one of the physical buttons arranged in the first panel is input while the application menu for editing the home screen is displayed in the second touch screen **14**, the portable device displays the menu window **256** for completing the home screen editing. The menu window **256** includes at least one of a storage key and an ignore key. When a tap gesture **210***h* is detected from the storage key within the menu window **256**, the portable device stores icons, which include icons **260***c* and **262***c* copied from the application lists **260** and **262**, displayed in the first touch screen **12** as the home screen and displays previous information, that is, the second page **204** of the home screen instead of removing the application menu from the second touch screen **14** as illustrated in FIG. **7**J.

[0153] Although not illustrated, when the tap gesture is detected from the disregard key within the menu window **256**, the portable device removes the added icons **260***c* and **262***c* from the first touch screen **12** and returns to FIG. **7**A.

[0154] The aforementioned dual home screen function may be similarly applied to the application menu which is a basic application of the portable device. The application menu may be loaded by an icon or menu displayed in the home screen or an external button and provide more application lists, that is, icons in comparison with the home screen. The application menu provides a plurality of pages including a plurality of icon groups designated as the application menu.

[0155] The portable device provides two pages designated as the application menu through the display device including the first touch screen and the second touch screen arranged on

at least one foldable panel, and moves and navigates in the unit of two pages in response to a touch gesture of the user

[0156] FIGS. **8**A and **8**B illustrate a user interface of the application menu according to one or more exemplary embodiments.

[0157] Referring to FIG. **8**A, when a tap gesture is detected from the icon of the application list provided in the home screen or the physically configured home button is input, the application menu is executed and first and second pages **272** and **274** designated as the application menu are displayed in the first and second touch screens **12** and **14**. Each of the pages **272** and **274** includes one or more icons corresponding to each of the applications or application groups. When the application menu includes a plurality of pages, the first and second touch screens **12** and **14** may further display page counters **272***a* and **274***a* together with the first and second pages **272** and **274**.

[0158] When a pre-designated touch gesture **280***a* in a direction of the first touch screen **12**, for example, a flick or a touch drag is detected from one position of the second touch screen **14**, the portable device displays the next pages of the application menu, that is, a third page **276** including a third icon group and a fourth page **278** including a fourth icon group in the first and second touch screens **12** and **14** in response to the touch gesture **280***a* as illustrated in FIG. **8**B. Here, the third page **276** and the fourth page **278** may be displayed while sliding in a direction from the second touch screen **14** to the first touch screen **12** according to a motion direction and a speed of the touch gesture **280***a*. Similarly, the first and second touch screens **12** and **14** may further display page counters **276***a* and **278***a* together with the third page **276** and the fourth page **278**.

[0159] Although not illustrated, when a touch gesture in a direction from the first touch screen **12** to the second touch screen **14** is detected from the first or second touch screen **12** or **14**, the portable device displays previous pages of the application menu, that is, the first page **272** including the first icon group and the second page **274** including the second icon group in the first and second touch screens **12** an **14** in response to the touch gesture. Similarly, the first and second pages **272** and **274** may be displayed while sliding in a direction from the first touch screen **12** to the second touch screen **14** according to the touch gesture.

[0160] When the first and second touch screens **12** and **14** are connected not to be continuous by the hinge or separate connector, the pages may be displayed over both the first and second touch screens **12** and **14** when sliding through the hinge or connector. As a selectable embodiment, each icon within each page may be displayed while rapidly passing though the hinge or connector without being displayed over both the first and second touch screens **12** and **14**.

[0161] When a plurality of items such as icons of the home screen or the application menu or thumbnail images of a photo gallery application are displayed in two touch screens in a list or a grid form, the items may be scrolled (or translated) together by the touch gesture. The touch gesture may be a flick, a sweep, or a touch drag.

[0162] As one embodiment, the touch gesture may start at one position within the first touch screen **12** and be released at another position (farther from the second touch screen **14**) within the first touch screen **12**. As an embodiment, the touch gesture may start at one position within the second touch screen **14** and be released at another position (closer to the first touch screen **12**) within the second touch screen **14** or released at one position within the first touch screen **12**.

[0163] When the touch gesture starts and is released within one of the first and second touch screens **12** and **14**, the portable device replaces two pages of the items displayed in the first and second touch screens **12** and **14** with the next or previous two pages according to a motion direction of the touch gesture and then displays the replaced next or previous two pages. As another embodiment, the items displayed in the first and second touch screens **12** and **14** may be scrolled according to a motion direction, a motion distance, and a speed of the touch gesture. As an example, the portable device scrolls items corresponding to the distance or speed at which the touch gesture has moved.

[0164] As another embodiment, when the touch gesture is a flick which is generated in one of the first and second touch screens **12** and **14** and moves through the hinge (or connector), the portable device scrolls two pages displayed in the first and second touch screens **12** and **14** up to first or last two pages according to a motion direction of the touch gesture. As still another embodiment, when the touch gesture is the sweep which is generated in one of the first and second touch screens **12** and **14** and moves through the hinge (or connector), the portable device scrolls and displays the two pages displayed in the first and second touch screens **12** and **14** by the speed of the touch gesture.

[0165] When the items are scrolled, each of the items is not displayed over the two touch screens. That is, when each of the items reaches the hinge (or connector), it skips over the hinge and then is displayed in the next touch screen.

[0166] The touch screens of the portable device are switched to a portrait view mode or a landscape view mode based on a detection signal received from one or more accelerometers and then display information according to the switched mode. That is, the accelerometer may be included in the sensor module **170** and senses a rotation of the portable device. The accelerometer detects the switching between the portrait view mode in which the touch screens of the portable device are arranged in a left side and a right side and the landscape view mode in which the touch screens of the portable device are arranged in an upper side and a lower side, and generates the detection signal.

[0167] When the portable device is rotated substantially by 90 degrees and switched to the landscape view mode while displaying items in a grid form in the portrait view mode, the items within the grid may be rotated in a horizontal direction and scrolled. When the items are horizontally arranged, the items on the grid may be scrolled in a vertical direction according to a selection of the manufacturer or user or simultaneously scrolled in both an upper screen and a lower screen in a horizontal direction. Similarly, a movement of each grid is based on a direction and a speed of the motion of the touch gesture.

[0168] As another selectable embodiment, when a list is displayed in one touch screen and not displayed in the other touch screen in the portrait view mode, the list is displayed in both the two touch screens according to a setting of the manufacturer or user or information of another touch screen is extensively displayed in the two touch screens when the portable device rotates by 90 degrees.

[0169] When the portable device is rotated by 90 degrees and switched to the landscape view mode while displaying the home screen or the application menu in the portrait view mode, the portable device may operate to display a search

window or a pre-designated application (for example, a search window of an Internet browsing application) in at least one of the touch screens.

[0170] FIG. **8**C illustrates an example of a user interface for using the landscape view mode of the home screen according to an exemplary embodiment. Here, although a touch screen layout in a case where the portable device rotates by 90 degrees in a left direction is illustrated, the case can be applied when the portable device rotates by 90 degrees in a right direction. In the landscape view mode, it is described that the touch screen located in an upper part is the first touch screen **12**.

[0171] Referring to FIG. **8**C, when portable device is switched to the landscape view mode, that is, the portable device rotates by about 90 degrees while providing the home screen or pages of the application menu through the first and second touch screens **12** and **14** in the portrait view mode as illustrated in FIG. **6**A or FIG. **8**A, the first touch screen **12** displays a search window **282** interworking with the Internet browsing application or a pre-designated application. As one embodiment, the search window **282** may be displayed with or on the previously displayed home screen or page of the application menu of which a mode is switched to the landscape view mode. As another embodiment, the search window **282** may be displayed in an upper part of the second touch screen **14**. As a selectable embodiment, the dock area **216** may be displayed in a position of one of the first and second touch screens **12** and **14**, for example, a right end of the first touch screen **12** in the landscape view mode and shortcut icons within the dock area may be vertically arranged.

[0172] As a selectable embodiment, when the switching to the landscape view mode is performed, the second touch screen **14** replaces the page of the home screen with at least one pre-designated application, that is, a task manager screen including at least one running application **286** and displays the replaced page in the shown example. At this time, preview windows including simple information on each running application **286** or last executed information may be displayed in the task manager screen of the second touch screen **14** in an in activated state, for example, in a shaded state, or a shortcut icon of each running application **286** may be displayed in a grid or a list form. Further, the preview windows of the running application **286** may be displayed to partially overlap each other or displayed in a grid form not to overlap each other. The preview window refers to an area in a deactivated state in which a touch input is not allowed in comparison with a task screen which actually executes an application and provides a user interface such as the touch input.

[0173] As another embodiment, when the switching to the landscape view mode is performed, the second touch screen **14** displays the previously displayed home screen or page of the application menu of which a mode is switched to the landscape view mode and the search window **282** or displays a pre-designated application and the search window **282**. The pre-designated application may be designated by the manufacturer or user. For example, the pre-designated application may be a quick search application, an Internet browsing application, a recommended application list in the landscape view mode provided by the portable device, and another application designated by the user.

[0174] As a selectable embodiment, when a touch gesture of the user is detected from one of the preview windows (or shortcut icons) of the running application, the second touch screen **14** can display a task screen (providing an activated user interface) through an execution of the corresponding application.

[0175] When a touch gesture (for example, tap gesture) of the user is detected from an input area **282***a* included in the search window **282** displayed in the first touch screen **12** in the landscape view mode in which the first touch screen is located in the upper part and the second touch screen **14** is located in the lower part, a virtual keypad for receiving a text input, that is, a keypad area (not shown) is displayed in a predetermined area, for example, a lower part of the first touch screen **12**, a lower part of the second touch screen **14**, or the whole second touch screen **14**. When a keyword desired to be searched for through the keypad area is input by the user and then a touch gesture (for example, tap gesture) of the user is detected from a search execution key **282***b* displayed within the search window **282** or next to the search window **282**, search results corresponding to the keyword provided by the search application interworking with the search window **282** are displayed in the first touch screen **12**, the second touch screen **14**, or entire areas including the first and second touch screens **12** and **14**.

[0176] The portable device includes the display device including the first touch screen and the second touch screen arranged on at least one foldable panel and supports the following various view modes by using the two touch screens.

[0177] A multi mode or a multi tasking mode refers to a mode in which different applications are displayed in two touch screens, respectively, and each of the applications may respond to a touch gesture detected from the corresponding touch screen. For example, the first touch screen displays a photo gallery application, and the second touch screen displays an Internet browsing application. The portable device can swap information of the two touch screens by a pre-designated touch gesture. For example, the touch gesture includes two touches which are generated in the two touch screens, respectively and move to the hinge (or connector). The portable device can replace the photo gallery application of the first touch screen with the Internet browsing application and replace the Internet browsing application of the second touch screen with the photo gallery application in response to the detection of the two touches.

[0178] A main-sub mode (or slit mode) displays two task screens for one application in two touch screens, respectively. The two task screens provide task screens having different depths (or levels) of the application or task screens having different functions. That is, some applications may be configured to provide a plurality of task screens and the task screens may have different depths.

[0179] For example, the photo gallery application can provide a search screen including a plurality of thumbnail images and a full image screen displaying a picture image of one thumbnail image selected from the thumbnail images with a larger size, that is, with a full size through different touch screens. In this case, the full image screen may be designated to have a final depth. As another example, a music play application provides a playlist screen including a plurality of listed music and a music play screen for playing one of the music through different touch screens. In this case, the music play screen may be designated to have a final depth.

[0180] A full mode (or expanded mode) extensively displays one task screen of one application in two touch screens regardless of the hinge (or connector). For example, the first touch screen displays a first page of thumbnail images pro-

vided through the photo gallery application and the second touch screen displays a second page of the thumbnail images. As another example, one picture image is displayed to fully fills the whole of the first touch screen and the second touch screen. Here, displaying the picture image to fully fill the touch screens means that the picture image is displayed to fully fill horizontal widths and/or vertical widths of the first and second touch screens. As still another example, the first touch screen displays a map area having a first scale of a map application and the second touch screen displays a map area having a more detailed scale.

[0181] A change between the view modes may be achieved according to a running application, a detection of the touch gesture on the first and/or second touch screens, or a motion gesture of the portable device. The motion gesture includes a physical motion such as a rotation of the portable device and bending/folding of the first and/or second touch screens. Here, the bending/folding of the touch screens may refer to bending/folding within a predetermined relative angle. As a selectable embodiment, the change between the view modes is loaded by expanding a setting menu of the portable device or an upper status bar of the main touch screen or two touch screens and may be achieved by using a view mode changing button disposed within a quick panel allowing a quick control of a change in a status and a mode of the portable device.

[0182] FIGS. **9**A to **9**J illustrate examples of a change in the view mode according to a touch gesture according to one or more exemplary embodiments.

[0183] As illustrated in FIG. **9**A, the first touch screen **12** displays a first application **302** and the second touch screen **14** displays a second application **304**. For example, the first touch screen **12** displays the photo gallery application and the second touch screen **14** displays the Internet browsing application.

[0184] As illustrated in FIG. **9**B, when the portable device **100** detects a predetermined touch gesture **306** from the first and/or second touch screens **12** and/or **14**, the first application **302** of the first touch screen **12** is displayed in both the first touch screen **12** and the second touch screen **14**. At this time, as an example, the first application **302** may be displayed in the two touch screens **12** and **14** in the full mode or separately displayed in the two touch screens **12** and **14** through two task screens in the main-sub mode.

[0185] For example, the touch gesture **306** includes actually simultaneously generated two or more flicks which move in a direction from the first touch screen **12** to the second touch screen **14**. As another example, the touch gesture **306** includes actually simultaneously generated two or more touch drags which move in a direction from the first touch screen **12** to the second touch screen **14**. Specifically, when the portable device **100** detects a plurality of touches starting at the first touch screen **12** and detects that the detected touches simultaneously move in a direction from the first touch screen **12** to the second touch screen **14**, the portable device **100** displays the first application **302** in the both the first touch screen **12** and the second touch screen **14**. As one embodiment, the flicks or the touch drags may move through the hinge or connector between the first and second touch screens **12** and **14**.

[0186] Here, although it has been illustrated that the flicks or the touch drags are generated in parallel, the flicks or the touch drags can be generated irregularly. As a selectable embodiment, when an interval between the flicks or the touch drags is equal to or smaller than a predetermined value, that is, 2 cm, the portable device can recognize the touch gesture for changing the view mode. As another selectable embodiment, positions of the first touch screen **12** where the touches are first detected may be horizontally or vertically arranged side by side.

[0187] As still another embodiment, the touch gesture **306** includes a pinch gesture for expanding a selected area, that is, a pinch zoom-in gesture. As an embodiment, two touches of the pinch zoom-in gesture start at the first touch screen **12**, wherein a first touch is released within the first touch screen **12** and a second touch is released within the second touch screen **14**.

[0188] At this time, the task screen of the first application **302** may be displayed while sliding in a direction from the first touch screen **12** to the second touch screen **14** according to a motion (and a speed) of the touch gesture **306**. When the first and second touch screens **12** and **14** are connected by the hinge or separated connector not to be continuous, the task screen of the first application **302** may be displayed over both the first and second touch screens **12** and **14** when sliding through the hinge or connector.

[0189] Although not illustrated, the first application **302** enlarged over the first and second touch screens **12** and **14** by the touch gesture **306** may be reduced within the first touch screen **12** by another pre-designated touch gesture. As one example, when a pinch zoom-out gesture including two touches which start at first and second touch screens **12** and **14**, respectively and are released in one touch screen, for example, the second touch screen **14** is detected, the portable device reduces the first application **302** and displays the reduced first application **302** in the second touch screen **14**. At this time, the first touch screen **12** can display the second application **304** or the home screen.

[0190] [2-2. From the Full Mode to the Main-Sub Mode]

[0191] When the first application **302** is the photo gallery application, the photo gallery application **302** displays the first page of a plurality of thumbnail images in the first touch screen **12** as illustrated in FIG. **9**A. In response to the detection of the touch gesture **306** of FIG. **9**B, the portable device displays the first and second pages **302***a* and **302***b* of the plurality of thumbnail images in the first and second touch screens **12** and **14** as illustrated in FIG. **9**C. At this time, according to a motion of the touch gesture **306**, the first page **302***b* of the thumbnail images displayed in the first touch screen **12** slides to the second touch screen **14** and the second page **302***a* of the thumbnail images slides to the first touch screen **12** following the first page **302***b*.

[0192] When a plurality of items such as the thumbnail image are displayed in the first and second touch screens **12** and **14** in a grid form, the items may be scrolled (that is, translated) according to a motion and a speed of the touch gesture as illustrated and described in FIGS. **8**A and **8**B. That is, when a touch gesture such as the flick or sweep is generated in one of the first and second touch screens **12** and **14**, the thumbnail images are scrolled according to a motion direction and a speed of the touch gesture. At this time, the thumbnail images may be scrolled over the hinge (or connector) between the first and second touch screens **12** and **14**.

[0193] Referring to FIG. **9**D, the portable device **100** detects a touch gesture **310** (for example, tap gesture) of the user on a first thumbnail image **306** which is one of the thumbnail images **302***a* of the first touch screen **12**, that is, "thumbnail21". Then, as illustrated in FIG. **9**E, the second touch screen **14** replaces the first page **302***b* of the thumbnail

images with a picture image **306***a* of the first thumbnail image **306** and displays the replaced picture image **306***a* in response to the detection of the touch gesture **310**. The picture image **306***a* has a larger size than the first thumbnail image **306** and may be displayed to fill one of a horizontal width and a vertical width of the second touch screen **14**. As illustrated in FIG. **9**F, when a touch gesture **312** (for example, tap gesture) of the user is detected on a second thumbnail image **308** among the thumbnail images **302***a* of the first touch screen **12**, the picture image **306***a* of the first thumbnail image **306** is replaced with a picture image **308***a* of the second thumbnail image **308** and the replaced picture image **308***a* is displayed in the second touch screen **14** in response to the detection of the touch gesture **312**.

[0194] Referring to FIG. **9**G, the portable device **100** detects a predetermined touch gesture **320** on the first picture image **308***a* displayed in the second touch screen **14** in a state where the first touch screen **12** displays the plurality of thumbnail images **302***a* provided through the photo gallery application and the second touch screen **14** displays the first picture image **308***a* of the first thumbnail image selected from the plurality of thumbnail images **302***a*. Then, as illustrated in FIG. **9**H, the portable device **100** enlarges the first picture image **308***a* and displays the enlarged first picture image **308***a* to fully fill the first touch screen **12** and the second touch screen **14**. The first picture image **308***b* expands up to the first touch screen **12** while covering the thumbnail images **302***a* of the first touch screen **12**. When the expansion is completed, a part (for example, a left half) of the first picture image **308***a* is displayed in the first touch screen **12** and the remaining part (for example, a right half) of the first picture image **308***b* is displayed in the second touch screen **14**. As a selectable embodiment, when the first picture image **308***b* is an image generated in the portrait view mode (vertically long image), the first picture image **308***b* may be displayed in one of the first and second touch screens **12** and **14**.

[0195] As one embodiment, the touch gesture **320** includes a pinch gesture of expanding a selected area, that is, a pinch zoom-in gesture. First and second touches of the pinch zoom-in gesture are all generated in the second touch screen **14**, wherein the first touch is released within the second touch screen **14** and the second touch is released within the first touch screen **12**. As another embodiment, the touch gesture **320** includes two touch drags which are simultaneously generated in the second touch screen **14** and move farther from each other in approximately opposite directions. As one example, at least one of the touch drags may start at one position of the second touch screen **14** and end at another position of the second touch screen **14**. As another example, at least one of the touch drags may start at one position of the second touch screen **14** and end at one position of the first touch screen **12**.

[0196] When the portable device **100** substantially simultaneously or sequentially detects two touches from the second touch screen **14** and substantially simultaneously detects that the detected touches are father from each other in opposite directions or continuously farther from each other in approximately opposite directions, the portable device **100** expands the first picture image **308***a* and displays the expanded the first picture image **308***a* to fully fill the first touch screen **12** and the second touch screen **14**.

[0197] Although not illustrated, when a pinch zoom-out gesture including two touches which start at the first and second touch screens **12** and **14**, respectively and are released on one touch screen, for example, the first touch screen **12** is detected while the first picture image **308***a* is displayed in the first and second touch screens **12** and **14**, the portable device reduces the first picture image **308***a* and displays the reduced first picture image **308***a* to fully fill the first touch screen **12**.

[0198] As illustrated in FIG. **9**I, the portable device **100** detects a touch gesture **322** in a predetermined direction from the first picture image **308***c* displayed in both the first touch screen **12** and the second touch screen **14**, for example, a flick or a touch drag in a direction from the second touch screen **14** to the first touch screen **12** (or opposite direction). Then, as illustrated in FIG. **9**J, the portable device **100** replaces the first picture image **308***c* displayed in the first touch screen **12** and the second touch screen **14** with a second picture image **324** continuous to the first picture image **308***c* and displays the replaced second picture image **324** in response to the touch gesture **322**. At this time, the first picture image **308***c* may be removed while sliding in a direction from the second touch screen **14** to the first touch screen **12** (or opposite direction) according to a direction and a speed of a motion of the touch drag **322**. The second picture image **324** slides within the first touch screen **12** and the second touch screen **14** while following the first picture image **308***c*.

[0199] As a selectable embodiment, the touch drag **322** may be performed on one touch screen. As another selectable embodiment, the touch drag **322** may be performed over the two touch screens **12** and **14**, that is, passing through the hinge.

[0200] The portable device can provide a familiar and a new home user interface such as a foldable wallet or compact powder through the display device including the first touch screen and the second touch screen arranged on at least one foldable panel. It is referred to as a pocket mode home screen in this specification. The portable device can provide the home screen as illustrated in FIG. **6** or the pocket mode home screen which will be described later according to a setting made when the portable device is manufactured or a setting of the user. As an embodiment, the pocket mode home screen may be usefully used in a double screen mode or an in-folded screen mode.

[0201] FIGS. **10**A to **10**H illustrate user interfaces of the pocket mode home screen according to one or more exemplary embodiments.

[0202] Referring to FIG. **10**A, the first touch screen **12** displays areas **402**, **404**, **406**, and **408** in a form of cards, for example a credit card or identification card, each stored in a card slot of a wallet which include some information on widgets or applications designated as the home screen and further displays a dock area **410** including icons of frequently used applications. Each of the areas **402**, **404**, **406**, and **408** may have a form of the received credit card partially hidden by a graphic image embodying a slit for receiving the credit card in the wallet and may be vertically aligned with the received credit cards. The areas **402** to **408** display at least one of simple information provided by the widget or application and a shortcut key for executing a predetermined function. The simple information includes information which the user desires to first know through the application and may be updated in real time according to the application. For example, an area related to a message application can display whether a newly received message exists through a notice such as a flickering phrase of "NEW". As a selectable

embodiment, the area **408** located in a bottommost part may have a form of the received credit card partially hidden by a slit of a diagonal line.

[0203] When a pre-designated touch gesture, for example, a tap gesture or a touch and hold is detected from one of the areas **402**, **404**, **406**, and **408**, the portable device displays an application of the corresponding area to occupy the whole of the first touch screen **12** or the second touch screen **14** or displays the application to occupy the whole of the first touch screen **12** and the second touch screen **14**.

[0204] At least some of the areas (for example, the areas **402**, **404**, and/or **408**) display simple information provided by the widget or application, and the simple information may be enlarged and displayed in response to a pre-designated touch gesture. For example, the area **402** of a schedule widget includes today's date and time and titles of N schedules (for example, one or two schedules), the area **404** of a weather widget includes a current city, a current temperature, and a weather icon, and the area **408** of a business card widget includes a person's name in contact information, shortcut keys for connecting a call and/or sending a message, and a picture image. The picture image may be replaced with a default image.

[0205] As one embodiment, in response to the detection of a predetermined touch gesture, for example, a flick or a touch drag up from one of the areas **402**, **404**, and **408**, the portable device expands the corresponding area in a form of the credit card partially withdrawn from a graphic image having a slit form. The expanded area includes more information in comparison with the corresponding widget or application. The expanded area may be reconstructed to an original size in response to the detection of a touch drag down from the enlarged area or the detection of a touch gesture from another area.

[0206] At least some of the areas (for example, the area **406**) display shortcut keys for functions provided by the application while operating as the background. For example, the area **406** of a music play application displays a status bar showing an album image, a title, a musician, and a play status of a played music and additionally provides shortcut keys such as a previous music selecting key, a stop/play key, and a next music selecting key. When a tap gesture is detected from one of the shortcut keys, the music play application executes a function corresponding to the corresponding shortcut key as the background.

[0207] Referring to FIG. **10**B, the portable device detects a pre-designated touch gesture **420**, for example, a flick or a touch drag up from the area **402** of the schedule widget. Referring to FIG. **10**C, in response to the detection of the touch gesture **420**, the area **402** of the schedule widget is expanded in a top direction and then the expanded area **402***a* is displayed. The expanded area **402***a* displays time and titles of M schedules (for example, three or more schedules) and may further selectively display a weekly schedule according to an expanded length. The area **402** may be expanded in a top direction according to a movement of the touch gesture **420** and expanded to reach a terminus of the first touch screen **12** within a predetermined maximum size.

[0208] Referring to FIG. **10**D, the portable device detects a pre-designated touch gesture **422**, for example, a tap gesture or a touch drag from one of the shortcut keys and the status bar included in the area **406** of the music play application. Then, the music play application performs a function of playing music, playing previous music, stopping music, playing next music, or moving a play position. The area **406** of the music play application which operates as the background and does not require an area expansion may be embodied and displayed in a form of a sewed label, not the form of the received credit card.

[0209] Referring to FIG. **10**E, the portable device detects a pre-designated touch gesture **424**, for example, a flick or a touch drag up from the area **404** of the weather widget. In response to the detection of the touch gesture **424**, the area **404** of the weather widget is expanded in a top direction and then the expanded area is displayed. The expanded area **404***a* may further display more detailed information on the weather, for example, additional information on today's weather and weekly weather. The area **404** of the weather widget may be expanded in a top direction according to a movement of the touch gesture **424** and expanded to reach a terminus of the first touch screen **12** within a predetermined maximum size. The area **404** of the weather widget may be expanded to cover at least some of the area **402** of the schedule widget which had been located in an upper part. As one embodiment, the area **404** cannot be expanded to exceed a predetermined maximum range. When an expanded length of the expanded area **404***a* reaches the maximum range, the expanded area **404***a* remains in an expanded state or is reconstructed to the area **404** in an original size.

[0210] Referring to FIG. **10**F, the portable device detects a pre-designated touch gesture **426**, for example, a flick or a touch drag up in a top direction from the area **408** of the business card widget. In response to the detection of the touch gesture **426**, the area **408** of the business card widget is expanded in a top direction and the expanded area **408***a* is displayed. The expanded area **408***a* may further include a picture image **408***d* of the person in the contact information and more detailed information **408***e* in comparison with those before the expansion, for example, a mobile phone number, an office phone number, a birthday, an address, an e-mail address and the like. The area **408** may be expanded to cover at least one widget (**406**, **404**, and/or **402**) which had been located in upper parts according to a movement of the touch gesture **426** and expanded to reach a terminus of the first touch screen **12** within a predetermined maximum range. As one embodiment, the area **408** cannot be expanded to exceed a predetermined maximum rage. When an expanded length of the expanded area **408***a* reaches the maximum range, the expanded area **408***a* remains in an expanded state or is automatically returned to the area **408** in an original size.

[0211] Referring to FIG. **10**G, the area **408** of the business card widget and the expanded area **408***a* display at least one of shortcut keys **408***b* and **408***c* for connecting a call and sending a message. When a pre-designated touch gesture **428**, for example, a tap gesture is detected from the shortcut key **408***b* for connecting the call, the portable device proceeds to FIG. **10**H.

[0212] Referring to FIG. **10**H, the portable device attempts to connect a call to a phone number related to the area **408** of the business card through a call application and displays a dialing screen **408***f* of the call application in some or all of the first and second touch screens **12** and **14**. The dialing screen **408***f* may replace at least a part of the pocket mode home screen of the first and second touch screens **12** and **14** and then be displayed. In the shown example, the dialing screen **408***f* is displayed in the whole of the first touch screen **12** and includes a call participant identification area including a picture image and a phone number of a counterpart call partici-

pant and soft keys of mid-call functions such as adding a phone number, calling a dial pad, ending the call, connecting a speakerphone, mute, and a headset. As a selectable embodiment, the second touch screen **14** maintains the home screen, is turned off, or provides a guide message screen **408***g* for recommending to fold the portable device for the call.

[0213] Although not illustrated, when a tap gesture is detected from the shortcut key **408***c* for sending the message included in the area **408** of the business card widget or the expanded area **408***a*, a text input area and a virtual keypad for sending the message provided by the message application are displayed in some or all of the first touch screen **12**. As one embodiment, the virtual keypad is displayed while partially covering the lower part of the first touch screen **12**. As another embodiment, the virtual keypad is continuously displayed over the lower part of the first touch screen **12** and a lower part of the second touch screen **14**. As a selectable embodiment, the keypad is displayed in the lower part of the first touch screen **12** and may be expanded through an expand button provided within the virtual keypad and displayed in both the lower parts of the first and second touch screens **12** and **14**.

[0214] FIGS. **11**A to FIG. **11**F illustrate user interfaces of the home screen in the pocket mode according to one or more exemplary embodiments.

[0215] Referring to FIG. **11**A, the second touch screen **12** displays first areas **412** of applications designated as the home screen. The first areas **412** are displayed in a form of stored cards partially hidden by a graphic image in a form of a slit for receiving the cards within a wallet and include at least one of simple information (for example, two to three lines) provided by each application and a shortcut key **416** for executing a predetermined function. The simple information may be automatically updated in real time according to the application. As one embodiment, an area of a Social Networking Service (SNS) application can display whether an update is recently performed and display a part of contents of a recently updated message.

[0216] As a selectable embodiment, an area **414** of a photo gallery application which is one of the areas displayed in the second touch screen **12** can provide a predetermined number of thumbnail images. As an embodiment, the area **414** additionally includes a shortcut key for changing view modes of the thumbnail images. For example, the shortcut key includes a slider switch. Further, the thumbnail images may be scrolled according to an arranged direction of the thumbnail images within the area **414**, for example, a motion direction and a speed of a touch gesture in a horizontal direction. As a selectable embodiment, because the area **414** of the photo gallery application does not need an area expansion, the area **414** may be embodied and displayed in a form of a sewed label, not the form of a received credit card.

[0217] The second touch screen **14** displays the first areas **412** including simple information on a predetermined number of applications, for example, three applications according to a setting of the home screen in the pocket mode. It is possible that the first areas **412** are sequentially arranged in a vertical direction like the stored cards. For example, each of the first areas **412** includes a name of a graphic symbol of the application, information of one or two lines provided by the application, and an indicator showing an updated state of the application. When a pre-designated touch gesture (for example, a flick up or a touch drag up) is detected from each of the first areas **412**, the corresponding first area **412** may be expanded to a top direction within a predetermined maximum size.

[0218] Referring to FIG. **11**B, when a pinch gesture **430** for reducing the area, that is, a pinch zoom-out is detected from the first areas **412**, each of the first areas **412** is reduced and reduced areas **412***a* of other applications are further displayed in a space within the second touch screen **14** generated by the reduced areas. That is, the reduced first areas **412** and the second areas **412***a* including the reduced areas of the other applications include more applications (for example, six or more applications) in comparison with the first areas **412**, and accordingly display less information in comparison with the first areas **412**, for example, only a name, a graphic symbol, and an update indicator of the application with one line.

[0219] As illustrated in FIG. **11**C, when a touch gesture **432** in a predetermined direction, that is, a flick up/down or a touch drag up/down is detected from the second areas **412***a*, the portable device proceeds to FIG. **11**D. Referring to FIG. **11**D, the portable device displays reduced areas **412***b* of applications designated as the home screen in the pocket mode while scrolling the reduced areas **412***b* in a top direction or a bottom direction in response to the touch gesture **432**.

[0220] When a pinch gesture **434** for expanding the area, for example, a pinch zoom-in is detected from the reduced areas **412***b*, the portable device proceeds to FIG. **11**E. Referring to FIG. **11**E, the reduced areas **412***b* according to the pinch gesture **434** are expanded to have an original size **412***c* and reduced areas (for example, topmost part and/or bottommost areas) of some applications by the area expansion are not displayed in the second touch screen **14** anymore. The areas **412***c* include a number of applications according to a basic setting of the home screen in the pocket mode, for example, five applications.

[0221] Referring to FIG. **11**F, when a pre-designated touch gesture **436**, for example, a flick in a top direction or a touch drag up is detected from one of the reduced areas **412***a* and **412***b* or the areas **412** and **412***c* having the original sizes, the corresponding area is expanded in a top direction and the expanded area **412***d* is displayed. The expanded area **412***d* may further display more detailed information of the corresponding application, for example, a recently uploaded image and more information on a recent activity. The expanded area **412***d* is generated by an expansion in a top direction according to a movement of the touch gesture **436** and may be expanded to reach a predetermined maximum range. According to a type of application, the expanded area **412***d* can provide at least one of a text input window having a size which can be included in the expanded area **412***d* and soft keys for predetermined functions together with the more detailed information.

[0222] As one example, the area in the form of the received credit card related to the message application is expanded by a touch drag up of the user and displays a miniaturized text input window and a transmission shortcut key in an area secured through the expansion.

[0223] As a selectable embodiment, when the pre-designated touch gesture **436**, for example, a tap gesture is detected from a first area which is one of the areas **412**, **412***a*, **412***b*, and **412***c*, the portable device expands the first area and displays the expanded first area in the second touch screen **14**. At this time, the first area may be expanded in the same or similar sizes to those of all of the areas **412**, **412***a*, **412***b*, and **412***c* or expanded to occupy the whole second touch screen **14**. For

example, the area in the form of the received credit card related to the social network service application is expanded by a tap gesture by the user and displays a predetermined number of recently received messages in an area secured through the expansion. The expanded area may include short-cut keys such as forward, reply, copy and the like on each message. The expanded area may be reconstructed to have an original size by a touch on another area or a pinch gesture.

[0224] As another selectable embodiment, when the pre-designated touch gesture **436**, for example, a tap gesture is detected from the first area which is one of the areas **412**, **412***a*, **412***b*, and **412***c*, the portable device displays an application corresponding to the first area in the whole second touch screen **14**.

[0225] The portable device can display a gallery map application corresponding to a combination of the photo gallery application and the map application through the display device including the first touch screen and the second touch screen arranged on at least one foldable panel. The first touch screen and the second touch screen displays a map and at least one picture image registered in the map, respectively. The gallery map application can register and manage at least one picture image of one position on the map. As one embodiment, the gallery map application receives the picture image registered in a server located in the Internet and position information on the picture image from the server, links the picture image with a position indicated by the position information, and manages the linked information. The picture image may be shot or generated in the position or include contents related to the position. As one embodiment, the gallery map application may be useful for the double screen mode or the in-folded screen mode.

[0226] FIGS. **12**A to **12**I illustrate user interfaces of the gallery map application according to one or more exemplary embodiments.

[0227] Referring to FIG. **12**A, the first touch screen **12** displays a map area **502** provided by the gallery map application. For example, the map area **502** may include a geographical area of a predetermined scale including a current position of the user or a geographical area of a predetermined scale including a position designated by the user. The map area **502** includes at least one of position indicators **504***a*, **504***b*, and **504***c* indicating a search result, a tourist attraction spot, or a position in which the picture image is registered.

[0228] The second touch screen **14** displays a gallery area **506***a* in which thumbnail images of the picture images registered in positions included in the map area **502** are listed. The gallery area **506***a* lists at least some of the thumbnail images of the registered picture images of the position indicators **504***a*, **504***b*, and **504***c* included in the map area **502**. When all the thumbnail images cannot be simultaneously displayed in the gallery area **506***a*, the thumbnail images may be divisibly displayed in a plurality of pages, and the second touch screen **14** can scroll the thumbnail images according to a touch drag detected from the gallery area **506***a*. The thumbnail images may be displayed in a grid view mode, a list view mode, or a group view mode according to a basic setting or a setting of the user. In the group view mode, thumbnail images for each group may be displayed in a disordered form where at least some of the thumbnail images overlap.

[0229] When a touch gesture **512** in a predetermined direction, for example, a flick or a touch drag is detected from the map area **502** displayed in the first touch screen **12**, a map area **502***a* moved according to a motion of the touch gesture **512** is displayed in the first touch screen **12** as illustrated in FIG. **12**B. Then, the second touch screen **14** displays a gallery area **506***b* in which at least some of the thumbnail images of the registered picture images of the position indicators **504***b*, **504***c*, **504***d*, and **504***e* included in the map area **502***a* are listed.

[0230] Although not illustrated, when a pre-designated touch gesture, for example, a tap gesture is detected from one (for example, the position indicator **504***c*) of the position indicators **504***b*, **504***c*, **504***d*, and **504***e* displayed on the map area **502***a* displayed in the first touch screen **12**, the gallery area of the second touch screen **14** can display at least some of the thumbnail images of the registered picture image of the selected position indicator **504***c*.

[0231] Referring to FIG. **12**C, the first touch screen **12** displays the map area **502***b* and the gallery area **506***c* of the second touch screen **14** displays the thumbnail images of the registered picture images of the positions included in the map area **502***b*. The portable device detects a pre-designated touch gesture **514**, for example, a tap gesture or a touch and hold from one **504***a* of the position indicators **504***a*, **504***c*, **504***d*, **504***f*, and **504***g* displayed on the map area **502***b* displayed in the first touch screen **12**. Then, in response to the detection of the touch gesture, the first touch screen **12** displays thumbnail images **520** of the registered images of the position indicator **504***a* in an area adjacent to the position indicator **504***a* **514** as illustrated in FIG. **12**D. The thumbnail images **520** may be displayed in the grid form or in the group view mode where at least some of the thumbnail images **520** overlap each other, and a name **520***a* of the registered image group of the position indicator **504***a*, for example, "A Castle" may be displayed together with the thumbnail images **520**.

[0232] Referring to FIG. **12**E, the portable device detects a touch gesture from one **504***g* of the position indicators **504***a*, **504***c*, **504***d*, **504***f*, and **504***g* displayed on the map area **502***b* displayed in the first touch screen **12** and displays thumbnail images **522** of registered images of the position indicator **504***g* in an area adjacent to the position indicator **504***g*. The thumbnail images **522** may be displayed in the grid form or the partially overlapping form, and a name **522***b* of the registered image group of the position indicator **504***g*, for example, "B Café" may be displayed together with the thumbnail images **522**.

[0233] The second touch screen **14** provides a soft key **530** for selecting the view mode to change the view mode of the gallery area **506***c* into the group view mode or the grid view mode. For example, the soft key **530** includes a slider switch. When a touch of the user is detected from the slider switch and the slider switch moves to an icon indicating the view mode in a group form according to the touch, a gallery area **506***e* of the second touch screen **14** groups the registered thumbnail images of the position indicators **504***a*, **504***c*, **504***d*, **504***f*, and **504***g* included in the map area **502***b* displayed in the first touch screen **12** for each position and then displays the grouped thumbnail images. In the group view mode, the thumbnail images of each group may be displayed in a disordered form where the thumbnail images partially overlap each other.

[0234] Referring to FIG. **12**F, the first touch screen **12** displays the map area **502***b* provided by the gallery map application. The map area **502***b* includes position indicators **504***a*, **504***c*, **504***d*, **504***f*, and **504***g* indicating a search result, a registered tourist attraction spot, or a position in which the picture image is registered. The second touch screen **14** includes a gallery area **506***e* in which thumbnail images of the

picture images registered in positions included in the map area **502***b* are listed. The gallery area **506***e* displays at least some of the registered thumbnail images of the position indicators **504***a*, **504***c*, **504***d*, **504***f*, and **504***g* included in the map area **502***b* in the grid view mode or the group view mode.

[0235] When a pre-designated touch gesture **530**, for example, a tap gesture or a touch and hold (that is, long tap) is detected from one (for example, the position indicator **504***a*) of the position indicators **504***a*, **504***c*, **504***d*, **504***f*, and **504***g* on the map area **502***b*, the first touch screen **12** displays a menu window **530***a* for selecting a path in an area adjacent to the position indicator **504***a*. The menu window **530***a* includes a start key and an arrival key. When a tap gesture **530***b* is detected from the start key of the menu window **530***a*, the gallery map application designates the position indicator **504***a* as a start position in response to the detection of the tap gesture **530***b*. At this time, the position indicator **504***a* may be changed to a conspicuous color, for example, red in order to be visually distinguished from other displayed position indicators **504***c*, **504***d*, **504***f*, and **504***g*.

[0236] Referring to FIG. **12**G, when a pre-designated touch gesture **532**, for example, a tap gesture or a touch and hold is detected from one (for example, the position indicator **504***d*) of the position indicators **504***a*, **504***c*, **504***d*, **504***f*, and **504***g* on the map area **502***b* displayed in the first touch screen **12**, the first touch screen **12** displays a menu window **532***a* for selecting a path in an area adjacent to the position indicator **504***d*. The menu window **532***a* includes a start key and an arrival key. When a tap gesture **532***b* is detected from the arrival key of the menu window **532***a*, the gallery map application designates the position indicator **504***d* as an arrival position in response to the detection of the tap gesture **532***b*. At this time, the position indicator **504***d* may be changed to a conspicuous color, for example, red in order to be visually distinguished from other displayed position indicators **504***c*, **504***f*, and **504***g*.

[0237] When the start position or the arrival position is registered, the gallery map application displays a slide show control area **542** including information on the path from the start position to the arrival position in a lower part of the first touch screen **12**. The slide show control area **542** may be displayed while partially covering the map area **502***b*.

[0238] Referring to FIG. **12**H, when the start position **504***a* and the arrival position **504***d* are registered, the gallery map application displays a path **540** from the start position **504***a* to the arrival position **504***d* in a graphic line form in the map area **502***b* of the first touch screen **12**. The path **540** is displayed along an actual road between the start position **504***a* and the arrival position **504***d* and may include at least one indicator **504***c* existing between the start position **504***a* and the arrival position **504***d* as an intermediate position. The slide show control area **542** displayed in the lower part of the first touch screen **12** may include a path trace bar **544** showing position indicators included in the path from the start position to the arrival position and movement states according to the path and a slide show view key **546** for selecting to initiate a slide show of the picture images included in the path **540**. As another embodiment, the slide show control area **542** is displayed in response to the display of the path **540**.

[0239] When a pre-designated touch gesture, for example, a tap gesture is detected from the slide show view key **546**, the portable device removes the map area **502***b* from the first touch screen **12** and reproduces the slide show of the picture images registered in the positions included in the path **540** as illustrated in FIG. **12**I. As one embodiment, the picture images are sequentially displayed to completely fill at least one of a horizontal width and a vertical width of the first touch screen **12** during the slide show. During the slide show, the path trace bar **544** of the slide show control area **542** includes a current slide indicator indicating a position of the picture image currently displayed in the first touch screen **12** and the slide show control area **542** provides a slide show stop key **548** for selecting to stop the slide show instead of the slide show view key **546**.

[0240] As a selectable embodiment, the slide show control area **542** may be hidden from the first touch screen **12** during the slide show in order not to interrupt viewing of the slid picture images. The slide show control area **542** may be displayed again in a predetermined area of the first touch screen **12** for the slide show by, for example, detecting a predetermined touch gesture in the lower part of the first touch screen.

[0241] The portable device can display a task manager area including icons of a plurality of running applications through the display device including the first touch screen and the second touch screen arranged on one foldable panel. As another embodiment, the task manager area may include icons of favorite applications designated by the user. The task manager area may be disposed in pre-designated positions of the first touch screen and the second touch screen, for example, lower parts of the first touch screen and the second touch screen. That is, some of the icons of the task manager area are displayed in the lower part of the first touch screen and the remaining icons are displayed in the lower part of the second touch screen. The icons of the task manager area may be continuously disposed in the lower parts of the first and second touch screens.

[0242] FIGS. **13**A to **13**J illustrate user interfaces of a task manager panel according to one or more exemplary embodiments.

[0243] Referring to FIG. **13**A, the first touch screen **12** displays a task screen **610** of a first application and the second touch screen **14** displays a task screen **612** of a second application. The task screens **610** and **612** have sizes to fill displayable areas of the first and second touch screens **12** and **14**, display information executed by each application, and provide a user interface. Although a multi mode in which the first and second touch screens **12** and **14** display the task screens **610** and **612** of different applications is illustrated herein, an execution of the task manager which will be described below may be similarly applied to a case where the home screen or the application menu is displayed in at least one of the first and second touch screens **12** and **14** or the first and second touch screens **12** and **14** operate in the main-sub mode or the full mode.

[0244] The portable device detects a predetermined command or a user gesture for executing the task manager. The command or the user gesture includes, for example, at least one of an input of a physical button included in the housing of the portable device, a detection of a touch on a predetermined area within at least one of the first and second touch screens **12** and **14**, a detection of a touch on a soft key provided through at least one of the first and second touch screens **12** and **14**, and a control of a soft menu.

[0245] FIG. **13**A illustrates an example of executing a task manager function by using one **600***a* of the physical buttons arranged in a second panel including the second touch screen **14**. The button **600***a* for executing the task manager function

may be, for example, a home button which is one of the touch detection typed physical buttons arranged in the second panel. When the portable device detects an input **602** of the home button **600***a* arranged in the second panel, for example, a tap gesture on the home button or a touch and hold, the portable device proceeds to FIG. **13**B.

[0246] Referring to FIG. **13**B, the portable device displays task manager panels **604***a* and **604***b* in predetermined positions of the first and/or second touch screens **12** or/and **14**, for example, lower parts of the first and second touch screens **12** and **14** in response to the input **602**. The task manager panels **604***a* and **604***b* form the task manager areas and are located in different touch screens **12** and **14** and disposed close to each other to be continuous. As another embodiment, the task manager panels **604***a* and **604***b* may be disposed in basically set positions or positions designated by the user, for example, upper parts of the first and/or second touch screens **12** and **14**, a left part of the first touch screen **12**, a right part of the second touch screen **14**, and a right part of the first touch screen **12**, and a left part of the second touch screen **14**.

[0247] With displays of the task manager panels **604***a* and **604***b*, the first and second touch screens **12** and **14** replace the task screens **610** and **612** of the first and second applications with preview windows **610***a* and **612***a* of the first and second applications. The preview windows **610***a* and **612***a* have smaller sizes in comparison with the task screens **610** and **612** and may be displayed with a shadow in order to indicate a deactivated state in which the user interface such as a touch input or the like is not allowed.

[0248] In the shown example, the task manager panels **604***a* and **604***b* are divisibly displayed through two touch screens including the first touch screen **12** and the second touch screen **14** and include at least some of the icons of the running applications. For example, each of the task manager panels **604***a* and **604***b* may include a maximum of four icons which do not overlap each other. That is, the first task manager panel **604***a* includes icons of first to fourth running applications App#**1** to App#**4**, and the second task manager panel **604***b* includes icons of fifth to eighth running applications App#**5** to App#**8**. When the number of running applications exceeds a maximum number of icons which can be displayed in the task manager panels **604***a* and **604***b*, that is, when the number of running applications exceeds eight, the task manager panels **604***a* and **604***b* display only eight icons and may further display other icons by scrolling the displayed icons in response to a touch gesture.

[0249] As one embodiment, orders of the applications included in the task manager panels **604***a* and **604***b* are based on a last played time. Icons **610***b* and **612***b* of the first and second applications displayed in the first and second touch screens **12** and **14** before the execution of the task manger are located in first and second positions within the task manager panels **604***a* and **604***b*. When the number of running applications is smaller than a maximum number (for example, eight) of icons which can be included in the two task manager panels **604***a* and **604***b*, the icons of the running applications may be center-aligned from the hinge between the first and second touch screens **12** and **14**. The center-aligned icons may move within the first task manger panel **604***a* or the second task manager panel **604***b* by a touch drag in a left direction or a right direction.

[0250] An end indicator **606** (for example, in an X form) for immediately ending the corresponding running application may be attached to each icon. A tap gesture is detected from the end indicator **606** attached to the application App#**8** which is one of the displayed icons, the portable device ends the application App#**8** of the corresponding icon. When a preview screen of the application App#**8** is displayed within the first and/or second touch screens **12** and/or **14**, the preview screen of the application App#**8** of the corresponding touch screen is replaced with one page of the home screen. When the preview screen of the application App#**8** is not displayed within the first and/or second touch screens **12** and/or **14**, the application App#**8** ends as the background.

[0251] Referring to FIG. **13**C, the portable device detects a touch gesture **602***a* acting in parallel to a direction in which the icons are arranged on the first and/or second task manger panels **604***a* and **604***b*, for example, a flick or a touch drag in a left direction or a right direction and scrolls and displays the icons displayed in the first and second task manager panels **604***a* and **604***b* according to the touch gesture **602**. The icons designated as the task manger may be scrolled while rotating. When passing though the hinge between the first and second touch screens **12** and **14** according to the touch gesture **602***a*, each of the icons may be displayed over the two touch screens **12** and **14**. As another embodiment, when passing through the hinge according to the touch gesture **602***a*, each of the icons is displayed to skip the hinge without being divisibly displayed in the two touch screens **12** and **14**.

[0252] Referring to FIG. **13**D, the portable device detects a predetermined touch gesture **602***b* which starts at one **614***b* of the icons included in the first and/or second task manager panels **604***a* and/or **604***b* and heads for outsides of the first and/or second task manger panels **604***a* and/or **604***b*, for example, a touch drag which starts at the icon **614***b* of the application App#**5** and is released at an area included in the first touch screen except for the first task manager panel **604***a*. As illustrated in FIG. **13**E, the first touch screen **12** replaces the preview window **610***a* of the first application displayed in the first touch screen **12** with a preview window **614***a* of the application App#**5** related to the icon **614***b* and displays the replaced preview window **614***a* in response to the detection of the touch drag **602***b*.

[0253] Referring to FIG. **13**F, the portable device detects a touch drag **602***c* from an icon **616***b* of the application App#**11** included in the first task manager panel **604***a* to an area included in the first touch screen **12** except for the first task manager panel **604***a*. The touch drag **602***c* starts at the icon **616***b* and is released at one point within an area included in the first touch screen **12** except for the first task manger panel **604***a*. As illustrated in FIG. **13**G, the first touch screen **12** replaces the preview window **614***a* of the application App#**5** with the preview window **616***a* of the application App#**11** related to the icon **616***b* and displays the replaced preview window **616***a* in response to the detection of the touch drag **602***c*.

[0254] Although it has been illustrated that the replacement of the preview window made in the first touch screen **12** in FIGS. **13**D to **13**G, the preview window of the application corresponding to the icon included in the first task manager panel **604***a* may be drawn to the second touch screen **14** or the preview window of the application corresponding to the icon included in the second task manager panel **604***b* may be drawn to the first touch screen **12** according to a start position and a release position of the touch drag.

[0255] Referring to FIG. **13**G, the portable device detects a pre-designated touch gesture **602***d* headed for an inside of the second task manager panel **604***b* displayed in the second

touch screen **14**, for example, a touch drag which starts at one position of the preview window **612***a* and is released at one position within the second task manager panel **604***b* from the preview window **612***a* of the second application displayed in the second touch screen **14**. Then, the second touch screen **14** converts the preview window **612***a* to the icon **612***b* of the second application in response to the detection of the touch drag **602***d* and moves the icon **612***b* to the second task manager panel **604***b* according to the touch drag **602***d*. The icon **612***b* may be disposed between icons conventionally displayed within the second task manager panel **604***b*, that is, a position where the touch drag **602***d* is released.

[0256] Referring to FIG. **13**H, as the icon **612***b* enters an area of the second task manager panel **604***b* according to the touch drag **602***d*, the second task manager panel **604***b* inserts the icon **612***b* between the previously displayed icons and displays them together. The icons displayed within the first and second task manager panels **604***a* and **604***b* may rearranged with the newly entered icon **612***b*. At this time, the second touch screen **14** replaces the preview window **612***a* of the second application with a preview window **618***a* of the running application App#**10** and displays the replaced preview window **618***a*.

[0257] After the preview window **612***a* is removed according to the touch drag **602***d*, the second touch screen **14** may not display any preview window or task window except for the second task manager panel **604***b*. As a selectable embodiment, the second touch screen **14** can display a first page of the home screen after the preview window **612***a* is removed. Thereafter, when the preview window **616***a* of the first touch screen **12** is removed by the touch drag headed for the task manager panel **604***a* or **604***b*, the portable device displays the first page of the home screen in the first touch screen **12** and displays a second page of the home screen in the second touch screen **14**. At this time, the first page of the home screen may be displayed together with a dock area in the first or second touch screen **12** or **14**.

[0258] Referring to FIG. **13**I, the portable device detects a predetermined command or user gesture for ending the task manager while the preview windows **616***a* and **620***a* of the applications are displayed in the first and second touch screens **12** and **14**. The command or the user gesture includes, for example, at least one of an input of a physical button included in the housing of the portable device, a detection of a touch on a predetermined area within at least one of the first and second touch screens **12** and **14**, a detection of a touch on a soft key provided through at least one of the first and second touch screens **12** and **14**, and a control of a soft menu.

[0259] FIG. **13**I illustrates an example of executing a task manager function by using one **600***b* of the physical buttons arranged in a second panel including the second touch screen **14**. The button **600***b* for executing the task manager function may be, for example, a back button which is one of the touch detection typed physical buttons arranged in the second panel. The portable device detects an input **602***f* of the back button **600***b* arranged in the second panel, for example, a tap gesture or a touch and hold on the back button **600***b*.

[0260] Referring to FIG. **13**J, in response to the input **602***f*, the portable device removes the first and second task manager panels **604***a* and **604***b* from the first and second touch screens **12** and **14** and replaces the preview windows **616***a* and **620***a* which previously displayed in the first and second touch screens **12** and **14** with activated task screens **616** and **620** of the corresponding applications and displays the replaced task screens **616** and **620**.

[0261] The portable device can support a personal broadcasting service by the user through the display device including the first touch screen and the second touch screen arranged on at least one foldable panel. The user having the portable device who corresponds to a broadcaster of the personal broadcasting service can broadcast an image recorded through a camera of the portable device by using the personal broadcasting application installed in the portable device.

[0262] FIGS. **14**A to **14**M illustrate user interfaces of the personal broadcasting application according to one or more exemplary embodiments.

[0263] Referring to FIG. **14**A, the first touch screen **12** displays a map area **630** provided by the personal broadcasting application. For example, the map area **630** may includes a geographical area of a predetermined scale including a current position of the user or a geographical area of a predetermined scale including a position selected by the user. The map area **630** includes at least one of caster indicators **634***a*, **634***b*, **634***c*, **634***d*, **634***e*, and **634***f* indicating a position of at least one broadcaster. The caster indicators **634***a* to **634***f* are simple information on broadcast contents broadcasted by the broadcasters, and may include, for example, at least one of a captured image, a caster name, and a broadcast title. As a selectable embodiment, the first touch screen **12** displays a broadcasting category including the broadcast contents of the broadcaster displayed within the map area **630**, for example, at least one of all, lift, sports, and entertainment, and may further display a category display line **632** for a change to a desired broadcast category.

[0264] The second touch screen **14** displays broadcast lists **636** including at least some broadcast items **636***a*, **636***b*, **636***b*, **636***c*, **636***d*, and **636***e* indicating broadcast contents provided by the broadcasters included in the map area **630**. Each of the broadcast items **636***a* to **636***e* includes a captured image of the broadcast contents, a broadcast title, a name of the broadcaster, broadcasting hours, and the number of views.

[0265] Referring to FIG. **14**B, the portable device detects a touch gesture **640** in a predetermined direction, for example, a flick or a touch drag from the map area **630** displayed in the first touch screen **12**. Referring to FIG. **14**C, the first touch screen **12** displays a map area **630** moved from the map area **630** according to a motion direction and a speed of the touch gesture **640**. Then, the second touch screen **14** displays the broadcast lists **636** including the broadcast items **636***e*, **636***f*, **636***g*, **636***h*, **636***i*, and **636***h* of the broadcast contents provided by the caster indicators **634***a*, **634***b*, **634***d*, **634***e*, **634***g*, and **634***h* included in the map area **630***a*.

[0266] Referring to FIG. **14**C, the second touch screen **14** detects a touch gesture **640***a* in a predetermined direction, for example, a flick in a vertical direction or a touch drag in a vertical direction from the displayed broadcast lists **636**. Then, the second touch screen **14** scrolls and displays the broadcast items of the broadcast lists **636** according to the touch gesture **640***a*.

[0267] Referring to FIG. **14**D, the portable device detects a predetermined touch gesture **640***b*, for example, a tap gesture or a touch and hold from one (for example, the broadcast item **636***g* of the broadcast items of the broadcast lists **636** displayed in the second touch screen **14**. Then, as illustrated in FIG. **14**E, the first touch screen **12** displays a broadcast image **636** reproducing broadcast contents corresponding to the

broadcast item **636***g* and the second touch screen **14** displays discussion areas **642** and **644** in which viewers who view the broadcast image **638** can participate in response to the detection of the touch gesture **640***b*. The discussion areas **642** and **644** include a message display window **642** and a message input window **644**, and the message input window **644** includes a message input area **644***a* and a message sending key **644***b*. The message input area **644***a* receives a message including a text and/or a conversation icon from the user. When a tap gesture is detected from the message sending key **644***b* in a state where a message input into the message input area **644***a* exists, the message display window **644** displays the input message together with a name of the user (actual name or a nickname registered in the personal broadcasting application).

[0268] Referring to FIG. **14**F, the portable device detects an input of one **646***a* of physical buttons arranged in the second panel including the second touch screen **14**, for example, an input **640***c* of the back button, that is, a tap gesture while the broadcasting image **638** is displayed in the first touch screen **12** and the discussion areas **642** and **644** are displayed in the second touch screen **14**. Then, as illustrated in FIG. **14**G, the portable device replaces the broadcasting image **638** and the discussion areas **642** and **644** of the first and second touch screens **12** and **14** with the previously displayed map area **630***a* and broadcast lists **636** and displays the replaced map area **630***a* and broadcast lists **636** in response to the input **640***c*.

[0269] When the user cannot find a desired broadcast through a movement of the map area **630***a* and a search for the broadcast lists **636**, the user can make a request for the desired broadcast to other users through a broadcast request function provided by the personal broadcasting application. Hereinafter, a scenario for making a request for the broadcast will be described.

[0270] FIGS. **14**G to **14**I illustrate a user interface for a requester who makes a request for a desired broadcast through the personal broadcasting application.

[0271] Referring to FIG. **14**G, the portable device displays the map area **630***a* and the broadcast lists **636** through the first and second touch screens **12** and **14** or detects an input of one **646***b* of the physical buttons arranged in the second panel including the second touch screen **14**, for example, an input **640***d* of the menu button, that is, a tap gesture while displaying the broadcasting image **638** and the discussion areas **642** and **644**. Then, in response to the input **640***d*, a menu window **648** for the personal broadcasting application is displayed in the lower part of the second touch screen **14**. The menu window **648** includes at least one of a create broadcast key **648***a*, a broadcast request key **648***b*, a broadcast item search key **648***c*, a broadcast item sorting key **648***d*, and a setting key **648***e*. When the portable device detects a predetermined touch gesture **640***e*, for example, a tap gesture from the broadcast request key **648***b*, the portable device proceeds to FIG. **14**H.

[0272] Referring to FIG. **14**H, in response to the detection of the tap gesture **640***e*, on the second touch screen **14**, the broadcast request window **650** replaces the broadcast lists **636** or is displayed on the broadcast lists **636**. The broadcast request window **650** includes at least one of a message input area **650***a* for receiving a message for the broadcast request, a category selection area **650***b* for selecting a desired broadcast category, a completion key **650***c*, and a cancel key **650***d*. After the message for the broadcast request, for example, "Please show me B-boy events in A park" is input into the message input area **650***a* and the desired broadcast category is selected from the category selection area **650***b*, the portable device detects a predetermined touch gesture **640***f*, for example, a tap gesture from the completion key **650***c*.

[0273] The personal broadcasting application transmits a broadcast request including the input information (request message and category) and selective additional information (name of the requester and current position of the requester) to users of other portable devices which are running the personal broadcasting application in response to the detection of the touch gesture **640***f*. The broadcast request may be transmitted through a cellular network or a WiFi network. As a selectable embodiment, the broadcast request is transmitted to other users located within a predetermined range from a current position of the requester or a position designated by the requester.

[0274] FIGS. **14**I to **14**M illustrate a user interface for the user who receives the broadcast request through the personal broadcasting application.

[0275] Referring to FIG. **14**I, the portable device receives a broadcast request of the requester through the personal broadcasting application and displays a request message window **654** including a request message of "Please show me B-boy events in A park" according to the broadcast request in the second touch screen **14** while the first touch screen **12** displays the map area **630***b* which can include at least one of caster indicators **652***a*, **652***b*, **652***c*, **652***d*, **652***e*, **652***f*, **652***g*, and **652***h* and the second touch screen **12** displays broadcast lists related to the caster indicators **652***a* to **652***h*. The request message window **654** further includes a view key **654***a* and a ignore key **654***b* together with the request message. As one embodiment, the request message window **654** may be displayed to overlap the broadcast lists displayed in the second touch screen **14** or the discussion areas displayed in the second touch screen **14**. As another embodiment, the request message window **654** may be displayed to overlap the map area **630***b* or the broadcast image displayed in the first touch screen **12**.

[0276] As a selectable embodiment, the personal broadcasting application receives the broadcast request, and inserts and displays a broadcast request indicator **652** indicating a position of the requester of the broadcast request on the map area **630***b* displayed in the first touch screen **12**. When a predetermined touch gesture, for example, a tap gesture or a touch and hold is detected from the broadcast request indicator **652**, the second touch screen **14** displays the request message window **654** according to the broadcast request.

[0277] The portable device detects a predetermined touch gesture **640***f*, for example, a tap gesture from the view key **654***a* of the request message window **654** and proceeds to FIG. **14**J. Referring to FIG. **14**J, the second touch screen **14** displays broadcast request lists including a broadcast request item **656** according to the broadcast request in response to the detection of the touch gesture **640***f*. The broadcast request item **656** includes a response key **656***a*. The portable device detects a predetermined touch gesture **640***g*, for example, a tap gesture from the response key **656***a* within the broadcast request item **656** and proceeds to FIG. **14**K. As another embodiment, the request message window **654** of FIG. **14**I may further include the response key, and the first and second touch screens **12** and **14** may proceed to FIG. **14**K in response to the tap gesture detected from the response key within the request message window **654**.

[0278] Referring to FIG. **14**K, the first and second touch screens **12** and **14** display first and second broadcast create windows **660** and **662**, respectively, in response to the detection of the touch gesture **640***g*. As a selectable embodiment, the first and second broadcast create windows **660** and **662** may be located in one of the first and second touch screens **12** and **14**.

[0279] The first broadcast create window **660** displayed in the first touch screen **12** includes mode selection areas **660***a*, **660***b*, and **660***c* for receiving one broadcast among a scene mode, a caster mode, and a mix mode. The second broadcast create window **662** displayed in the second touch screen **14** includes at least one of a title input window **662***a* for receiving a broadcast title, a category selection area **662***b* for selecting a broadcast category, a completion key **662***c*, and a cancel key **662***d*. Here, the view mode refers to a mode in which a scene image shot through the rear camera **26** of the portable device is broadcasted, the caster mode refers to a mode in which a caster image shot through the front camera **24** of the portable device is broadcasted, and the mix mode refers to a mode in which the caster image is combined with the scene image in a Picture In Picture (PIP) manner and then broadcasted.

[0280] After a broadcast mode, a broadcast title, and a broadcast category are input through the first and second broadcast create windows **660** and **662**, the portable device detects a predetermined touch gesture **640***h*, for example, a tap gesture from the completion key **662***c*. In response to the detection of the touch gesture **640***h*, the personal broadcasting application operates at least one of the front camera **24** and the rear camera **26** according to a selected mode, collects an image shot by the at least one operated camera **24** or **26**, and carries a broadcast image generated through a combination of the collected images and broadcast service data including the input information (broadcast mode, broadcast title, and broadcast category) and selective additional information (name and current position of the caster) on a wireless signal according to a pre-designated transmission scheme and broadcasts the wireless signal. The broadcast service data may be transmitted through, for example, a cellular network or a WiFi network.

[0281] Referring to FIG. **14**L, in response to the detection of the touch gesture **640***h*, the portable device displays a broadcast image **664** shot by the at least one camera **24** or **26** and generated by the personal broadcasting application in the first touch screen **12** and displays discussion areas **666** and **668** in which a caster of the broadcast image **664** and viewers who view the broadcast image **664** can participate in the second touch screen **14**. The discussion areas **666** and **668** include a message display window **666** and a message input window **668**, and the message input window **668** includes a message input area **668***a* and a message sending key **668***b*. The message input area **668***a* receives a message including a text and/or a conversation icon from the user. When a tap gesture is detected from the message sending key **668***b* in a state where a message input into the message input area **668***a* exists, the message display window **666** displays the input message together with a name of the user (an actual name or a nickname registered in the personal broadcasting application).

[0282] Although not illustrated, when the caster creates a broadcast, a caster indicator indicating the broadcast by the caster newly appears in the map area **630***a* of the requester and a broadcast item indicating the broadcast is included in the broadcast lists. When a tap gesture is detected from the broadcast item, the first and second touch screens of the requester display the broadcast area and discussion area of the broadcast by the caster.

[0283] FIG. **14**M illustrates a request for and a response of a broadcast through the personal broadcasting application. As illustrated in FIG. **14**M, a requester **670** can make a request for a desired broadcast to other users within a desired area by using the personal broadcasting application executed by a portable device **670***b* of the requester **670**. One of the other users is a caster **672** in response to the request, and the caster **672** creates and transmits the requested broadcast by using the personal broadcasting application executed by a portable device **672***b* of the caster **672**. A position indicator **670***a* of the requester **670** and a position indicator **672***a* of the caster **672** may be displayed in map areas displayed in the portable devices **670***b* and **672***b* of the requester **670** and the caster **672**.

[0284] When the portable device includes the display device including the first touch screen and the second touch screen arranged on at least one foldable panel and the first touch screen and the second touch screen are connected by the hinge or the flexible connector, the portable device can recognize motions of the first panel including the first touch screen and the second panel including the second touch screen as an input of a command. The motion includes, for example, folding back and folding hold. Here, the folding back includes bending of the flexible panel as well as folding of hard panels.

[0285] The folding back command refers to a user interface scheme of executing a predetermined function in the portable device by folding two panels within an effective angle range and then unfolding the two panels within an effective time. The folding hold command refers to a user interface scheme of executing a predetermined function in the portable device by folding two panels within an effective angle range and maintaining the two panels for an effective time. Hereinafter, the folding back command and the folding hold command will be described in detail with reference to the drawings.

[0286] FIG. **15** is a diagram for describing a detection of the folding back command according to an exemplary embodiment.

[0287] FIG. **15**A illustrates a state before the folding back command is input into the portable device **100**, wherein a relative angle of the second panel **4** with respect to the first panel **2** is 180 degrees or close to 180 degrees within a predetermined range. Here, although it is illustrated that the relative angle θ is 180 degrees for the convenience, the relative angle can be any angle. As illustrated in FIG. **15**B, the portable device **100** detects that the second panel **4** relatively moves such that the relative angle becomes a predetermined relative angle within an effective angle range Δa, for example, a range from 200 to 210 degrees (for example, 205 degrees). Further, as illustrated in FIG. **15**C, the portable device **100** detects that the relative angle escapes from the effect angle range because the second panel **4** moves in a direction opposite to an entering direction of the effective angle range within an effective time (for example, one second).

[0288] The, the folding back command is input into the portable device **100** and the portable device **100** executes a function according to the folding back command.

[0289] As one embodiment, as long as the relative angle between the two panels **2** and **4** escapes from the effective angle range in the direction opposite to the entering direction within the effective time, the folding back command can be

considered as being input. The second panel **4** does not need to return to an original position, that is, a state where the relative angle θ is 180 degrees (see FIG. **15**A), and the folding back command is input when the second panel **4** moves such that the relative angle θ becomes a random value smaller than 200 degrees. Further, although it has been described that the second panel **4** moves in the direction opposite to the entering direction and thus escapes from the effective angle range in FIG. **15**C, even when the relative angle between the first panel **2** and the second panel **4** becomes a random value smaller than 200 degrees by moving the first panel in a bottom direction instead of moving the second panel **4** in the state of FIG. **15**B, the folding back command can be input. That is, regardless of which panel moves, as long as the relative angle between the first panel **2** and the second panel **4** enters the effective angle range and escapes in the direction opposite to the entering direction, the folding back command is input.

[0290] Here, the effective angle range refers to a range of the relative angle between the two panels **2** and **4** preset by a manufacturer to recognize the folding back command, and the relative angle θ is not limited to an angle range of 10 degrees between 200 degrees and 210 degrees but may be set to have various ranges. Further, the effective angle range may be changed to an angle range designated by the user. That is, the portable device allows the user to directly change the effective angle range through an environment setting menu and thus to optimize the portable device in accordance with a utilization pattern of the user.

[0291] Further, the effective time refers to a time interval preset by the manufacturer to recognize the folding back command and is computed after a time point when the relative angle between the two panels **2** and **4** enters the effective angle range. Although it has been described that the effective time taken when the two panels **2** and **4** are unfolded after the two panels **2** and **4** are folded within the effective angle range is one second in the present embodiment, the effective time may be variously set to a value larger or smaller than one second. Similarly, the portable device may be implemented to set a time desired by the user as the effective time so that the portable device can be optimized in accordance with a utilization pattern of the user.

[0292] Although the folding back command has been described by using parameters such as the effective angle range and the effective time in the aforementioned embodiments, the present invention is not limited thereto and the portable device can input the folding back command without using the effective angle range in other embodiments. That is, when the relative angle between the two panels is changed by moving at least one panel of the two panels in a first direction and then the relative angle between the two panels is returned to the original angle (or an angle close to the original angle within a predetermined range) by moving at least one panel of the two panels in a second direction actually opposite to the first direction, the portable device may recognize that the folding back command is input.

[0293] The folding back command may be subdivided according to whether there is an additional input. As illustrated in FIG. **15**W, when the relative angle enters the effective angle range Δa, as the second panel **4** moves in the first direction and then a touch gesture of the user is detected from the first and/or second touch screen within an effective time or an additional input generated by pressing at least one of the physical buttons **5** and **5'** is detected and when the relative angle escapes from the effective angle range as the second panel **4** moves in the second direction opposite to the first direction, the portable device may recognize that a folding back command executing a different function from that of the aforementioned folding command is input. That is, the folding back command of folding and then unfolding the two panels **2** and **4** is divided into a folding back single command (in FIGS. **15**A, **15**B, and **15**C) having no additional input by the user within the effective time and a folding back combination command (in FIGS. **15**A, **15**B', and **15**C) having an additional input (of touching the screen or pressing the physical button) by the user within the effective time. The portable device is implemented to execute different functions with respect to the folding back single command and the folding back combination command so as to execute the subdivided folding back commands.

[0294] FIG. **16** is a diagram for describing a detection of the folding hold command according to an exemplary embodiment.

[0295] FIG. **16**A illustrates a state before the folding hold command is input into the portable device **100**, wherein a relative angle θ of the second panel **4** with respect to the first panel **2** is 180 degrees or close to 180 degrees within a predetermined range. Although it is illustrated herein that the relative angle θ is 180 degrees for convenience, the relative angle can be any angle. As illustrated in FIG. **16**B, the portable device **100** detects that the second panel **4** relatively moves such that the relative angle θ becomes a predetermined relative angle within an effective angle range Δa, for example, a range from 200 to 210 degrees (for example, 205 degrees). Further, as illustrated in FIG. **15**C, when the relative angle maintains an effective angle range for an effective time (for example, 0.5 seconds), the portable device **100** determines that the folding hold command is input and executes a function according to the folding hold command.

[0296] Here, the effective angle range and the effective time may be preset by the manufacturer or designated by the user as described above.

[0297] The folding hold command may be subdivided according to an existence or nonexistence of an additional input like the folding back command. As illustrated in FIG. **16**W, when the second panel **4** moves such that the relative angle is within the effective angle range Δa and then a touch gesture of the user on the first and/or second touch screens is detected or an additional input of pressing at least one of the physical buttons **5** and **5'** is detected while the relative angle is maintained for an effective time, the portable device can recognize the detection as an input of a folding hold command for performing a function different from the aforementioned folding hold command. That is, the folding hold command in which the relative angle after the two panels **2** and **4** are folded is maintained within the effective angle range for the effective time is divided into a folding hold single command (FIGS. **16**A, **16**B, and **16**C) in which there is no additional input by the user within the effective time and a folding hold combination command (FIGS. **16**A, **16**W, and **16**C) in which there is the additional input by the user within the effective time. The portable device is implemented to execute different functions with respect to the folding hold single command and the folding hold combination command so as to execute the subdivided folding hold commands.

[0298] The folding hold command may be implemented to execute a function of performing consecutive operations, for example, a zoom-in/out function, a quick play function, a rewind function and the like. In a case where a function by the

folding hold command (single command or combination function) is executed, when the relative angle between the first panel **2** and the second panel **4** escapes from the effective angle range as illustrated in FIG. **16**D, the function by the folding hold command is stopped. Here, the portable device can be implemented such that the executed function is stopped as long as the relative angle between the two panels escapes from the effective angle range in any direction regardless of the entering direction of the effective angle range.

[0299] When the portable device includes the display device including the first touch screen and the second touch screen arranged on one foldable panel and the first touch screen and the second touch screen are arranged on at least one foldable or bendable panel, the portable device can support a clipboard function by the folding back command input by the touch screen display device. Objects (text, image, sound and the like) cut or copied by a cut or copy command in the portable device are stored in an area called a clipboard. The clipboard stores the objects until a paste command from the clipboard is input or the objects area removed from the clipboard, and visually displays and provides the objects in response to a predetermined command.

[0300] FIGS. **17**A to **17**K illustrate user interfaces for the clipboard function according to one or more exemplary embodiments.

[0301] Referring to FIG. **17**A, a relative angle between the first panel **2** including the first touch screen **12** and the second panel **4** including the second touch screen **14** is actually 180 degrees (hereinafter, referred to as a first relative angle), the first touch screen **12** displays a first application **702**, and the second touch screen **14** displays a second application **704**. The first and second applications **702** and **704** may be any of the home screen, the application menu, the basic application, the application installed by the user. For example, the first and second applications **702** and **704** may be configured to display and input an object such as a text or image. In the shown example, the first application **702** is a message application such as a Short Messaging Service (SMS), an e-mail, or an Instant Messaging Service (IMS), and the second application **704** is an Internet browsing application.

[0302] Referring to FIG. **17**B, as the second panel **4** relatively moves with respect to the first panel **2**, that is, moves in a first direction, the portable device recognizes that a relative angle between the first panel **2** and the second panel **4** is changed. As one example, as the second panel **4** rotates based on the hinge between the first panel **2** and the second panel **4**, the relative angle between the first panel **2** and the second panel **4** becomes an angle (hereinafter, referred to as a second relative angle) within a predetermined range exceeding 180 degrees. As the second panel **4** relatively rotates with respect to the first panel **2**, that is, in a second direction opposite to the first direction within a predetermined effective time after the relative angle between the first and second panels **2** and **4** becomes the second relative angle, the portable device detects that the relative angle between the first panel **2** and the second panel **4** becomes again the first relative angle (or actually becomes the first relative angle) and determines that a folding back command **700** is input. As described above, the folding back command **700** is detected when the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are slightly folded outward and then unfolded back.

[0303] Referring to FIG. **17**C, the portable device displays a clipboard **710** in a predetermined area of the first and/or second touch screen **12** and/or **14**, for example, a right part of the second touch screen **14** in response to the folding back command **700**.

[0304] The clipboard **710** is an area in which objects **710***a*, **710***b*, **710***c*, **710***d*, and **710***e* cut or copied by a cut or copy command are stored and displayed, and a text, an image, and a sound which are the original of each the objects **710***a* to **710***e* are displays in a form of a simplified (or miniaturized) image or icon within the clipboard **710**. As one example, each of the objects **710***a* to **710***e* within the clipboard **710** may be displayed together with a date and time derived from the original.

[0305] Although not illustrated, when the folding back command is input again while the clipboard **710** is displayed, the second touch screen **14** can remove the clipboard **710**. Then, the original second application **704** is displayed again in the second touch screen **14**.

[0306] Referring to FIG. **17**D, the portable device detects a touch gesture **700***a* moving from one object **706** among objects displayed by the first or second application **702** or **704** in the first or second touch screen **12** or **14**, that is, texts or images to one position (hereinafter, referred to as a first position) within the clipboard **710**, for example, a touch drag and proceeds to FIG. **17**E. Referring to FIG. **17**E, in response to the detection of the touch gesture **700***a*, an object **710***f* which is a copy of the object **706** becomes included in the clipboard **710**. The clipboard **710** may be displayed in the first position in a symbol form of a simplified image or icon. As the object **710***f* newly enters the clipboard **710**, the objects displayed within the clipboard **710** may be rearranged together with the newly entered object **710***f*.

[0307] Referring to FIG. **17**F, the portable device detects a touch gesture **700***b* in a direction of the arranged objects **710***a*, **710***b*, **710***c*, **710***d*, and **710***e* within the clipboard **710**, for example, a flick up/down or a touch drag up/down and displays the objects included in the clipboard **710** while scrolling the objects in a top direction or a bottom direction in response to the touch gesture **700***b*.

[0308] Referring to FIG. **17**G, the portable device detects a touch gesture **700***c* moving from one object **710***d* among the objects **710***c*, **710***f*, **710***d*, **710***e*, **710***g*, and **710***h* displayed in the clipboard **710** to one position (hereinafter, referred to as a second position) of the first or second touch screen **12** or **14**, for example, a touch drag. In the shown example, the object **170***d* is an Internet address, that is, "http://mobile.nytimes.com" which is a text of the Uniform Resource Locator (URL) and is dragged to an address input window of the Internet browsing application **704** displayed in the second touch screen **14**. As illustrated in FIG. **17**H, the Internet browsing application **704** receives a text of the object **710***d* as an Internet address according to the touch gesture **700***c* and displays a webpage **704***a* corresponding to the Internet address.

[0309] Referring to FIG. **17**H, the portable device detects a touch gesture **700***d* heading for an outside of the clipboard **710** from a boundary between the application **704***a* and the clipboard **710** displayed in the second touch screen **14**, for example, a flick or a touch drag. As illustrated in FIG. **17**I, the clipboard **710** is expanded within the second touch screen **14** according to the touch gesture **700***d*. For example, the touch gesture **700***d* is a touch drag which starts at the boundary of the clipboard **710** and ends at one position (hereinafter, referred to as a third position) of the second touch screen **14** located in the outside of the clipboard **710**. Then, the expanded clipboard **712** has a horizontal length allowing the

boundary thereof to meet the third position. As another example, the touch gesture **700***d* includes a flick starting at the boundary of the clipboard **710** and moving in a direction of the first touch screen **12** and the expanded clipboard **712** has a horizontal length predetermined within a range of the second touch screen **14**. As the clipboard **712** expanded by the touch gesture **700***d* spreads, the application **704***a* displayed in the second touch screen **14** may be partially or mostly hidden by the expanded clipboard **712**.

[0310] The expanded clipboard **712** can display more objects **712***b* in comparison with the original sized clipboard **710**. As a selectable embodiment, the expanded clipboard **712** may include a menu window **712***a* in which categories of the displayed objects, for example, all, text, image, and sound can be selected. The initially expanded clipboard **712** displays the objects **712***b* of all categories. When a tap gesture is detected from one category key within the menu window **712***a*, only objects of the corresponding category are filtered and displayed.

[0311] Although not illustrated, when a touch gesture headed for an inside of the expanded clipboard **712** from the boundary between the application **704***a* and the expanded clipboard **712** displayed in the second touch screen **14**, for example, a flick or a touch drag is detected, the second touch screen **14** reduces the expanded clipboard **712** to the original sized clipboard **710** and displays the reduced clipboard **710**.

[0312] Also although not illustrated, when the folding back command is input while the expanded clipboard is **712** is displayed, the second touch screen **14** removes the expanded clipboard **712** without displaying the clipboard **712** anymore. Then, the original second application **704***a* is displayed again in the second touch screen **14**.

[0313] Referring to FIG. **17**J, the portable device detects a touch gesture **700***e* moving from one object **712***c* among the objects **712***a* displayed in the expanded clipboard **712** to one position (hereinafter, referred to as a fourth position) of the first or second touch screen **12** or **14**, for example, a touch drag. In the shown example, the object **712***c* is a picture image and is dragged to the message application **702** displayed in the first touch screen **12** according to the touch gesture **700***e*. As illustrated in FIG. **17**K, the message application **702** receives a picture image **714***b* of the object **712***c* in response to a release of the touch gesture **700***e* and displays **702***a* a message sending input window **714** for sending the picture image **714***b* and a sending key **714***a* for executing the sending of the picture image **714***b* in the first touch screen **12**. When a tap gesture **700***f* is detected from the sending key **714***a*, the message application **702** sends a message including the picture image to a recipient.

[0314] As a selectable embodiment, when a touch gesture headed for the inside of the clipboard **710** from the boundary of the clipboard **710**, for example, a flick or a touch drag reaching the opposite boundary of the clipboard **710** is detected while the clipboard **710** is displayed in the second touch screen **14**, the second touch screen **14** removes the clipboard **710**. In other words, the clipboard **710** which does not expand may be removed from the second touch screen **14** by the touch gesture or folding back command.

[0315] When the portable device includes the display device including the first touch screen and the second touch screen arranged on one foldable panel and the first touch screen and the second touch screen are arranged on at least one foldable or bendable panel, an electronic book function may be supported by the folding back command input by the touch screen display device.

[0316] FIGS. **18**A to **18**P illustrate user interfaces for an electronic book function according to one or more exemplary embodiments.

[0317] Referring to FIG. **18**A, a relative angle between the first panel **2** including the first touch screen **12** and the second panel **4** including the second touch screen **14** is actually 180 degrees (hereinafter, referred to as a first relative angle), the first touch screen **12** displays edge lines **802** of a first page **802***a* and previous pages provided by an electronic book application, and the second touch screen **14** displays edge lines **804** of a second page **804***a* and next pages provided by the electronic book application. The first and second page **802***a* and **804***a* include a text and/or an illustration of the same electronic book contents.

[0318] As one embodiment, the edge lines **802** and **804** may have different areas and intervals depending on amounts of the previous pages and the next pages. For example, when currently displayed pages correspond to 20 to 40% of the electronic book contents, the edge lines **802** of the previous pages are displayed as 1 cm and the edge lines **804** of the next pages are displayed as 2 cm. When the currently displayed pages correspond to 40 to 60% of the electronic book contents, the edge lines **802** of the previous pages are displayed as 1.5 cm and the edge lines **804** of the next pages are displayed as 1.5 cm. When the currently displayed pages correspond to 60 to 80% of the electronic book contents, the edge lines **802** of the previous pages are displayed as 2 cm and the edge lines **804** of the next pages are displayed as 1 cm. When the currently displayed pages correspond to 80 to 100% of the electronic book contents, the edge lines **802** of the previous pages are displayed as 2.5 cm and the edge lines **804** of the next pages are displayed as 0.5 cm.

[0319] As another embodiment, the edge lines **802** and **804** corresponding to the previous and next pages are hidden in a state where the first and second panels **2** and **4** are unfolded, and the corresponding edge lines **802** and **804** are displayed when one of the first and second panels **2** and **4** is slightly folded inward and then the folding state is maintained for a predetermined effective time. As one example, when the second panel **4** is slightly folded inward, for example, the second panel **4** is folded such that the relative angle becomes an angle equal to or larger than 180 degrees and smaller than 210 degrees, the second touch screen **14** displays the edge lines **804** in a right side of the displayed second page **804***a*. When the second panel **4** is further folded, for example, when the second panel **4** is folded such that the relative angle becomes an angle equal to or larger than 210 degrees and smaller than 230 degrees, the edge lines **804** may be expansively displayed to have a wider area or interval in accordance with the relative angle. Similarly, when the first panel **2** is slightly folded inward, for example, the first panel **2** is folded such that the relative angle becomes an angle equal to or larger than 180 degrees and smaller than 210 degrees, the first touch screen **12** displays the edge lines **802** in a left side of the displayed first page **802***a*. When the first panel **2** is further folded, for example, when the first panel **2** is folded such that the relative angle becomes an angle equal to or larger than 210 degrees and smaller than 230 degrees, the edge lines **802** may be expansively displayed to have a wider area or interval in accordance with the relative angle. As a selectable embodiment, when the first and second panels **2** and **4** are unfolded

again, the edge lines **802** and **804** may be removed from the first and second touch screens **12** and **14**.

[0320] When the portable device detects a pre-designated touch gesture **800***a* heading for a direction of the first touch screen **12** from the second touch screen **14**, for example, a flick or a touch drag is detected, the portable device proceeds to FIG. **18**B.

[0321] As illustrated in FIG. **18**B, the first and second touch screens **12** and **14** replace the first and second pages **802***a* and **804** with succeeding third and fourth pages **802***b* and **804***b* and display the third and fourth pages **802***b* and **804***b* in response to the detection of the touch gesture **800***a*. At this time, the third and fourth pages **802***b* and **804***b* may be displayed with a three dimensional graphic effect of turning the second page **804***a*. After the second page **804***a* is turned, the edge lines **802** and **804** of the previous and next pages of the third and fourth pages **802***b* and **804***b* are still displayed.

[0322] Referring to FIG. **18**B, as the second panel **4** relatively moves with respect to the first panel **2**, that is, in a first direction, the portable device detects that the relative angle between the first panel **2** and the second panel **4** is changed. As one example, as the second panel **4** rotates based on the hinge between the first panel **2** and the second panel **4**, the relative angle between the first angle **2** and the second angle **4** becomes an angle (hereinafter, referred to as a second relative angle) within a predetermined range (for example, 200 to 210 degrees) exceeding 180 degrees. As the second panel **4** relatively moves with respect to the first panel **2**, that is, in a second direction opposite to the first direction within a predetermined effective time after the relative angle between the first and second panels **2** and **4** becomes the second relative angle, the portable device detects that the relative angle between the first panel **2** and the second panel **4** becomes the first relative angle (or actual first relative angle) again and determines that a folding back command **800***b* is input.

[0323] Referring to FIG. **18**C, the portable device displays tags **806** attached to at least some edge lines of the edge lines **804** of the next pages of the fourth page **804***b* displayed in the second touch screen **14** in response to the folding back command **800***b*. Each of the tags **806** is located in an edge line of the page designated by the user or a provider of the electronic book contents, and the tags **806** may have different colors which are visually distinguished from the pages **802***b* and **804***b* and the edge lines **804**. As a selectable embodiment, each of the tags **806** may be attached to an edge line of the page including a memo or highlighted item designated by the user or the provider of electronic book contents. Although not illustrated, when a touch gesture for example, a tap gesture is detected from a first tag which is one of the tags **806**, the portable device executes a graphic effect of turning the pages and displays two pages including the page to which the first tag is attached in the first and second screens **12** and **14**. As a selectable embodiment, the tags **806** may be removed when the folding back command is input again.

[0324] Referring to FIG. **18**D, the portable device detects a predetermined touch gesture **800***c*, for example, a touch or a touch and hold from a first edge line **808** which is one of the edge lines **804** of the next pages of the fourth page **804***b* displayed in the second touch screen **14**. The second touch screen **14** changes a color of the first edge line **808** into a color (a first color, for example, red) visually distinguished from other edge lines in response to the detection of the touch **800***c*. At this time, a page number of the first edge line **808**, for example, a page indicator **808***a* showing "P**105**" may be displayed on the first edge line **808**.

[0325] Referring to FIG. **18**E, as the touch **800***c* moves in a direction of intersecting the edge lines **804** while being held, the touch **800***c* is released **800***d* at a second edge line **808***b* within the edge line area **804**. Accordingly, when the touch drag **800***c* or **800***d* reaching the second edge line **808***b* from the first edge line **808** is detected, the second touch screen **14** changes a color of the second edge line **808***b* into the first color. At this time, page number of the second edge line **808***b*, for example, a page indicator **808***c* showing "P**51**" may be displayed on the second edge line **808***b*.

[0326] Referring to FIG. **18**F, the portable device detects that the touch **800***c* is released **800***d*, and replaces the third and fourth pages **802***b* and **804***b* displayed in the first and second touch screens **12** and **14** with fifth and sixth pages **802***c* and **804***c* including the page of the second edge line **808***b* and displays the replaced fifth and sixth pages **802***c* and **804***c*. At this time, the fifth and sixth pages **802***c* and **804***c* may be displayed with a graphic effect of successively turning pages between the third and fourth pages **802***b* and **804***b* and the fifth and sixth pages **802***c* and **804***c*. Further, the edge lines **802** and **804** of previous and next pages of the fifth and sixth pages **802***c* and **804***c* are still displayed.

[0327] Referring to FIG. **18**F, the second touch screen **14** can highlight a first item (text or illustration) **810** among items included in the sixth page **804***c* and display the highlighted first item **810**. The highlighted first item **810** may be designated by the user or the provider of the electronic book contents and displayed together with an indicator **810***a* showing a designated date/time.

[0328] Referring to FIG. **18**G, the portable device detects a touch drag **800***e* moving along a second item **810***b* among items included in the sixth page **804***c* in the second touch screen **14**, and highlights the second item **810***b* with a designated color according to the touch drag **800***e* and displays the highlighted second item **810***b*.

[0329] Referring to FIG. **18**H, the portable device detects that the touch drag **800***e* is released and displays a menu bar **812** which is a soft menu for controlling a highlight function in a position where the touch drag **800***e* is released, that is, an end of the second item **810***b*. For example, the menu bar **812** includes a highlight key **812***a* for selecting whether the highlight is performed or controlling the highlight, a color key **812***b* for changing a highlight color (or character), and a memo key **812***c* for attaching a memo. When a predetermined touch gesture **800***f*, for example, tap gesture is detected from the memo key **812***c*, the portable device proceeds to FIG. **18**I.

[0330] Referring to FIG. **18**I, the portable device displays a memo input window **814** in the second touch screen **14** in response to the detection of the touch gesture **800***f* on the memo key **812***c*. For example, a memo input window **814** includes at least contents of the second item **810***b* selected by the touch drag **800***e* and allows an editing function by the user. When a tap gesture is detected from a done key included in the memo window **814**, the second touch screen **14** displays a memo window **814***a* including contents of the second item **810***b* input and edited by the memo input window **814** in a predetermined position as illustrated in FIG. **18**J. The memo window **814***a* has a size smaller than the memo input window **814** and may include some of the contents input through the memo input window **814** or reduced contents and have a shape simplified from the memo input window **814**. Further, a tag having the same color as the highlight color of the

corresponding second item **810***b* may be attached to the memo window **814***a*. As a selectable embodiment, when the memo window **814***a* is displayed, a tag having the same color as that of the memo window **814***a* may be attached to an edge line of the page including the memo window **814***a*.

[0331] Referring to FIG. **18**K, the second touch screen **14** displays one or more memo windows **814***a* and **814***b* including items selected from the sixth page **804***c* by the user. Referring to FIG. **18**K, in response to a touch drag **800***g* which starts at the memo window **814***b* and is released at an external position (first position) of the memo window **814***b* within the first and second touch screens **12** and **14**, the portable device can move the memo window **814***b* to the first position and then display the moved memo window in the first position. In the shown example, the first position is located within the first touch screen **12**. Similarly, referring to FIG. **18**L, in response to a touch drag **800***h* headed for an external position (second position) of the memo window **814***a* from the memo window **814***a*, the portable device can move the memo window **814***a* to the second position and display the moved memo window **814***a* in the second position.

[0332] Referring to FIG. **18**M, as the second panel **4** relatively moves with respect to the first panel **2**, that is, in a first direction while the pages **802***c* and **804***c* are displayed in the first and second touch screens **12** and **14**, the portable device detects that the relative angle between the first panel **2** and the second panel **4** is changed. For example, as the second panel **4** rotates based on the hinge between the first panel **2** and the second panel **4**, the relative angle between the first panel **2** and the second panel **4** becomes an angle (hereinafter, referred to as a second relative angle) within a predetermined range (for example, 200 to 210 degrees) exceeding 180 degrees. When the relative angle between the first and second panels **2** and **4** becomes the second relative angle and the second relative angle remains for a predetermined effective time or more, the portable device determines that a folding hold command **800***i* is input.

[0333] The portable device displays a graphic effect **816** of successively turning pages from current pages **802***c* and **804***c* displayed in the first and second touch screens **12** and **14** to next pages, that is, a moving image in response to the folding hold command **800***i*. Here, when each page is turned in a direction from the second touch screen **14** to the first touch screen **12**, the page may be displayed over both the first and second touch screens **12** and **14**.

[0334] Referring to FIG. **18**N, as the second panel **4** relatively moves with respect to the first panel **2**, that is in a second direction opposite to the first direction, the portable device detects that the relative angle between the first panel **2** and the second panel **4** becomes again the first relative angle (or actual first relative angle) and determines that the folding hold command **800***i* is released and a folding back command **800***j* is input while the graphic effect **816** of successively turning the pages according to the folding hold command **800***i* is displayed.

[0335] Referring to FIG. **18**O, the portable device ends the graphic effect **816** of turning the pages in response to the detection of the folding back command **800***j* and displays new pages **802***d* and **804***d* which have not been turned in the first and second touch screens **12** and **14**. The successive page turning function can be executed at different speeds depending on the relative angle between the first and second panels **2** and **4** while the folding hold command **800***i* is maintained. For example, a range of the relative angle is subdivided into four angle ranges, a 1× backward page turning function is executed when the second relative angle is within a first angle range, a 2× backward page turning function is executed when the second relative angle is within a second angle range, a 1× forward page turning function is executed when the second relative angle is within a third angle range, and a 2× forward page turning function is executed when the second relative angle is within a fourth angle range.

[0336] Referring to FIG. **18**O, when the portable device detects a pre-designated touch gesture **800***k*, for example, a touch and hold from a random position of the current pages **802***d* and **804***d* displayed in the first and second touch screens **12** and **14**, the portable device proceeds to FIG. **18**D.

[0337] As illustrated in FIG. **18**P, the portable device displays an electronic book setting menu **818** in a predetermined area within the first and second touch screens **12** and **14** in response to the detection of the touch gesture **800***k*. As one example, the electronic book setting menu **818** may be displayed in a translucent state in upper parts of the current pages **802***d* and **804***d* and includes soft keys **818***a* for a font change, an index, and a text input and a chapter list **818***b*.

[0338] As one example, the chapter list **818***b* includes a current chapter indicator **820** indicating chapter numbers and a current chapter position included in the electronic book contents. When a tap gesture **800***l* is detected from a first chapter number which is one of the chapter numbers of the chapter list **818***b*, the portable device can display first pages (not shown) of a first chapter corresponding to the first chapter number in the first and second touch screens **12** and **14** in response to the detection of the tap gesture **800***l*.

[0339] As another embodiment, the chapter list **818***b* does not require an input of a touch gesture and may be displayed in upper or lower parts of the first and second touch screens **12** and **14** all the time.

[0340] The portable device can support a video conference application in a separate work environment through the display device including the first touch screen and the second touch screen arranged on one foldable panel. Participants of the video conference can participate in the video conference through a connection of a group call.

[0341] FIGS. **19**A to **19**G illustrate user interfaces of a video conference application according to one or more exemplary embodiments.

[0342] Referring to FIG. **19**A, the first touch screen **12** displays at least one of a participant list area **802***a*, a basic information area **902***b*, a conference restart key **902***c*, and a new conference create key **902***d* which are related to a first video conference among a plurality of video conferences which can be provided by a video conference application. The participant list area **802***a* includes names (or nicknames) of the participants including the user of the portable device and picture images (thumbnails). The basic information area **902***b* includes at least one of a conference date, for example, "Tuesday 16 Nov. 2010", a conference start and end (expected) time, for example, "15:00" and "16:37", and a name of a document file used for the conference, for example, "Dual Display.ppt". When the first video conference is temporarily stopped, the conference restart key **902***c* is a soft key used to make a request for the restart of the first video conference to the participants or to inform the participants of the restart of the first video conference. The new conference create key **902***d* is a soft key used to create a new video conference.

[0343] The second touch screen **14** displays video conference lists **904** including at least some of conference items

indicating video conferences which can be provided by the video conference application. Each of the conference items included in the video conference lists **904** include at least one of a title of the video conference, a start time, a host, a number of participants, and a progress time. In addition, the second touch screen **14** may further display at least one of a keypad key **904***a* for loading a virtual keypad, a favorites key **904***b* for selecting only frequently used video conferences, and a contact key **904***c* for loading contact numbers. Although not illustrated, when a tap gesture is detected from a conference item of a second video conference of conference items displayed in the second touch screen **14**, the portable device replaces information **902***a* ad **902***b* related to the first video conference displayed in the first touch screen **12** with information related to the second video conference and displays the replaced information.

[0344] When the portable device detects a predetermined touch gesture **900***a*, for example, a tap gesture from the conference restart key **902***c* of the first touch screen **12**, the portable device proceeds to FIG. **19**B.

[0345] Referring to FIG. **19**B, the portable device displays a participant list area **906** expanded from the participant list area **902***a* of the first video conference in the first touch screen **12** and displays a shared board area **14** for the first video conference in the second touch screen **14** in response to the detection of the touch gesture **900***a*. The participant list area **906** includes names (or nicknames) of the connected participants including the user him/herself, "ME" and picture images, and each of the picture images may have a larger size than the picture image within the participant list area **902***a*. As a selectable embodiment, the participant list area **906** can provide more information on each of the participants in comparison with the participant list area **902***a*.

[0346] In addition, the first touch screen **12** further displays at least one of a participant addition key **906***a* for adding a new participant, a microphone off key **906***b* for turning off a microphone, and a call end key **906***c* for ending or leaving from the video conference. The shared board area **908** displays contents of a document file, for example, "Atomic Structure.ppt" registered to be used for the first video conference according to a basic setting. The second touch screen **14** scrolls up/down the contents of the displayed document file in response to the detection of a touch gesture, for example, a flick up/down or a touch drag up/down on the shared board area **908**. In addition, the second touch screen **14** may further display a white board key **908***a* for selecting to use the shared board area **908** as the white board area.

[0347] When the portable device detects a predetermined touch gesture **900***b*, for example, a tap gesture from the participant addition key **906***a* of the first touch screen **12**, the portable device proceeds to FIG. **19**C.

[0348] Referring to FIG. **19**C, the portable device displays a contact window **910** including person lists in the contact information who can participate in the first video conference in the first touch screen **12** in response to the detection of the touch gesture **900***b*. The contact information window **910** includes person lists **910***a* including names of respective people and check boxes, an addition key **910***b*, and a cancel key **910***c*. When a check box of at least one person, for example, "Jae" within the person lists **910***a* is checked and a touch gesture **900***c*, for example, a tap gesture is detected from the addition key **910**, the portable device proceeds to FIG. **19**D. Referring to FIG. **19**D, the portable device displays a participant list area **906***d* including a name and a picture image of "Jae" which is the person designated from the contact information window **910** as a new participant in the first touch screen **12** in response to the detection of the touch gesture **900***c*.

[0349] When a predetermined touch gesture **900***d*, for example, a tap gesture is detected from the white board key **908***a* displayed in the second touch screen **14**, the portable device proceeds to FIG. **19**E.

[0350] Referring to FIG. **19**E, the portable device replaces the document file displayed in the shared board area **908** of the second touch screen **14** with a white board area **912** in response to the detection of the touch gesture **900***d* and displays the replaced white board area **912**. The white board area **912** allows an input of a freehand drawing object by a touch of the user and displays freehand drawing objects **912***a*, **912***b*, and **912***c* input by respective participants of the first video conference including the user. The freehand drawing objects **912***a*, **912***b*, and **912***c* refer to graphic data in a form of a text or image input by the respective participants through the white board areas provided to the respective participants.

[0351] It is possible that each the freehand drawing objects **912***a*, **912***b*, and **912***c* has different colors for each participant. During a display of the white board area **912**, a color indicator **912***f* indicating a color of the corresponding freehand drawing object **912***a*, **912***b*, or **912***c* is displayed in each picture image included in the participant list area **906***d* of the first touch screen **12**. The color indicator of the participant who is inputting the freehand drawing object into the white board area **912** is displayed while flickering. In addition, the white board area **912** may include keys **912***d* and **912***e* for inputting and erasing the freehand drawing of the user.

[0352] During the display of the white board area **912**, the second touch screen **14** further displays a document file selection key **908***b* for displaying a document file in the shared board area. When a tap gesture is detected from the document file selection key **908***b*, the second touch screen **14** replaces the white board area **912** with the document file and displays the replaced document file.

[0353] When the first touch screen **12** and the second touch screen **14** are arranged on at least one foldable or bendable panel, the portable device can support the video conference application in an out-folded screen mode.

[0354] Referring to FIG. **19**F, as the first panel **2** including the first touch screen **12** relatively moves with respect to the second panel **4** while the video conference application is displayed in the first and second touch screens **12** and **14**, the portable device detects that the relative angle between the first panel **12** and the second panel **14** becomes an angle smaller than 180 degrees and determines that a fold-out command **900***e* is input. As one example, when the relative angle between the first panel **2** and the second panel **4** becomes an angle within a predetermined range (for example, 30 to 60 degrees) which is smaller than 180 degrees as the first panel **2** rotates based on the hinge between the first panel **2** and the second panel **4**, the portable device determines that the fold-out command **900***e* is input.

[0355] The portable device replaces information of the second touch screen **14** with a participant list area **906***e* and a shared board area **912***f* in response to the detection of the fold-out command **900***e* and displays the replaced participant list area **906***e* and shared board area **912***f*. At this time, it is possible that the first touch screen **12** which has moved to the back is turned off. The participant list area **906***e* and the shared board area **912***f* have smaller sizes of those of the

participant list area **906***d* and the shared board area **912** before the fold-out command **900***e*. In addition, the second touch screen **14** further displays at least one of a participant list selection key **914***a* for expansively showing participant lists in the second touch screen **14**, a shared board selection key **914***b* for selecting whether to show the shared board area **912***f* in the second touch screen **14**, a microphone off key **914***c*, and a call end key **914***d*. The first touch screen **12** may be turned off in response to the fold-out command **900***e* or display information such as a clock according to an option which can be designated by the user.

[0356] When a tap gesture **900***f* is detected from the participant list selection key **914***a*, the portable device proceeds to FIG. **19**G.

[0357] Referring to FIG. **19**G, the portable device expands the participant list area **906***f* in response to the detection of the touch gesture **900***f* and displays the expanded participant list area in the second touch screen **14**. The participant list area **906***f* includes picture images having a larger size than that of the participant list area **906***e* of FIG. **19**F. In addition, the second touch screen **14** further displays at least one of the participant list selection key **914***a*, the shared board selection key **914***b*, the microphone off key **914***c*, and the call end key **914***d*.

[0358] Although not illustrated, when a tap gesture is detected from the shared board selection key **914***b*, the portable device displays the shared board area including the document file of the white board area in the second touch screen **14** and displays simple participant lists together with the shared board area, for example, lists of only names without picture images or lists of smaller picture images and names.

[0359] The portable device can support an application requiring an interaction between two or more users, for example, a collaborative game application through the display device including the first touch screen and the second touch screen arranged on one foldable panel. The collaborative game application may be useful for an out-folded screen mode in which two touch screens are almost folded outwardly to face almost opposite directions. That is, the folded-out portable device is stood in a triangle shape, a front touch screen is used as a main touch screen for providing a user interface for a holder of the portable device, and a back touch screen is used as a sub touch screen shown to another user. That is, the back touch screen provides information to a holder of another portable device who executes the linked collaborative game application.

[0360] FIGS. **20**A to **20**H illustrate user interfaces of the collaborative game application according to one or more exemplary embodiments. Here, a touch screen layout in a case where the portable device rotates by 90 degrees in a left direction is illustrated, wherein the first touch screen **12** located in a lower part before the fold-out becomes the main touch screen which provides a user interface for a user having the portable device, that is, the front touch screen, and the second touch screen **14** located in an upper part becomes the sub touch screen shown to other users, that is, the back touch screen. The above case also can be applied when the portable device rotates by 90 degrees in a right direction.

[0361] Referring to FIG. **20**A, the first touch screen **12** displays a game ready screen **1002** provided by the collaborative game application, and the second touch screen **14** displays a guide phrase **1000** of making a request for turning off or folding-out the second touch screen **14**. As one embodiment, when the collaborative game application supporting the out-folded screen mode is executed in the portable device, the collaborative game application identifies whether the panels **2** and **4** including the first and second touch screens **12** and **14** are folded-out. When it is detected that the panels **2** and **4** are not folded-out, the collaborative game application displays the guide phrase **1000** making a request for folding-out the second touch screen **14**, for example, "Please fold the phone".

[0362] The game ready screen **1002** displayed in the first touch screen **12** includes participant identification areas **1002***a*, **1002***b*, **1002***c*, and **1002***d* for participants of the game including the user having the portable device and a ready key **1002***e* for selecting a game ready completion. Each of the participant identification areas **1002***a*, **1002***b*, **1002***c*, and **1002***d* includes a picture image, a name (or nickname), or carried money of each participant. In one embodiment, the collaborative game application is a poker game application, and the game ready screen **1002** has a form embodied as a physical table on which the poker game is performed. Further, the first touch screen **12** may further display a chatting area **1004** including a chatting input window **1004***a* for the participants and potential participants. When a tap gesture is detected from the chatting input window **1004***a*, the second touch screen **14** displays a virtual keypad in a predetermined area, for example, some of lower parts of the chatting area **1004** or second touch screen **14**.

[0363] When a predetermined touch gesture **1000***a*, for example, a tap gesture is detected from the ready key **1002***e* of the first touch screen **12**, the portable device proceeds to FIG. **20**B.

[0364] Referring to FIG. **20**B, the portable device determines that the user becomes in a "Ready" state in response to the detection of the tap gesture **1000***a*, displays a state indicator of "Ready" in the participant identification area **1002***a*, and informs a portable device of another participant who is participating in the game that the user becomes in the "Ready" state by using a predetermined communication means. That is, the portable devices of all participants are mutually interworked by executing the poker game application, inform other participants of information generated from the poker game application of each participant, receive the information generated from the poker game application of another participant, and display the received information. When all the participants become in the "Ready" state, the portable device proceeds to FIG. **20**C to start one round of the poker game.

[0365] As illustrated in FIG. **20**C, when one round of the poker game starts, the portable device displays a game interface screen **1006** for the user of the portable device in the first touch screen **12**. As one example, the game interface screen **1006** of the first touch screen **12** includes a chatting area **1006***a* receiving an input of a chatting message of the user and displaying chatting messages of other participants, a carried card area **1006***b* showing playing cards given to the user, a betting money area **1006***c* displaying money bet in the poker game of the current round, a carried money area **1006***d* displaying carried money of the user, and a card slot area **1006***e* displaying a card pool including closed cards which have not been provided to the participants.

[0366] Further, when one round of the poker game starts, the portable device displays game information **1008** for other participants in the second touch screen **14**. As one example, the game information **1008** for other participants displayed in the second touch screen **14** includes an identification area

1008*a* of the user, a betting display area **1008***b* displaying a betting item selected by the user, an open card area **1008***c* displaying cards selected to be shown to other users by the user, a carried money area **1008***d* displaying carried money of the user, and a card slot area **1008***e* displaying a card pool including closed cards which have not been provided to the participants.

[0367] As a selectable embodiment, when the portable device detects that the panels including the first and second touch screens **12** and **14** are folded outwardly (folded-out) while displaying the guide phrase **1002***a* making a request for folding-out the second touch screen **14** by the poker game application, the portable device displays the game information **1008** for other participants in the second touch screen **14**. That is, the guide phrase **1002***a* may be displayed in the second touch screen **14** until the fold-out is generated, and the game information **1008** may be displayed after the folding-out.

[0368] As another selectable embodiment, the poker game application activates the ready key **1002***e* only in a state where the panels of the portable device are folded-out. That is, the poker game application can start the poker game only in a fold-out state, and continuously displays the guide phrase **1002***a* in the second touch screen **14** until the second touch screen **14** is folded-out.

[0369] FIG. **20**D is a perspective view of the portable device having folded-out panels. As illustrated in FIG. **20**D, the portable device is stood in a triangle shape which is supported by two folded-out panels, wherein the game interface screen **1006** for the user having the portable device is displayed in the first touch screen **12** located in the front side and the game information **1008** for other participants is displayed in the second touch screen **14** located in the back side. Here, other participants refer to other users who execute the poker game application and have respective portable devices interworking with the portable device of the user. FIG. **20**E illustrates portable devices of participants which interwork with each other through the poker game application. As illustrated in FIG. **20**E, the portable device of the user displays the game interface screen **1006** for the user through the first touch screen **12**. The portable devices for other participants also display game information for the corresponding participants through the front touch screen shown to the respective participants and displays game information **1014** for other participants through the opposite touch screen.

[0370] Referring to FIG. **20**F, after one round of the poker game starts, the portable device sequentially withdraws the predetermined number of cards from the card slot area **1006***e* of the first touch screen **12** in a first turn of the user and arranges to expose front surfaces of the cards in a carried card area **1010***a*. Simultaneously, the portable device sequentially withdraws the same number of cards from the card slot area **1008***e* of the second touch screen **14** and arranges to expose back surfaces of the cards in an open card area **1012***a*. In addition, the first touch screen **12** can display stacked coins corresponding to currently bet money in an area **1010***b*. When a predetermined touch gesture **1000***c*, for example, a tap gesture or a flick up is detected from at least one of the cards arranged in the carried card area **1010***a*, the portable device proceeds to FIG. **20**G.

[0371] Referring to FIG. **20**G, the portable device slightly moves the card selected by the touch gesture **1000***c* among the cards of which the front surfaces are exposed in the carried card area **1010***a* of the first touch screen **12** and simultaneously turns face-up and displays, that is, opens a card in a position corresponding to the selected card among the cards located in the open card area **1012***a* of the second touch screen **14**. When open cards are selected by all the participants, the portable device displays a betting command window **1010***c* through which betting items can be input into the first touch screen **12** when an order determined according to a rule of the poker is reached. The betting command window **1010***c* includes at least one of the betting items for the poker game, that is, "Check", "Pin", "Call", "Raise", "Half", and "Fold". At this time, the betting item which cannot be selected in the current order can be displayed in a deactivated state, that is, in a shadow.

[0372] When a predetermined touch gesture **1000***d*, for example, a tap gesture is detected from one of the betting items of the betting command window **1010***c* displayed in the first touch screen **12**, for example, "Pin", the portable device updates the game interface screen **1006** according to the betting item selected by the tap gesture **1000***d*, displays the selected betting item of "Pin" in the betting display area **1008***b* of the second touch screen **14**, and informs the portable devices of other participants of the selected betting item at the same time. When the betting of all the participants is completed, the portable device withdraws a new card from the card slot area **1006***e* of the first touch screen **12**, displays to expose the front surface of the card in the card slot area **1006***e*, withdraws a new card from the card slot area **1008***e* of the second touch screen **12**, and displays to expose the front surface of the card in the open card area **1012***a* at the same time, and then displays a betting command window **1010***c* in the first touch screen **12** when an order determined according to a rule of the poker game is reached similarly to FIG. **20**F.

[0373] FIG. **20**H illustrates screens when one round of the poker game ends. When one round of the poker game ends, the first touch screen **12** displays open states **1016***a* of all cards of the user and a game result **1016***b*, for example, "Flush" and "Winner" and the second touch screen **14** displays open states **1018***a* of at least some of the cards given to the user and a game result **1018***b* at the same time.

[0374] The portable device can provide a more convenient user interface for a schedule management application through the display device including the first touch screen and the second touch screen arranged on one foldable panel. An example of the application for the schedule management may include a calendar application.

[0375] FIGS. **21**A to **21**O include user interfaces of the schedule management application according to one or more exemplary embodiments.

[0376] Referring to FIG. **21**A, the first touch screen **12** displays a view mode selection area **1102** for selecting a schedule view mode and a calendar area **1102***a* of a month mode. The schedule management application selects a schedule view mode through a month mode key, a week mode key, a day mode key, and a list mode key included in the view mode selection area **1102**. As one embodiment, the schedule management application displays the calendar area **1102***a* in a month mode, that is, dates of a current month including a today's date by default when the schedule management application starts. The calendar area **1102***a* of the month mode includes day blocks corresponding to dates included in the selected month and may include some of the day blocks of a previous month and a next month. For example, the day blocks form a row corresponding to a week and a column corresponding to a day. A day block corresponding to today's

date among the day blocks may be displayed with a predetermined color which is visually distinguished. A date indicator **1106***a* indicating a date selected by the user is disposed in one of the day blocks and may be, for example, a rectangular form in a bold line surrounding a number of the selected date. When the calendar application starts, the date indicator **1106***a* is displayed in the day block of the today's date.

[0377] The second touch screen **14** can display another application or information on the schedule management program according to a setting of a schedule management program or a selection by the user while the first touch screen **12** displays the calendar area of a month mode, a week mode, a day mode, or a list mode. FIG. **21**A illustrates an example of displaying information provided by the schedule management program in the second touch screen **14**.

[0378] Referring to FIG. **21**A, the second touch screen **14** displays event lists **1104***a* including registered event items of the selected date of the calendar area **1102***a*. Each of the event items may indicate an event registered in a selected date or an event registered in a period including the selected date. As another embodiment, the event lists **1104***a* of the second touch screen **14** may include event items registered in a month of the calendar area **1102***a*. Each of the event items includes at least one of an event title, an event date(s), an event time, and an event related image icon. Further, the first or second touch screen **12** or **14** displays a new event create key **1104** for registering a new event in a predetermined position. For example, the new event create key **1104** is disposed in a lower part of the event lists **1104***a* of the second touch screen **14**.

[0379] When a predetermined touch gesture **1100***a*, for example, a tap gesture is detected from one date of the calendar area **1102** of the first touch screen **12**, for example, "**16**", the portable device proceeds to FIG. **21**B.

[0380] Referring to FIG. **21**B, the portable device places a date indicator **1106***b* on the date selected by the touch gesture **1100***a* within the calendar area **1102***a* of the first touch screen **12** in response to the detection of the tap gesture **1100***a* and displays the event lists **1104***b* including the registered event items of the selected date in the second touch screen **14**.

[0381] When a selection of a menu button which is one of the physical buttons disposed in a lower part of the first touch screen **12**, for example, a touch gesture **1100***b* is detected while the calendar area **1102***a* is displayed in the first touch screen **12**, the portable device displays a first menu window **1104***c* in the lower part of the first touch screen **12** in response to the detection of the touch gesture **1100***b*. The first menu window **1104***c* includes at least one of a create key for creating a new event, a go to key for moving to a selected date, a today key for moving to today's date, a search key for searching for a desired event, a deletion key for deleting a registered event, and a setting key for changing a setting of the schedule management application. The first menu window **1104***c* may be loaded by a touch of the menu button while the calendar area of the month mode, the week mode, the day mode, or the list mode is displayed in the first touch screen **12**.

[0382] When the menu button which is one of the physical buttons disposed in the lower part of the second touch screen **14** is selected, for example, when a touch gesture **1100***d* is detected while the event lists **1104***b* are displayed in the second touch screen **12**, the portable device displays a second menu window **1104***d* in the lower part of the second touch screen **14** in response to the detection of the touch gesture **1100***c*. The second menu window **1104***d* includes at least one of a search key for searching for a desired event and a deletion key for deleting a registered event. The second menu window **1104***d* may be loaded by a touch of the menu button while the event lists are displayed in the second touch screen **140**

[0383] When a tap gesture **1100***d* is detected from a main mode key included in the view mode selection area **1102** of the first touch screen **12**, the portable device proceeds to FIG. **21**C.

[0384] Referring to FIG. **21**C, the portable device displays a calendar area **1102***c* of the week mode including the today's date (or a selected date) in the first touch screen and displays event lists **1104***e* including event items registered in the selected date of the calendar area **1102***c* or week of the calendar area **1102***c* in the second touch screen **14** in response to the detection of the tap gesture **1100***d*. The calendar area **1102***c* of the week mode includes a week display line indicating a selected week, for example, "3rd week January, 2009", dates of the selected week, for example, S**11**, M**12**, T**13**, W**14**, T**15**, F**16**, and S**17**, and hour blocks indicating a schedule for each hour of each date. That is, the calendar area **1102***c* of the week mode includes columns corresponding to the day and rows corresponding to the hour. A first letter of each date refers to the day. Each of the hour blocks may be displayed with a predetermined color when there is an event registered in the corresponding hour.

[0385] When a tap gesture **1100***e* is detected from the day mode key included in the view mode selection area **1102** of the first touch screen **12**, the portable device proceeds to FIG. **21**D.

[0386] Referring to FIG. **21**D, the portable device displays a calendar area **1102***d* of the day mode including the today's date (or a selected date) in the first touch screen **12** and displays event lists **1104***f* including event items registered in the date of the calendar area **1102***d* in the second touch screen **14** in response to the detection of the tap gesture **1100***e*. The calendar area **1102***d* of the day mode includes a date display line indicating the selected date, for example, "Thu, Jan. 13, 2009" and an hour line for each hour on the selected date. When there is an event registered in the corresponding hour, each of the hour lines includes an event tile of the corresponding event and may be displayed with a predetermined color.

[0387] When a predetermined touch gesture **1100***f*, for example, a tap gesture is detected from one event item of the event lists **1104***f* of the second touch screen **14**, the portable device proceeds to FIG. **21**E.

[0388] Referring to FIG. **21**E, the portable device replaces the calendar area **1102***d* of the first touch screen **12** with event lists **1104***g* including an event item selected by the tap gesture **1100***f* and displays the replaced event lists **1104***g*, and displays detailed information **1108** on the event item selected from the event lists **1104***g* in the second touch screen **14** in response to the detection of the tap gesture **1100***f*. The detailed information **1108** includes at least one of an event title and date **1108***a*, the remaining days to the event **1108***b*, a registered image **1108***c* of the event item, and participant lists **1108***d* related to the event item. The first touch screen **12** can dispose the new event create key **1104** in a lower part of the event lists **104***g* while the event lists **1104***g* are displayed in the first touch screen **12**.

[0389] Referring to FIG. **21**F, a tap gesture **1100***g* is detected from the list mode key included in the view mode selection area **1102** of the first touch screen **12**, and a calendar area **1102***e* listing all the registered event items including the event item registered in the selected date (or today's date) is displayed in the first touch screen **12** and detailed information

1108*e*, **1108***f*, **1108***g*, and **1108***h* of the event item selected from the calendar area **1102***e* are displayed in the second touch screen **14** in response to the tap gesture **1100***g*. As one embodiment, the calendar area **1102***e* of the list mode includes event lines corresponding to the event items, and each of the event lines may include an event title and event hour.

[0390] When a touch gesture **1100***h* is detected from the menu button disposed in the lower part of the first touch screen **12** while the calendar area **1102***a* of the list mode is displayed in the first touch screen **12**, the portable device displays the first menu window **1104***c* in the lower part of the first touch screen **12** in response to the detection of the touch gesture **1100***h*.

[0391] As the event item is selected from the event lists **1104***g* displayed in the first touch screen **12** or the list mode key within the view mode selection area **1102** is selected, when a touch gesture **1100***i* is detected from the menu button disposed in the lower part of the second touch screen **14** while the detailed information **1108***a* to **1108***h* of the selected event item are displayed in the second touch screen **14**, the portable device displays a third menu window **1104***g* in the lower part of the second touch screen **14** in response to the detection of the touch gesture **1100***i*. The third menu window **1104***g* includes at least one of an editing key for editing a selected event item, a deletion key for deleting a selected event item, a sending key for sending a selected event item to a desired recipient, a search key for searching for a desired event item, a participant sending key for sending a selected event item to the participants, and a export key for sending a selected event item to a plurality of recipients.

[0392] As a selectable embodiment, when the schedule management application starts, the second touch screen **14** can display another application, for example, a home screen, an application menu, or a previously executed other application. It is referred to as a schedule management application operating in a multi mode.

[0393] Although not illustrated, when the portable device is in a landscape view mode, a lower touch screen can display the calendar area of the month mode, the week mode, the day mode, or the list mode provided by the schedule management application and an upper touch screen can display an event list related to the selected date of the calendar area or detailed information on the selected event item. As a selectable embodiment, when the portable device is in the landscape view mode, the upper touch screen can display the calendar area of the month mode, the week mode, the day mode, or the list mode provided by the schedule management application and the lower touch screen can display information on another application.

[0394] FIGS. **21**G to **21**I illustrate a scenario for generating a new event in the schedule management application according to an exemplary embodiment.

[0395] Referring to FIG. **21**G, the portable device displays the view mode selection area **1102** and the calendar area **1102***a* in the first touch screen **12** and displays the event lists **1104***a* of the selected data of the calendar area **1102***a* and the new event create key **1104** in the second touch screen **14**. Although the calendar area **1102***a* of the month mode is illustrated herein, a new event can be generated in a similar way when the calendar area corresponds to a calendar area **1102***c*, **1102***d*, or **1102***e* of the week mode, the day mode, or the list mode. The portable device can detect a create command of a new event through the first or second touch screen **12** or **14** or the menu button in the lower part of the first touch screen **12**. For example, when a touch and hold **1100***j*-**1** is detected from a particular date of the calendar area **1102***a* of the first touch screen **12**, a tap gesture **1100***j*-**2** is detected from the new event create key **1104** of the second touch screen **14**, or a tap gesture **1100***j*-**4** is generated from the create key within the first menu window **1104***c* loaded by selecting a menu button **1100***j*-**3**, the portable device recognizes the detection as a create command of the new event and proceeds to FIG. **21**H.

[0396] Referring to FIG. **21**H, the portable device replaces the view mode selection area **1102** of the first and second touch screens **12** and **14**, the calendar area **1102***a*, the event lists **1104***a*, and the new event create key **1104** with first and second event create windows **1110***a* and **1110***b* for receiving event elements of the new event and displays the replaced first and second event create windows **1110***a* and **1110***b* in response to the create commands **1100***j*-**1**, **1100***j*-**2**, and **1100***j*-**4** of the new event. The first event create window **1110***a* displayed in the first touch screen **12** includes an event title input area, a start date selection area, an end date input area, and an all day selection area. The second event create window **1110***b* displayed in the second touch screen **14** includes at least one of a position input area related to the event, a participant input area, an alarm selection area, a repetition selection area, and an explanation input area. Each of the event create windows **1110***a* and **1110***b* may be scrolled in response to the detection of a flick up/down or a touch drag up/down within the corresponding window.

[0397] When a tap gesture is detected from at least one of the input areas, a virtual keypad is displayed in a predetermined area of the touch screen selected by the corresponding tap gesture. For example, when a tap gesture is detected from the event title input area displayed in the first touch screen **12**, the first touch screen **12** displays a virtual keypad in a lower half part of the first touch screen **12** and receives an event title through the virtual keypad. As a selectable embodiment, when a tap gesture is detected from one of the input areas, one virtual keypad is displayed in lower parts of both the first and second touch screens **12** and **14**.

[0398] /** ppt #13, 11. Text Input **/

[0399] Although not illustrated, when the portable device is in the landscape view mode, the upper touch screen can display the first event create window **1110***a* and the lower touch screen can display the second event create window **1110***b*. As one embodiment, when a tap gesture is detected from one of the input areas included in the upper touch screen, the virtual keypad is displayed in at least a part of the lower touch screen (lower half part or whole lower part). As one embodiment, when a tap gesture is detected from one of the input areas included in the lower touch screen, the virtual keypad is displayed in at least a part of the lower touch screen (for example, lower half part). As one embodiment, when a tap gesture is detected from one of the input areas included in the lower touch screen, the second event create window **1110***b* is displayed in the upper touch screen and the virtual keypad is displayed in the whole lower touch screen.

[0400] FIG. **21**I illustrates another example of first and second event create windows **1110***c* and **1110***d* displayed when a touch and hold **1100***j*-**1** is detected from a particular date of the calendar area **1102***a* of the first touch screen **12**. As illustrated in FIG. **21**I, a date in a position where the touch and hold **1100***j*-**1** is detected may be automatically input into the start date selection area and the end date selection area of the

first event create window **1110***c*. As a selectable embodiment, when the touch and hold **1100***j*-**1** is generated in a time line of the calendar area **1102***d* of the day mode, a start time and/or an end time may be automatically input into the first event create window **1110***c*.

[0401] FIGS. **21**J to **21**L illustrate a scenario for deleting an event registered in the schedule management application according to an exemplary embodiment.

[0402] Referring to FIG. **21**J, the portable device displays the view mode selection area **1102** and the calendar area **1102***a* in the first touch screen **12** and displays the event lists **1104***a* of the date selected from the calendar area **1102***a* of the second touch screen **14** and the new event create key **1104** in the second touch screen **14**. Although the calendar area **1102***a* of the month mode is illustrated herein, the event can be deleted in a similar way to that when the calendar area corresponds to the calendar area **1102***c*, **1102***d*, or **1102***e* of the week mode, the day mode, or the list mode. The portable device can detect a deletion command of the event through the first or second touch screen **12** or **14** or the physical button (menu button) in the lower part of the first touch screen **12**. For example, when a tap gesture **1120***a* is detected from the deletion key within the first menu window **1104***c* loaded by selecting the menu button **1120**, the portable device recognizes the detection as a deletion command of the registered event and proceeds to FIG. **21**K.

[0403] Referring to FIG. **21**K, the portable device replaces the view mode selection area **1102** and the calendar area **1102***a* of the first touch screen **12** with an event deletion window **1112***a* and a deletion key **1112***b* for executing the deletion command and displays the replaced event deletion window **1112***a* and deletion key **1112***b* in response to the deletion command **1120***a*. The event deletion window **1112***a* lists event deletion items corresponding to events registered in the month of the calendar area **1102***a* displayed in the first touch screen **12**. Each of the event deletion items includes an event name of each registered event and a check box, and an input of selecting the event item to be deleted is detected through the check box. When the calendar area **1102***a* of the month mode is displayed in the first touch screen **12**, the event deletion window **1112***a* includes events registered in the month of the calendar area **1102***a*. Similarly, when the calendar area **1102***c*, **1102***d*, or **1102***e* of the week mode, the day mode, or the list mode is displayed in the first touch screen **12**, the event deletion window **1112***a* includes events registered in the corresponding week, day, or list.

[0404] The second touch screen **14** may be in a deactivated state while the event deletion window **1112***a* is displayed in the first touch screen **12**. In the deactivated state, the second touch screen **14** is filled with a shadow and does not respond to the touch gesture.

[0405] When a tap gesture **1120***b* is detected from at least one check box of the event deletion events of the first touch screen **12** and a tap gesture **1120***c* is detected from the deletion key **1112***b*, the portable device proceeds to FIG. **21**L.

[0406] Referring to FIG. **21**L, the portable device replaces the event deletion window **1112***a* and the deletion key **1112***b* of the first touch screen **12** with previous information, that is, the view mode selection area **1102** and the calendar area **1102***a* and displays the replaced view mode selection area **1102** and calendar area **1102***a* in response to the detection of the tap gesture **1120***c*. When the event deletion window **1112***a* is removed from the first touch screen **12**, the second touch screen **14** escapes from the deactivated state and event lists **1104***h* including registered events except for the event item selected from the event deletion window **1112***a* by the tap gesture **1102***b* are displayed.

[0407] FIGS. **21**M to **21**O illustrate another scenario for deleting an event registered in the schedule management application.

[0408] Referring to FIG. **21**M, the portable device displays the view mode selection area **1102** and the calendar area **1102***c* in the first touch screen **12** and displays the event lists **1104***a* of the date selected from the calendar area **1102***a* and the new event create key **1104** in the second touch screen **14**. Although the calendar area **1102***a* of the month mode is illustrated herein, the event can be deleted in a similar way to that when the calendar area corresponds to the calendar area **1102***c*, **1102***d*, or **1102***e* of the week mode, the day mode, or the list mode. When a tap gesture **1120***e* is detected from the deletion key within the second menu window **1104***d* loaded by selecting the menu button **1120***d* in the lower part of the second touch screen **14**, the portable device recognizes the detection as a deletion command of the registered event and proceeds to FIG. **21**N.

[0409] Referring to FIG. **21**N, the portable device replaces the event lists **1104***a* and the new event create key **1104** of the second touch screen **14** with an event deletion window **1112***c* and a deletion key **1112***d* for executing the deletion command and displays the replaced event deletion window **1112***c* and deletion key **1112***d* in response to the deletion command **1120***e*. The event deletion window **1112***c* lists events registered in the event lists **1104***a* displayed in the second touch screen **14**, that is, event deletion items corresponding to the events registered in the selected date of the first touch screen **12**. Each of the event deletion items includes an event name of each registered event and a check box, and an input of selecting the event item to be deleted is detected through the check box. The first touch screen **12** may be in a deactivated state while the event deletion window **1112***c* is displayed in the second touch screen **14**. In the deactivated state, the first touch screen **12** may be filled with a shadow and does not respond to the touch gesture.

[0410] When a tap gesture **1120***f* is detected from at least one check box of the event deletion events of the second touch screen **14** and a tap gesture **1120***g* is detected from the deletion key **1112***d*, the portable device proceeds to FIG. **21**O.

[0411] Referring to FIG. **21**O, the portable device replaces the event deletion window **1112***c* and the deletion key **1112***d* of the second touch screen **14** with event lists **1104***i* and the new event create key **1104** and displays the replaced event lists **1104***i* and new event create key **1104** in response to the detection of the tap gesture **1120***g*. The event lists **1104***i* includes registered events except for the event item selected from the event deletion window **1112***c* by the tap gesture **1120***f* in comparison with the previous event lists **1104***a*. When the event deletion window **1112***c* is removed from the second touch screen **14**, the first touch screen **12** escapes from the deactivated state.

[0412] FIGS. **22**A to **22**M illustrate scenarios of expanding the calendar area in the schedule management application and displaying the expanded calendar area according to one or more exemplary embodiments.

[0413] Referring to FIG. **22**A, the portable device displays a view mode selection area **1202** and a calendar area **1202***a* in the first touch screen **12** and displays event lists **1206***a* of a date **1204***a* selected from a calendar area **1202***a* and a new event create key **1206** in the second touch screen **14**. Although

the expansion of the calendar area **1202***a* of the month mode is illustrated herein, the calendar area **1102***c*, **1102***d*, or **1102***e* of the week mode, the day mode, or the list mode can be expanded in a similar way. The portable device detects a touch gesture **1200***a* of expanding an area selected from the calendar area **1202***a*, that is, a pinch zoom-in. As another embodiment, the touch gesture **1200***a* includes two touch drags which are generated at the same time and move away from each other in approximately opposite directions. The touch gesture **1200***a* starts at two positions within the calendar area **1202***a*, and one of the two touch drags may end at the second touch screen **14**. At least one touch included in the touch gesture **1200***a* passes through the hinge between the two touch screens **12** and **14**.

[0414] As another embodiment, the portable device can detect a zoom-in command through the menu button in the lower part of the first touch screen **12**. That is, when the menu button which is one of the physical buttons located in the lower part of the first touch screen **12** is selected, for example, when a touch gesture **1200***b* is detected, the portable device displays a first menu window **1202***b* in the lower part of the first touch screen **12** in response to the detection of the touch gesture **1200***b*. The first menu window **1202***b* includes at least one of a create key for creating a new event, a go to key for moving to a selected date, a today key for moving to the today's date, a dual zoom key for expanding a displayed calendar area, a search key for searching for a desired event, a deletion key for deleting a registered event, and a setting key for changing a setting of the schedule management application. The first menu window **1202***b* including the dual zoom key may be loaded by a touch of the menu button while the calendar area of the month mode or the week mode is displayed in the first touch screen **12**.

[0415] When the portable device detects a touch gesture **1200***c*, that is, a tap gesture from the dual zoom key within the first menu window **1202***b* loaded by selecting the menu button **1200***b* in the lower part of the first touch screen **12**, the portable device proceeds to FIG. **22**B.

[0416] Referring to FIG. **22**B, in response to the detection of the pinch zoom-in **1200***a* on the calendar area **1202***a* or the tap gesture **1200***c* on the dual zoom key, the portable device displays first and second calendar areas **1208***a* and **1208***b* expanded from the calendar area **1202***a* in the first and second touch screens **12** and **14**. The first and second calendar areas **1208***a* and **1208***b* include larger day blocks than the calendar area **1202***a* before the expansion and display more information in comparison with the events registered in each day block. The first calendar area **1208***a* includes some of the day blocks corresponding to the month of the calendar area **1202***a*, and the second calendar area **1208***b* includes the remainders of the day blocks corresponding to the month of the calendar area **1202***a*. The new event create key **1206** may be disposed in an upper part of the second calendar area **1208***b* in the second touch screen **14** in order to successively dispose the first and second calendar areas **1208***a* and **1208***b*. The day block **1204***b* located in the today's date in the first and second calendar areas **1208***a* and **1208***b* may be displayed with a predetermined color which is visually distinguished.

[0417] As a selectable embodiment, detailed information on the date selected from the month areas **1208***a* and **1208***b* may be displayed in a form of a popup window while the first and second month areas **1208***a* and **1208***b* are displayed in the first and second touch screens **12** and **14**.

[0418] The portable device detects a touch gesture **1200***d* of reducing the area selected from the first and second month areas **1208***a* and **1208***b*, that is, pinch zoom-out and returns to FIG. **22**A. As another embodiment, the touch gesture **1200***d* includes two touch drags which are simultaneously generated and approach each other. The touch gesture **1200***d* may start at each of different touch screens **12** and **14** and end at one of the first and second touch screens **12** and **14**. At least one touch included in the touch gesture **1200***d* passes through the hinge between the two touch screens **12** and **14**.

[0419] Referring to FIG. **22**C, the portable device displays a view mode selection area **1202** and a calendar area **1202***c* of the week mode in the first touch screen **12** and displays event lists **1206***b* of the date selected from the calendar area **1202***c* and the new event create key **1206** in the second touch screen **14**. The portable device recognizes a touch gesture **1200***e* of expanding the area selected from the calendar area **1202***c*, that is, pinch zoom-in. As another embodiment, the touch gesture **1200***e* includes two touch drags which are simultaneously generated and move away from each other in approximately opposite directions. The touch gesture **1200***e* may start at two positions within the calendar area **1202***a* and one of the two touch drags may end at the second touch screen **14**. At least one touch included in the touch gesture **1200***e* passes through the hinge between the two touch screens **12** and **14**. Although not illustrated, the portable device can detect a zoom-in command of the calendar area **1202***c* of the week mode through the menu button in the lower part of the first touch screen **12**.

[0420] Referring to FIG. **22**D, the portable device detects a tap gesture from the dual zoom key within the first menu window loaded by selecting the menu button in the lower part of the first touch screen **12** or detects the pinch zoom-in on the calendar area **1202***c*, and displays the first and second calendar areas **1208***c* and **1208***d* expanded from the calendar area **1202***c* in the first and second touch screens **12** and **14**. The first and second calendar areas **1208***c* and **1208***d* include larger hour blocks in comparison with the calendar area **1202***c* before the expansion and display more information on the event registered in each of the hour blocks. The first calendar area **1208***c* includes hour blocks of some of the dates corresponding to the week of the calendar area **1202***c*, and the second calendar area **1208***d* includes hour blocks of the remainders of the dates corresponding to the week of the calendar area **1202***c*. The new event create key **1206** may be disposed in an upper part of the second calendar area **1208***d* in the second touch screen **14** in order to successively dispose the first and second calendar areas **1208***c* and **1208***d*.

[0421] As a selectable embodiment, detailed information on the date selected from the calendar areas **1208***c* and **1208***d* may be displayed in a form of a popup window while the first and second calendar areas **1208***c* and **1208***d* are displayed in the first and second touch screens **12** and **14**.

[0422] The portable device detects a touch gesture **1200***f* of reducing the area selected from the first and second calendar areas **1208***c* and **1208***d*, that is, pinch zoom-out and returns to FIG. **22**C. As another embodiment, the touch gesture **1200***f* includes two touch drags which are simultaneously generated and approach each other. The touch gesture **1200***f* may start at each of the different touch screens **12** and **14** and end at one of the first and second touch screens **12** and **14**. As one embodiment, the calendar area reduced by the touch gesture **1200***f* may be displayed in one touch screen where the touch gesture

1200*f* ends. At least one touch included in the touch gesture **1200***f* passes through the hinge between the two touch screens **12** and **14**.

[0423] A scenario in the calendar area expanded to occupy the first and second touch screens **12** and **14** will be described with reference to FIGS. **22**E to **22**G.

[0424] Referring to FIG. **22**E, the portable device displays the first and second calendar areas **1208***a* and **1208***b* including day blocks corresponding to one month in the first and second touch screens **12** and **14**, respectively. The first calendar area **1208***a* includes some of the day blocks corresponding to the selected month, and the second calendar area **1208***b* includes the remainders of the day blocks. When a predetermined touch gesture **1200***g*, for example, a tap gesture or a touch and hold is detected from one **1204***c* of the day blocks included in the first and second calendar areas **1208***a* and **1208***b*, the portable device proceeds to FIG. **22**F.

[0425] Referring to FIG. **22**F, the portable device places a date indicator **1204***e* in a date of the day block **1204** selected by the touch gesture **1200***g* and displays a popup window **1210***a* showing detailed information on an event registered in the selected date in an area near the selected date. In the shown example, the popup window **1210***a* is detailed information on the registered event of "Alice Birthday" of the selected date of "15" and provides at least one of a time such as "Tue, 15/01/2009 8:00 AM~Tue, 15/01/2009 3:00 PM", a place, and a map image. When an input **1200***h* of a back button which is one of the physical buttons located in the lower part of the first touch screen **12** is detected while the popup window **1210***a* is displayed, the portable device removes the popup window **1210***a* and restores the first and second touch screens **12** and **14** as illustrated in FIG. **22**E.

[0426] When a predetermined touch gesture **1200***i*, for example, a tap gesture or a touch and hold is detected from another one **1204** of the day blocks included in the first and second calendar areas **1208***a* and **1208***b* while the popup window **1210***a* is displayed, the portable device proceeds to FIG. **22**G.

[0427] Referring to FIG. **22**G, the portable device places a date indicator **1204***f* in the date of the day block **1204***d* selected by the touch gesture **1200***i* and removes the displayed popup window **1210***a* in response to the detection of the touch gesture **1200***i*. When there is no event registered in the date of the day block **1204***d* selected by the touch gesture **1200***i*, a new popup window is not displayed.

[0428] FIGS. **22**H to **22**J illustrate a scenario for generating a new event in the expanded calendar area of the schedule management application according to an exemplary embodiment.

[0429] Referring to FIG. **22**H, the portable device displays the first and second calendar areas **1208***a* and **1208***b* including day blocks corresponding to the selected month in the first and second touch screens **12** and **14**, respectively. When the menu button which is one of the physical buttons disposed in the lower part of the first touch screen **12** is selected, for example, when a touch gesture **1200***j* is detected while the calendar area of the month mode or the week mode is displayed over the two touch screens **12** and **14**, the portable device displays a menu window **1208***e* for the expanded calendar area in the lower part of the first touch screen **12** in response to the detection of the touch gesture **1200***j*. The menu window **1208***e* includes at least one of a create key for creating a new event, a go to key for moving to a selected date, a today key for moving to the today's date, a search key for searching for a desired event, a deletion key for deleting a registered event, and a setting key for changing a setting of the schedule management application.

[0430] The portable device can detect a create command of a new event through the first or second touch screen **12** or **14** or the menu button in the lower part of the first touch screen **12**. For example, when a touch and hole **1200***k*-**2** is detected from one of the day blocks included in the first and second calendar areas **1208***a* and **1208***b* or a tap gesture **1200***k*-**1** is detected from the create key within the menu window **1208***e* loaded by selecting the menu button **1200***j* located in the lower part of the first touch screen **12**, the portable device recognizes the detection as a create command of the new event and proceeds to FIG. **22**I.

[0431] Referring to FIG. **22**I, the portable device replaces the first and second calendar areas **1208***a* and **1208***b* of the first and second touch screens **12** and **14** with first and second event create windows **1210***a* and **1210***b* and displays the replaced first and second event create windows **1210***a* and **1210***b* in response to the create commands **1200***k*-**1** and **1200***k*-**2**. The first event create window **1210***a* displayed in the first touch screen **12** includes an event title input area, a start date selection area, an end date selection area, and an all day selection area. The second event create window **1210***b* displayed in the second touch screen **14** includes at least one of a position input area related to the event, a participant input area, an alarm selection area, a repetition selection area, an explanation input area, and a storage key. When a tap gesture is detected from one of the input areas, a virtual keypad is displayed in a lower area of the corresponding touch screen. For example, when a tap gesture is detected from the event title input area, the first touch screen **12** displays the virtual keypad in a lower half part of the first touch screen **12** and receives an event title through the virtual keypad.

[0432] FIG. **22**J illustrates another example of first and second event create windows **1210***c* and **1210***b* displayed when the touch and hold **1200***k*-**2** is detected from a particular block of the calendar area **1208***a* displayed in the first touch screen **12**. As illustrated in FIG. **22**J, a date in a position where the touch and hold **1200***k*-**2** is detected is automatically input into a start date selection area and an end date selection area of the first event create window **1210***c*. As a selectable embodiment, when the touch and hold **1200***k*-**2** is generated in a time line of the calendar area of the day mode, a start time and/or an end time may be additionally input into the first event create window **1210***c* together with the start/end date.

[0433] FIGS. **22**K to **22**M illustrate a scenario for deleting an event registered in the schedule management application according to an exemplary embodiment.

[0434] Referring to FIG. **22**K, the portable device displays the first and second calendar areas **1208***a* and **1208***b* including day blocks included in the selected month in the first and second touch screens **12** and **14**, respectively. Although the calendar areas **1208***a* and **1208***b* of the month mode are illustrated herein, the event may be deleted in a similar way to that when the calendar area of the week mode is displayed over the two touch screens **12** and **14**. The portable device can detect a deletion command of the event through the first or second touch screen **12** or **14** or the menu button which is one of the physical buttons in the lower part of the first touch screen **12**. For example, when a tap gesture **1214***b* is detected from the deletion key within the menu window **1208***e* loaded by select-

ing the menu button **1214***a*, the portable device recognizes the detection as a deletion command of the registered event and proceeds to FIG. **22**L.

[0435] Referring to FIG. **22**L, the portable device replaces the calendar area **1208***a* of the first touch screen **12** with an event deletion window **1212***a* and a deletion key **1212***b* for executing the deletion command and displays the replaced event deletion window **1212***a* and deletion key **1212***b* in response to the deletion command **1214***b*. The event deletion window **121***a* lists event deletion items corresponding to the registered events of the month of the calendar area **1202***a* displayed in the first touch screen **12**. Each of the event deletion items includes an event name of each registered event and a check box, and an input of selecting the event item to be deleted is detected through the check box. When the calendar area **1208***a* of the month mode is displayed in the first touch screen **12**, the event deletion window **1212***a* includes events registered in the month of the calendar area **1208***a*. Similarly, when the calendar area of the week mode is displayed in the first touch screen **12**, the event deletion window **1212***a* includes events registered in the corresponding week.

[0436] The second touch screen **14** may be in a deactivated state when the event deletion window **1212***a* is displayed in the first touch screen **12**. In the deactivated state, the second touch screen **14** is filled with a shadow and does not respond to the touch gesture.

[0437] When a tap gesture **1214***c* is detected from at least one check box of the event deletion item, that is, when a tap gesture **1214** is detected from "New year's Day" and "B's Birthday" and then a tap gesture **1214***d* is detected from the deletion key **1212***b* in the shown example, the portable device proceeds to FIG. **22**M.

[0438] Referring to FIG. **22**M, the portable device replaces the event deletion window **1212***a* and the deletion key **1212***b* of the first touch screen **12** with previous information, that is, the calendar area **1208***a* and displays the replaced calendar area **1208***a* in response to the detection of the tap gesture **1214***d*. When the event deletion window **1212***a* is removed from the first touch screen **12**, the second touch screen **14** escapes from the deactivated state. From the first and second calendar areas **1208***a* and **1208***b* of FIG. **22**M, the event item selected by the tap gesture **1214***c* on the event deletion window **1212***a*, that is, "B's Birthday" is removed.

[0439] The portable device provides a more convenient user interface for a call application through the display device including the first touch screen and the second touch screen arranged on at least one foldable panel.

[0440] FIGS. **23**A to **23**P illustrate a user interface of a call application according to one or more exemplary embodiments.

[0441] FIGS. **23**A to **23**E illustrate a scenario for processing an outgoing call in the call application according to an exemplary embodiment.

[0442] Referring to FIG. **23**A, the first touch screen **12** displays a first page **1302***a* of the home screen and a dock area **1302** including icons of frequently used applications, and the second touch screen **14** displays an A application **1302***b*. When a predetermined touch gesture **1300***a*, for example, a tap gesture is detected from an icon of the call application among icons of the application menu which provides the call application, a contact information application, a message application, and application lists included in the dock area **1302**, the portable device executes the call application and proceeds to FIG. **23**B. Although the dock area **1302** displayed together with the home screen is illustrated herein, the following description can be similarly applied to a case where the dock area **1302** is displayed together with another application or the call application starts through a control of another menu of the portable device.

[0443] Referring to FIG. **23**B, the portable device starts the call application in response to the detection of a touch gesture **1300***a* and replaces the first page **1302***a* of the home screen and the dock area **1302** with an outgoing call screen **1304** provided by the call application and displays the replaced outgoing call screen **1304** in the first touch screen **12**. The outgoing call screen **1304** includes at least one of a number display area **1304***a*, a keypad area **1304***b*, a call key **1304***c*, a video call key **1304***d*, a message sending key **1304***e*, and a function key area **1304***f*. Here, the function key area **1304***f* includes at least one of soft keys of functions which can be provided by the call application, for example, a keypad selection key for selecting whether to display the keypad area **1304***b* or selecting a type of keypad area **1304***b*, a log key for showing a call record, and a contact information key for calling contact numbers. As a selectable embodiment, when the call application is displayed in the first touch screen **12**, the second touch screen **14** continuously displays the A application **1302***b*.

[0444] When a phone number to be called is input through the keypad area **1304***b*, the first touch screen **12** displays the input phone number in the number display area **1304***a*, and further displays a picture image and a name of the contact information corresponding to the phone number when they exist. When the input of the phone number is completely input into the keypad area **1304***b* of the first touch screen **12** and a tap gesture **1300***b* is detected from the call key **1304***c*, the portable device proceeds to FIG. **23**C.

[0445] Referring to FIG. **23**C, the portable device replaces the outgoing call screen **1304** with a dialing screen **1306** and displays the replaced dialing screen **1306** in the first touch screen **12** in response to the detection of the tap gesture **1300***b*. The dialing screen **1306** includes a call participant identification area **1306***a* and a function key area **1306***b*. The call participant identification area **1306***a* includes at least one of a name, a picture image, and a phone number of a counterpart call participant corresponding to the input phone number. The function key area **1306***b* includes at least one of soft keys of mid-call functions, for example, a phone number addition key, a dial pad call key, a call end key, a speaker key, a mute key, and a headset connection key. The phone number addition key, the mute key, and the headset connection key which cannot be used during the dialing may be deactivated. Here, the speaker key performs switching between a public call mode and a private call mode. Here, the public call mode refers to a state of relatively increasing volume of the speaker and sensitivity of the microphone to allow a remote call (or a state of turning on an external speaker), that is, a speaker phone mode, and the private call mode refers to a state of relatively decreasing volume of the speaker and sensitivity of the microphone to allow a call performed by the user having the portable device close to user's ear and mouth (or a state of turning off an external speaker).

[0446] When a call connection starts in a state where the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are unfolded, the second touch screen **14** continuously displays the previously displayed A applica-

tion **1302***b*, is turned off, or displays a guide message screen **1302***c* of advising the user to fold the portable device for the call.

[0447] As a selectable embodiment, the call application connects the call in the public call mode in the state where the first and second panels **2** and **4** are unfolded. Further, when the first and second panels **2** and **4** of the portable device are folded-out such that the first touch screen **12** faces a front side during the dialing, the second touch screen **14** may be turned off.

[0448] When a counterpart call participant detects that the call is connected in response to the call connection, the portable device proceeds to FIG. **23**D.

[0449] Referring to FIG. **23**D, the portable device displays a mid-call screen **1308** in the first touch screen **12** in response to the detection of the call connection. The mid-call screen **1308** includes a call participant identification area **1308***a*, a call duration time **1308***b*, and a function key area **1308***c*. The call participant identification area **1308***a* includes at least one of a picture image, a call participant name, and a phone number. The function key area **1308***c* includes at least one of a phone number addition key, a dial pad call key, a call end key, a speaker mode switching key, a mute key, and a headset connection key.

[0450] When the call is connected in the state where the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are unfolded, the second touch screen **14** can remove the guide message screen **1302** and display the previously displayed information, that is, the A application **1302***b*. As another embodiment, the second touch screen **14** continuously maintains the guide message screen **1302***c* during the call in the unfolded state.

[0451] When it is detected that the first and second panels **2** and **4** included in the portable device are folded-out **1300***b* during the call in the public call mode, the portable device proceeds to FIG. **23**E. Referring to FIG. **23**E, the portable device turns off the second touch screen **14** and switches the public call mode to a deactivated state, that is, the private call mode in response to the folded-out **1300***b* of the first and second panels **2** and **4**. Although not illustrated, when it is detected that the first and second panels **2** and **4** included in the portable device are unfolded during the call in the private call mode, the portable device displays again the previously displayed information, that is, the A application **1302***b* in the second touch screen **14** and activates the public call mode as illustrated in FIG. **23**D.

[0452] FIGS. **23**F to **23**J illustrate another scenario for processing an outgoing call in the call application according to an exemplary embodiment.

[0453] Referring to FIG. **23**F, the first touch screen **12** displays the first page **1302***a* of the home screen and the dock area **1302**, and the second touch screen **14** displays a second page **1302***d*. When a predetermined touch gesture **1300***c*, for example, a tap gesture is detected from an icon of the call application included in the dock area **1302**, the portable device executes the call application and proceeds to FIG. **23**G. Although the dock area **1302** displayed together with the home screen is illustrated herein, the following description can be similarly applied to a case where the dock area **1302** is displayed with another application or the call application starts through a control of another menu of the portable device.

[0454] Referring to FIG. **23**G, the portable device starts the call application in response to the detection of the touch gesture **1300***c* and displays an outgoing call screen provided by the call application **1304**, that is, a number display area **1304***a*, the keypad area **1304***b*, the call key **1304***c*, the video call key **1304***d*, the message sending key **1304***e*, and the function key area **1304***f* in the first touch screen **12**. For example, the key area **1304***f* includes at least one of a keypad selection key for selecting whether to display the keypad area **1304***b* or selecting a type of keypad area **1304***b*, a log key for showing a call record, and a contact information key for loading contact numbers. As a selectable embodiment, when the call application starts in the first touch screen **12** while the second touch screen **14** displays the second page **1302***d* of the home screen, the dock area **1302** may be moved to and then displayed in a lower part of the second page **1302***d* of the second touch screen **14**.

[0455] When a phone number to be called is input through the keypad area **1304***b*, the first touch screen **12** displays the input phone number in the number display area **1304***a*, and further displays a picture image and a name of the contact information corresponding to the phone number when they exist. When the phone number is completely input and a tap gesture **1300***d* is detected from the call key **1304***c*, the portable device proceeds to FIG. **23**H.

[0456] Referring to FIG. **23**H, the portable device displays the dialing screen **1306** in the first touch screen **12** in response to the detection of the tap gesture **1300***d*. The dialing screen **1306** includes the call participant identification area **1306***a* and the function key area **1306***b*. The call participant identification area **1306***a* includes at least one of a picture image, a call participant name, and a phone number. The function key area **1306***b* includes at least one of a phone number addition key, a dial pad call key, a call end key, a speaker key, a mute key, and a headset connection key. The phone number addition key, the mute key, and the headset connection key which cannot be used during the dialing may be deactivated.

[0457] When a call connection starts in a state where the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are unfolded, the second touch screen **14** continuously displays the previously displayed A application **1302***b*, is turned off, or displays a guide message screen **1302***c* of advising the user to fold the portable device for the call. At this time, the guide message screen **1302***c* may be displayed to be overwritten with the second page **1302***d* of the home screen and the dock area **1302***e* which are previously displayed.

[0458] As a selectable embodiment, the call application connects the call in the public call mode in the state where the first and second panels **2** and **4** are unfolded. Further, when the portable device is folded-out, the second touch screen **14** may be turned off.

[0459] When a counterpart call participant detects that the call is connected in response to the call connection, the portable device proceeds to FIG. **23**I.

[0460] Referring to FIG. **23**D, the portable device displays the mid-call screen **1308** in the first touch screen **12** in response to the detection of the call connection. The mid-call screen **1308** includes the call participant identification area **1308***a*, the call duration time **1308***b*, and the function key area **1308***c*.

[0461] When the call is connected in the state where the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are unfolded, the second touch screen can replace the guide message screen **1302***c* with the previously displayed information, that is, the second page **1302***d* of the

home screen and display the replaced second page **1302***d*. As another embodiment, the second touch screen **14** continuously maintains the guide message screen **1302***c* during the call in the unfolded state.

[0462] When it is detected that the first and second panels **2** and **4** included in the portable device are folded-out **1300***e* during the call in the public call mode, the portable device turns off the second touch screen **14** and switches the public call mode to the private call mode as illustrated in FIG. **23**J. When the call is performed in the folded-out state and then ends, for example, when a tap gesture **1300***f* is detected from the call end key, the portable device replaces the mid-call screen **1308** of the second touch screen **12** with the previous information, that is, the second page **1302***d* of the home screen and the dock area **1302***e* and displays the replaced second page **1302***d* and the dock area **1302***e*.

[0463] FIGS. **23**K to **23**M illustrate a scenario for processing an incoming call in the call application according to one or more exemplary embodiments.

[0464] Referring to FIG. **23**K, the first touch screen **12** displays a first application **1322***a* and the second touch screen **14** displays a second application **1322***b*. The first and second applications **1322***a* and **1322***b* may be any of the home screen, the application menu, a basic application, and an application installed by the user. In the shown example, the first application **1322***a* is a message application such as a Short Messaging Service (SMS), an e-mail, or an Instant Messaging Service (IMS) and the second application **704** is a photo gallery application. As another example, the first and second touch screens **12** and **14** can display two task screens of one application in a main-sub mode or commonly display one task screen of one application in a full mode. When an incoming call is generated while the first and second touch screens **12** and **14** display one or more applications **1322***a* and **1322***b*, the portable device proceeds to FIG. **23**L.

[0465] Referring to FIG. **23**L, the portable device starts the call application in response to the generation of the incoming call, and replaces the first application **1322***a* with an incoming call screen **1324** provided by the call application and displays the replaced incoming call screen **1324** in the first touch screen **12**. The incoming call screen **1324** includes at least one of a call participant identification area **1324***a*, an incoming key area **1324***b*, and a rejection message key **1324***c*. The call participant identification area **1324***a* includes at least one of a picture image, a call participant name, and a phone number. The incoming key area **1324***b* may include an incoming key and a rejection key. The rejection key is used to reject the incoming call without sending a message. The rejection message key **1324***c* is used to automatically send a rejection message by the message application.

[0466] The second touch screen **14** is deactivated while the incoming call screen **1324** is displayed in the first touch screen **12** and a guide message screen **1326** of advising the user to fold the portable device for the call is displayed.

[0467] When a predetermined touch gesture **1310***a*, for example, a tap gesture on the incoming key or a touch drag (slide) starting at the incoming key and moving in a predetermined direction is detected, the portable device proceeds to FIG. **23**M.

[0468] Referring to FIG. **23**M, the portable device connects a call with a counterpart call participant, and replaces the incoming call screen **1324** with the mid-call screen **1324** and displays the replaced mid-call screen **1324** in the first touch screen **12** in response to the detection of the touch gesture **1310***a*. The mid-call screen **1324** includes the call participant identification area **1324***a*, the call duration time **1324***b*, and the function key area **1324***c*. The call participant identification area **1324***a* includes at least one of a picture image, a counterpart call participant name, and a phone number. The function key area **1324***c* includes at least one of a phone number addition key, a dial pad call key, a call end key, a speaker mode switching key, a mute key, and a headset connection key.

[0469] As a selectable embodiment, when a touch gesture **1310***a* is detected from the incoming key in the state where the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are unfolded, the call application starts a call connection in the public call mode and the second touch screen **14** is activated again.

[0470] When the call ends in the mid-call screen **1324**, for example, when a tap gesture **1320***b* is detected from the call end key within the function key area **1324***c*, the portable device returns to FIG. **23**K to replace the mid-call screen **1324** of the first touch screen **12** with the previous information, that is, the first application **1322***a* and display the replaced first application **1322***a*.

[0471] FIGS. **23**N to **23**P illustrate another scenario for responding to an incoming call in the call application according to one or more exemplary embodiments.

[0472] Referring to FIG. **23**N, the first and second touch screens **12** and **14** display first and second task screens **1326***a* and **1326***b* of the first application. The first application may be any of the home screen, the application menu, the basic application, and the application installed by the user. In the shown example, the first application is a photo gallery application providing two task screens having different depths, the first task screen **1326***a* of the first touch screen **12** includes one page of a plurality of thumbnail images, and the second task screen **1326***b* of the second touch screen **14** displays a picture image of one thumbnail image selected from the thumbnail images with a larger size, that is, a full size.

[0473] When an incoming call is generated while the first and second touch screens **12** and **14** displays the task screens **1326***a* and **1326***b* of the first application, the portable device proceeds to FIG. **23**O.

[0474] Referring to FIG. **23**O, the portable device starts the call application in response to the generation of the incoming call, and replaces the first task screen **1326***a* of the first application with an incoming call screen **1328** provided by the call application and displays the replaced incoming call screen **1328** in the first touch screen **12**. The incoming call screen **1328** includes a call participant identification area **1328***a*, an incoming key area **1328***b*, and a rejection message key **1328***c*. The call participant identification area **1328***a* includes at least one of a picture image, a call participant name, and a phone number. The incoming key area **1328***b* may include an incoming key and a rejection key. The rejection message key **1328***c* is used to automatically send a rejection message by the message application.

[0475] The second touch screen **14** is deactivated while the incoming call screen **1328** is displayed in the first touch screen **12**, and a guide message screen **1330** of advising the user to fold the portable device for the call is displayed.

[0476] When a predetermined touch gesture **1320***c* on the incoming key within the incoming key area **1328***b*, for example, a tap gesture or a touch drag (slide) starting at the incoming key and moving in a predetermined direction is detected, the portable device proceeds to FIG. **23**P.

[0477] Referring to FIG. **23**P, the portable device connects a call with a counterpart call participant, and replaces the incoming call screen **1328** with the mid-call screen **1332** and displays the replaced mid-call screen **1332** in the first touch screen **12** in response to the detection of the touch gesture **1320***c*. The mid-call screen **1332** includes a call participant identification area **1332***a*, a call duration time **1332***b*, and a function key area **1332***c*. The call participant identification area **1332***a* includes at least one of a picture image, a counterpart call participant name, and a phone number. The function key area **1332***c* includes at least one of a phone number addition key, a dial pad call key, a call end key, a speaker mode switching key, a mute key, and a headset connection key.

[0478] As a selectable embodiment, when a touch gesture **1320***c* is detected from the incoming key in the state where the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are unfolded, the call application starts a call connection in the public call mode and the second touch screen **14** is activated again.

[0479] When the call ends in the mid-call screen **1332**, for example, when a tap gesture **1320***d* is detected from the call end key within the function key area **1332***c*, the portable device returns to FIG. **23**N to replace the mid-call screen **1324** of the first touch screen **12** with the previous information, that is, the first task screen **1326***a* of the first application and display the replaced first task screen **1326***a*.

[0480] FIGS. **24**A to FIG. **24**R illustrate user interface of the call application according to another exemplary embodiment.

[0481] FIGS. **24**A to **24**C illustrate another scenario for responding to an incoming call of the call application according to an exemplary embodiment.

[0482] Referring to FIG. **24**A, the first touch screen **12** displays a text input area (that is, typing area) **1402***a* of the first application, and the second touch screen **14** displays additional information **1402***d* of the first application. The first application is an application requiring a typing input and illustrated as a message application herein. The first touch screen **12** further displays a message display area **1402***b* displaying a message input through the text input area **1402***a* and a virtual keypad area **1402***c* together with the text input area **1402***a*. The second touch screen **14** sequentially displays, for example, messages exchanged with the same counterpart as the additional information **1402***d* of the message application.

[0483] When an incoming call is generated while the first touch screen **12** displays the text input area **1402***a*, the portable device proceeds to FIG. **24**B.

[0484] Referring to FIG. **24**B, the portable device starts the call application in response to the generation of the incoming call, and replaces the text input area **1402***a* other information **1402***b* and **1402***c* with an incoming call screen **1404** provided by the call application and displays the replaced incoming call screen **1404** in the first touch screen **12**. The incoming call screen **1404** includes a call participant identification area **1404***a*, an incoming key area **1324***b*, and a rejection message key **1404***c*. The call participant identification area **1404***a* includes at least one of a picture image, a call participant name, and a phone number. The incoming key area **1404***b* may include an incoming key and a rejection key. The rejection message key **1404***c* is used to automatically send the rejection message by the message application.

[0485] The second touch screen **14** is deactivated while the incoming call screen **1404** is displayed in the first touch screen **12**, and a guide message screen **1406** of advising the user to fold the portable device for the call is displayed to be overwritten with the previous information **1402***d*.

[0486] When a predetermined touch gesture **1400***a* on the incoming key within the incoming key area **1404***b*, for example, a tap gesture, or a touch drag (slide) starting at the incoming key and moving in a predetermined direction is detected, the portable device proceeds to FIG. **24**C.

[0487] Referring to FIG. **24**C, the portable device connects a call with a counterpart call participant in response to the detection of the touch gesture **1400***a*, and replaces the incoming call screen **1404** with the mid-call screen **1404** and displays the replaced mid-call screen **1406** in the first touch screen **12**. The mid-call screen **1406** includes a call participant identification area **1406***a*, a call duration time **1406***b*, and a function key area **1406***c*. The call participant identification area **1406***a* includes at least one of a picture image, a counterpart call participant name, and a phone number. The function key area **1406***c* includes at least one of a phone number addition key, a dial pad call key, a call end key, a speaker mode switching key, a mute key, and a headset connection key.

[0488] When an incoming call is generated while information **1402***a*, **1402***b*, and **1402***c* including the text input area **1402***a* is displayed in the first touch screen **12**, the portable device moves the text input area **1402***a* and other information **1402***b* and **1402***c* previously displayed in the first touch screen **12** to the second touch screen **12** and displays the input area **1402***a* and other information **1402***b* and **1402***c* in the second touch screen **14** while displaying the mid-call screen **1406** in the first touch screen **12**. At this time, the text input area **1402***a* includes a text input into the first touch screen **12** before the incoming call and displays the text in the second touch screen **14**.

[0489] As a selectable embodiment, in the state where the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are unfolded, the portable device starts the call connection in the public call mode through the mid-call screen **1406** of the first touch screen **12** and provide support such that the user can continuously input messages through the text input area **1402***a* of the second touch screen **14**.

[0490] When a tap gesture **1400***b* is detected from the call end key of the function key area **1406***c*, the portable device returns to FIG. **24**A to replace the mid-call screen **1406** of the first touch screen **12** with the previous information, that is, the text input area **1402***a*, the message display area **1402***b*, and the virtual keypad area **1402***c* and display the replaced text input area **1402***a*, the message display area **1402***b*, and the virtual keypad area **1402***c* and displays the information **1402***d* before the incoming call in the second touch screen **14**.

[0491] FIGS. **24**D to **24**H illustrate another scenario for responding to an incoming call in the call application according to an exemplary embodiment.

[0492] Referring to FIG. **24**D, the first and second touch screens **12** and **14** display first and second task screens **1410***a* and **1410***b* of the first application. The first application may be any of the home screen, the application menu, the basic application, and the application installed by the user. In the shown example, the first application is a photo gallery application providing two task screens having different depths, the first task screen **1410***a* of the first touch screen **12** includes one page of a plurality of thumbnail images, and the second task screen **1410***b* of the second touch screen **14** displays a picture

image of one thumbnail image selected from the thumbnail images with a larger size, that is, a full size.

[0493] When an incoming call is generated while the first and second touch screens **12** and **14** display the task screens **1410***a* and **1410***b* of the first application, the portable device proceeds to FIG. **24**E.

[0494] Referring to FIG. **24**E the portable device starts the call application in response to the generation of the incoming call, and replaces the first task screen **1410***a* of the first application with an incoming call screen **1412** provided by the call application and displays the replaced incoming call screen **1412** in the first touch screen **12**. The incoming call screen **1412** includes a call participant identification area **1412***a*, an incoming key area **1412***b*, and a rejection message key **1412***c*. The call participant identification area **1412***a* includes at least one of a picture image, a call participant name, and a phone number. The incoming key area **1412***b* may include an incoming key and a rejection key. The rejection message key **1412***c* is used to automatically send a rejection message by the message application.

[0495] The second touch screen **14** is deactivated while the incoming call screen **1412** is displayed in the first touch screen **12**, and a guide message screen **1414** of advising the user to fold the portable device for the call is displayed.

[0496] When a predetermined touch gesture **1400***c* on the incoming key within the incoming key area **1412***b*, for example, a tap gesture or a touch drag (slide) starting at the incoming key and moving in a predetermined direction is detected, the portable device proceeds to FIG. **24**F.

[0497] Referring to FIG. **24**F, the portable device connects a call with a counterpart call participant, and replaces the incoming call screen **1412** with the mid-call screen **1416** and displays the replaced mid-call screen **1416** in the first touch screen **12** in response to the detection of the touch gesture **1400***c*. The mid-call screen **1416** includes a call participant identification area **1416***a*, a call duration time **1416***b*, and a function key area **1416***c*. The call participant identification area **1416***a* includes at least one of a picture image, a counterpart call participant name, and a phone number. The function key area **1416***c* includes at least one of a phone number addition key, a dial pad call key, a call end key, a speaker mode switching key, a mute key, and a headset connection key.

[0498] As a selectable embodiment, when a touch gesture **1400***c* is detected from the incoming key in the state where the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are unfolded, the call application starts a call connection in the public call mode and the second touch screen **14** is activated again as illustrated in FIG. **24**F.

[0499] When the home button which is one of the physical buttons disposed in the lower part of the second touch screen **14** is selected **1400***d* while the mid-call screen **1416** is displayed in the first touch screen **12** and the previous task screen **1410***b* is displayed in the second touch screen **14**, the portable device proceeds to FIG. **23**G.

[0500] Referring to FIG. **23**G, the portable device displays a first page **1418***a* of the home screen in the second touch screen **14** in response to the selected home button **1400***d*. At this time, the first touch screen **12** still displays the mid-call screen **1416**, and accordingly a dock area **1418***b* is displayed in the lower part of the second touch screen **14** together with the first page **1418***a*.

[0501] When a tap gesture **1400***e* is detected from the call end key of the function key area **1416***c*, the portable device proceeds to FIG. **24**H to replace the mid-call screen **1406** of the first touch screen **12** with the information before the incoming call, that is, the task screen **1410***b* of the first application and display the replaced task screen **1410***b* and maintains the first page **1418***a* of the home screen and the dock area **1418***b* of the second touch screen **14**. At this time, the first touch screen **12** displays a predetermined one of the task screens **1410***a* and **1410***b* of the first application, for example, the task screen **1418***b* having a final depth.

[0502] FIGS. **24**I to **24**J illustrate a scenario for rejecting an incoming call in the call application according to one or more exemplary embodiments.

[0503] Referring to FIG. **24**I, the portable device displays the incoming call screen **1404** provided by the call application in response to the generation of the incoming call. The incoming call screen **1404** includes the call participant identification area **1404***a*, the incoming key area **1404***b*, and the rejection message key **1404***c*. The call participant identification area **1404***a* includes at least one of a picture image, a call participant name, and a phone number. The incoming key area **1404***b* may include an incoming key and a rejection key. The rejection message key **1404***c* is used to automatically send the rejection message by the message application.

[0504] The second touch screen **14** is deactivated while the incoming call screen **1404** is displayed in the first touch screen **12**, and the guide message screen **1406** of advising the user to fold the portable device for the call is displayed.

[0505] When a predetermined touch gesture **1400***f* on the rejection message key **1404***c* within the incoming call screen **1404**, for example, a tap gesture or a touch drag (slide) starting at the rejection message key **1404***c* and moving in a predetermined direction is detected, the portable device proceeds to FIG. **24**J.

[0506] Referring to FIG. **24**J, the portable device displays a rejection message screen **1420** in the first touch screen **12** and a text input area **1422***a* for inputting a rejection message and a virtual keypad **1422***c* in the second touch screen **14** in response to the detection of the touch gesture **1400***f*. The rejection message screen **1420** includes a plurality of predesignated commonly used phrases as the rejection messages for rejecting the incoming call and sending keys. Although not illustrated, when a tap gesture is detected from the sending key of one of the commonly used phrases, the portable device automatically sends the corresponding selected commonly used phrase, for example, a short message including one of "I'll call later", "I'm in meeting", "I'm in class now", "In a cinema", and "While driving" to a counterpart call participant of the incoming call.

[0507] When a message for the rejection, for example, "I'm busy" is input through the virtual keypad **1422***c* and a tap gesture **1422***c* is detected from the sending key included in the text input area **1422***a*, the portable device automatically sends a short message including the input message of "I'm busy" to a counterpart call participant of the incoming call by the message application.

[0508] Although not illustrated, when the message is sent through the rejection message screen **1420** or the text input area **1422***a* and the virtual keypad **1422***c*, the portable device replaces the incoming call screen **1404** and the guide message screen **1406** of the first and second touch screens **12** and **14** with the information displayed before the incoming call and displays the replaced information.

[0509] FIGS. **24**K to **24**N illustrate another scenario for responding to a second incoming call in the call application according to one or more exemplary embodiments.

[0510] Referring to FIG. **24**K, the portable device displays the mid-call screen **1406** provided by the call application in the first touch screen **12**, performs a call with a first counterpart call participant, for example, "AAA", and displays the first application **1410***b* in the second touch screen **14**. The first application **1410***b* refers to another application, not the call application. When a second incoming call from a second counterpart call participant, for example, "BBB" is generated while the mid-call screen **1406** with the first counterpart call participant is displayed, the portable device proceeds to FIG. **24**L.

[0511] Referring to FIG. **24**L, the portable device replaces the mid-call screen **1406** of the first touch screen **12** with an incoming call screen **1426** of the second counterpart call participant and displays the incoming call screen **1426** while maintaining the call with the first counterpart call participant. The incoming call screen **1426** includes a call participant identification area **1426***a* of the second counterpart call participant "BBB", an incoming key area **1426***b*, and a rejection message key **1426***c*. The second touch screen **14** can continuously display the first application **1410***b* while the incoming call screen **1426** with the second counterpart call participant is displayed in the first touch screen **12**. As a selectable embodiment, when at least one of the panels included in the portable device is folded while the incoming call screen **1426** with the second counterpart call participant is displayed in the first touch screen **12**, the second touch screen **14** may be turned off.

[0512] When a predetermined touch gesture **1400***g* on the incoming key within the incoming key area **1426***b*, for example, a tap gesture or a touch drag (slide) starting at the incoming key and moving in a predetermined direction is detected, the portable device proceeds to FIG. **24**M.

[0513] Referring to FIG. **24**M, the portable device displays a multi incoming selection menu **1428** in the incoming call screen **1426** of the first touch screen **12** in a form of a popup window in response to the detection of the touch gesture **1400***g*. The multi incoming selection menu **1428***a* includes a waiting key **1427***a* for having the call with the first counterpart call participant wait and an end key **1428***b* for ending the call. Although not illustrated, when a tap gesture is detected from the end key **1428***b*, the portable device ends the call with the first counterpart call participant and displays the mid-call screen with the second counterpart call participant. When a tap gesture **1400***h* is detected from the waiting key **1428***a*, the portable device has the call with the first counterpart call participant wait and proceeds to FIG. **24**N. The waiting call is not connected with the microphone and the speaker.

[0514] Referring to FIG. **24**N, the portable device connects the call with the second counterpart call participant by the call application, and replaces the incoming call screen **1426** of the first touch screen **12** with a multi mid-call screen **1430** and displays the replaced multi mid-call screen **1430**. The multi mid-call screen **1430** includes call participant identification areas **1430***a* of a plurality of counterpart call participants who perform the call such as "AAA" and "BBB", a call swap key **1430***b*, a merge key **1430***c*, and a function key area **1430***d*. Each of the call participant identification areas **1430***a* includes at least one of a small picture image, a counterpart call participant name, and a phone number, and the call participant identification area which is in a call connection state may be displayed with a shadow or highlighted. The function key area **1430***c* includes at least one of a phone number addition key, a dial pad call key, a call end key, a speaker mode switching key, a mute key, and a headset connection key.

[0515] The call swap key **1430***b* is used to swap a current call participant. When a tap gesture is detected from the call swap key **1430***b* in a state where the call is connected with the second counterpart call participant "BBB", the portable device has the call with the second counterpart call participant "BBB" wait and connects the call with the first counterpart call participant "AAA". The merge key **1430***c* is used to simultaneously connect calls with all the waiting counterpart call participants. When a tap gesture is detected from the merge key **1430***c* in a state where the call with the first counterpart call participant "AAA" is in a waiting state and the call with the second counterpart call participant "BBB" is connected, the portable device connects all the calls with both the first and second counterpart call participants "AAA" and "BBB". The user can talk to both the first and second counterpart call participants through the portable device.

[0516] The second touch screen **14** can continuously display the first application **1410***b* while the multi mid-call screen **1430** is displayed in the first touch screen **12** in the state where the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are unfolded.

[0517] FIGS. **24**O to **24**R illustrate another scenario for responding to an incoming call by a motion of the portable device in the call application according to an exemplary embodiment.

[0518] Referring to FIG. **24**O, the first touch screen **12** displays a first application **1432** in a state where the first and second panels **2** and **4** are completely folded such that the first and second touch screens **12** and **14** face outward. In the shown example, the first application **1432** is a photo gallery application which displays one page of thumbnail images. At this time, the second touch screen **14** may be turned off. When an incoming call is generated while the first application **1432** is displayed in the folded state, the portable device proceeds to FIG. **24**P.

[0519] Referring to FIG. **24**P, the portable device starts the call application in response to the generation of the incoming call, and replaces the first application **1432** with an incoming call screen **1434** provided by the call application and displays the replaced incoming call screen **1434** in the first touch screen **12**. The incoming call screen **1434** includes a call participant identification area **1434***a*, an incoming key area **1434***b*, and a rejection message key **1434***c*. The call participant identification area **1434***a* includes at least one of a picture image, a call participant name, and a phone number. The incoming key area **1434***b* may include an incoming key and a rejection key. The rejection message key **1434***c* is used to automatically send a rejection message by the message application.

[0520] When the portable device detects overturning **1400***i* of making the second panel **4** including the second touch screen **14** side up while displaying the incoming call screen **1434** in the first touch screen **12** of the first panel **2** in the state where the first and second panels **2** and **4** are completely folded, the portable device proceeds to FIG. **24**Q.

[0521] Referring to FIG. **24**Q, the portable device turns off the first touch screen **12** and displays a rejection message screen **1436** in the second touch screen **14** in response to the detection of the overturning **1400***i*. Further, when the portable device is not in a vibration mode, the portable device turns off a ringtone. The rejection message screen **1436** includes a plurality of predetermined commonly used phrases for reject-

ing the incoming call and sending keys for the commonly used phrases and a new rejection message create key for additionally selecting an input of a new rejection message. Although not illustrated, when the sending key of one of the commonly used phrases is selected, the portable device automatically sends the corresponding selected commonly used phrase, for example, one of "I'll call later", "I'm in meeting", "I'm in class now", "In a cinema", and "While driving" to a counterpart call participant of the incoming call by the message application. Further, when a tap gesture is detected from the new rejection message create key, the portable device displays an input window of the rejection message in the second touch screen **14**.

[0522] When unfolding **1400***j* of the first and second panels **2** and **4** is detected while the rejection message screen **1436** is displayed in the second touch screen **14**, the portable device proceeds to FIG. **24**R.

[0523] Referring to FIG. **24**R, the portable device displays the rejection message screen **1436** in the first touch screen **12** and displays a text input area **1438***a* and a virtual keypad **1438***b* for sending the rejection message in the second touch screen **14** in response to the detection of the unfolding **1400***j*. When a message for the rejection, for example, "I'm busy" is input through the virtual keypad **1438***b* and a tap gesture is detected from the sending key included in the text input area **1438***a*, the portable device automatically sends a short message including the input message of "I'm busy" to a counterpart call participant of the incoming call by the message application.

[0524] The portable device provides a more convenient user interface for a camera application through the display device including the first touch screen and the second touch screen arranged on at least one foldable panel. As described above, the portable device drives the camera application and takes a picture through at least one camera module included in the first and second panels including the first and second touch screens to store the taken picture as a picture image.

[0525] A position of the camera module may be variously determined according to selection made by the manufacturer. For example, a first camera module is located in a front upper part of the first panel **2** and a second camera module is located in a rear upper part of the second panel **4**, so that the first camera module operates as a front camera and the second camera module operates as a rear camera. As another example, one camera module is located in the front upper part of the second panel **4** and the camera module operates as the front camera or the rear camera according to whether the second panel **4** is folded. As another example, the first and second camera modules are located in the front upper part and the rear upper part of the second panel **4**, the first camera module operates as the front camera or the rear camera according to whether the second panel **4** is folded, and the second camera module operates as the rear camera when the first camera module operates as the front camera.

[0526] FIGS. **25**A to **25**L and FIGS. **26**A to **26**K illustrate a user interface of the camera application according to one or more exemplary embodiments.

[0527] Here, an embodiment where the camera module is located in the front upper part of the second panel **4** including the second touch screen **14** will be described. Although not illustrated, an additional camera module may exist in a rear surface of the second panel **4**. When the portable device is in a portrait view mode, the first touch screen **12** which does not have the camera module is a main screen and the second touch screen **14** having the camera module is a sub screen. Although not illustrated, when the portable device is in a landscape view mode, an upper touch screen is a main screen and a lower touch screen is a sub screen. As another embodiment, the main screen and the sub screen may be determined according to the number and positions of the camera modules.

[0528] When the camera application is started by a shortcut button arranged in the housing of the portable device or a touch of a soft key provided through the touch screen of the portable device in the state where the first and second panels including the first and second touch screens **12** and **14** are unfolded, the camera application drives at least one camera module included in the portable device and displays, for example, screens shown in FIG. **25**A in the first and second touch screen **12** and **14**.

[0529] Referring to FIG. **25**A, the first touch screen **12** displays a live view screen **1502***a* shot by the camera module in a basic camera module and a camera menu **1502***b*, and the second touch screen **14** displays a camera mode menu **1504** for changing a camera mode. The camera mode menu **1504** includes mode buttons **1504***a*, **1504***b*, **1504***c*, and **1504***d* corresponding to a plurality of camera modes. For example, the camera mode menu **1504** may include at least one of a basic camera button **1504***a* for shooting a scene or model through the camera module **24** in the state where the first and second panels **2** and **4** are folded, a self camera button **1504***b* for shooting the user him/herself through the camera module **24** in the state where the first and second panels **2** and **4** are folded, a dual camera button **1504***c* for displaying a shot image through both the first and second touch screens **12** and **14**, and a baby camera button **1504***d* for displaying an image or animation generating the interest of the shot subject through the second touch screen **14** shown to the shot subject.

[0530] When the camera application starts, the camera application is set to operate in the basic camera mode, and a button corresponding to the selected camera mode, that is, the basic camera button **1504***a* is highlighted with a bold line or a different color to be distinguished. Further, when a touch gesture, for example, a tap gesture is detected from the basic camera button **1504***a* within the camera mode menu **1504** provided through the second touch screen **14** is detected, the camera application operates in the basic camera mode.

[0531] The camera menu **1502***b* may be disposed to be included in one or both sides of the shot image **1502***a* and includes function buttons for the shooting such as a shutter button, a stored image loading button, a mode selection button, a flash selection button, a timer shooting button, a white balance button, a resolution selection button and the like.

[0532] As a selectable embodiment, when the portable device includes the camera module **24** located in the front surface of the first or second panel **2** or **4** and the camera module **26** located in the rear surface of the second panel **4**, the shot image **1502***a* may be reproduced by combining images of the front camera module **24** and the rear camera module **26**.

[0533] Referring to FIG. **25**B, the portable device detects folding **1500***a* between the first and second panels **2** and **4** within a predetermined effective angle range while the shot image **1502***a* is displayed in the first touch screen **12** in the basic camera mode and proceeds to FIG. **25**C. Referring to FIG. **25**C, the portable device turns off the second touch screen **14** in response to the folding **1500***a* between the first and second panels **2** and **4**. As one embodiment, when the first and second panels **2** and **4** starts being folded, when the first

and second panels **2** and **4** are folded within a predetermined relative angle (for example, 60 degrees), or when the first and second panels **2** and **4** are completely folded, the second touch screen **14** may be turned off. The first touch screen **12** maintains the shot image **1502***a* and the camera menu **1502***b* after the folding **1500***a*.

[0534] Referring to FIG. **25**D, the first touch screen **12** displays the shot image **1502***a* shot by the camera module **24** in the self camera mode and the camera menu **1502***b*, and the second touch screen **14** displays the camera mode menu **1504** for changing the camera mode. The camera mode menu **1504** includes at least one of the basic camera button **1504***a*, the self camera button **1504***b*, the dual camera button **1504***c*, and the baby camera button **1504***d*. In the self camera mode, the self camera button **1504***b* is displayed with a bold line or a different color to be distinguished.

[0535] Referring to FIG. **25**E, the portable device detects folding **500***b* between the first and second panels **2** and **4** while the shot image **1502***a* is displayed in the first touch screen **12** in the self camera mode and proceeds to FIG. **25**F. Referring to FIG. **25**F, the portable device displays the shot image **1502***a* of the self camera mode and the camera menu **1502***b* in the second touch screen **14** of the second panel **4** having the camera module **24** in the front surface thereof and turns off the first touch screen **12** of the first panel **2** which does not have the camera module **24** in response to the detection of the folding **1500***b* between the first and second panels **2** and **4**.

[0536] Referring to FIG. **25**G, the first touch screen **12** displays the shot image **1502***a* shot by the camera module **24** in the dual camera mode and the camera menu **1502***b* and the second touch screen **14** displays the camera mode menu **1504** for changing the camera mode. The camera mode menu **1504** includes at least one of the basic camera button **1504***a*, the self camera button **1504***b*, the dual camera button **1504***c*, and the baby camera button **1504***d*. In the dual camera mode, the dual camera button **15004***c* is displayed with a bold line or a different color to be distinguished.

[0537] Referring to FIG. **25**H, the portable device detects folding **1500***c* between the first and second panels **2** and **4** while the shot image **1502***a* is displayed in the first touch screen **12** in the dual camera mode and proceeds to FIG. **25**I. Referring to FIG. **25**I, the portable device displays a shot image **1502***c* in the second touch screen **14** without the camera menu **1502***b* in response to the detection of the folding **1500***c* between the first and second touch panels **2** and **4**. Because the shot image **1502***c* of the second touch screen **14** has the purpose to be shown to the shot subject, the shot image **1502***c* does not require including the camera menu. The first touch screen **12** maintains the shot image **1502***a* and the camera menu **1502***b* after the folding **1500***c*.

[0538] Referring to FIG. **25**J, the first touch screen **12** displays the shot image **1502***a* shot by the camera module **24** in the baby camera mode and the camera menu **1502***b*, and the second touch screen **14** displays the camera mode menu **1504** for changing the camera mode. The camera mode menu **1504** includes at least one of the basic camera button **1504***a*, the self camera button **1504***b*, the dual camera button **1504***c*, and the baby camera button **1504***d*. In the self camera mode, the self camera button **1504***d* is displayed with a bold line or a different color to be distinguished.

[0539] Referring to FIG. **25**K, the portable device detects folding **1500***d* between the first and second panels **2** and **4** while the shot image **1502***a* is displayed in the first touch screen **12** in the dual camera mode and proceeds to FIG. **25**L. Referring to FIG. **25**L, the portable device displays an animation **1502***d* pre-stored in the second touch screen **14** in response to the detection of the folding **1500***d* between the first and second touch panels **2** and **4**. The animation is a video stored in the portable device by the manufacturer or user to generate the interest of the shot subject, and may be selected by a setting menu provided by the camera application. For example, the setting menu may be loaded by selecting the menu button which is one of the physical buttons in the lower part of the first touch screen **12** displayed in the shot image **1502***a*.

[0540] As one embodiment, the portable device stores a plurality of animations which can be used in the baby camera mode of the camera application and displays a previous or next animation (not shown) in the second touch screen **14** as a predetermine gesture **1502***d*-**1**, for example, a left/right direction flick, a touch drag, or a sliding is detected from the second touch screen **14** while the animation **1502***d* is displayed in the second touch screen **14** in the baby camera mode.

[0541] Although not illustrated, the portable device can display the shot image **1502***a* and the camera menu **1502***b* in one of the first and second touch screens and display another application in the other touch screen. As one example, the first touch screen **12** displays the shot image **1502***a* and the camera menu **1502***b* in the basic camera mode and the second touch screen **14** displays another application. As another embodiment, the second touch screen **14** displays the shot image **1502***a* and the camera menu **1502***b* in the self camera mode and the first touch screen **12** displays another application.

[0542] When the camera mode menu is not displayed, the camera application supports switching of the camera mode through the camera menu **1502***b*.

[0543] FIGS. **26**A to **26**C illustrate a scenario of switching the camera mode by the camera menu **1502***b* of the portable device. Although it is herein illustrated that the touch screen which does not display the shot image **1502***a* is turned off, the following description can be applied to a case where another application is displayed in the touch screen which does not display the shot image **1502***a*.

[0544] Referring to FIG. **26**A, the first touch screen **12** displays the shot image **1502***a* and the camera menu **1502***b* and the second touch screen **14** is turned off. The camera menu **1502***b* includes function buttons such as a shutter button, a stored image loading button, a mode selection button **1508**, a flash selection button and the like. When a predetermined touch gesture **1510***a*, for example, a tap gesture is detected from the mode selection button **1508**, the portable device proceeds to FIG. **26**B.

[0545] Referring to FIG. **26**B, the portable device displays a camera mode menu window **1512** for changing the camera mode in the shot image **1502***a* of the first touch screen **12** in response to the detection of the touch gesture **1510***a*. The camera mode menu window **1512** includes check boxes **1512***a*, **1512***b*, **1512***c*, and **1512***d* corresponding to a plurality of camera modules, for example, the basic camera mode, the self camera mode, the dual camera mode, and the baby camera mode. When a tap gesture **1510***b* is detected from the check box **1512***b* in the self camera mode among the check boxes **1512***a* to **1512***d*, the portable device proceeds to FIG. **26**C.

[0546] Referring to FIG. **26**C, the portable device displays the shot image **1502***a* and the camera menu **1502***b* in the

second touch screen **14** and turns off the first touch screen **12** in response to the detection of the tap gesture **1510***b*. As another embodiment, when another application is displayed in the second touch screen **14** before the camera mode is changed, the first touch screen **12** can display another application in response to the detection of the tap gesture **1510***b*.

[0547] Although not illustrated, when a tap gesture is detected from the dual camera mode **1512***c* within the camera mode menu window **1512**, the portable device displays the shot image **1502***c* in the second touch screen **14** without the camera menu while maintaining the shot image **1502***a* of the first touch screen **12** and the camera menu **1502***b* as illustrated in FIG. **25**I. Further, when a tap gesture is detected from the baby camera mode **1512***d* within the camera mode menu window **1512**, the portable device displays the pre-stored animation **1502***d* in the second touch screen **14** while maintaining the shot image **1502***a* of the first touch screen **12** and the camera menu **1502***b* as illustrated in FIG. **25**L.

[0548] FIGS. **26**D to **26**G illustrate a scenario of switching the camera mode by a touch of the touch screen which does not display the shot image.

[0549] Referring to FIG. **26**D, the first touch screen **12** displays the shot image **1502***b* and the camera menu **1202***b* and the second touch screen **14** is turned off. The first panel **2** including the first touch screen **12** and the second panel **4** including the second touch screen **14** are in a folded state. When a predetermined touch gesture **1510***c*, for example, two touches (double touch) or two taps (double tap) actually generated at the same time are detected from the turned off second touch screen **14**, the portable device proceeds to FIG. **26**E.

[0550] Referring to FIG. **26**E, the portable device displays the camera mode menu **1504** including mode buttons **1504***a*, **1504***b*, **1504***c*, and **1504***d* corresponding to a plurality of camera modes in the second touch screen **14** in response to the detection of the touch gesture **1510***c*. In an initial display, a camera mode corresponding to the shot image **1502***a* of the first touch screen **12** among the camera mode menu **1504**, that is, the basic camera button **1504***a* corresponding to the basic camera mode is highlighted in the shown example.

[0551] When a predetermined touch gesture **1510***d*, for example, a tap gesture is detected from one of the different mode buttons within the camera mode menu **1504**, for example, the self camera button **1504***b*, the portable device proceeds to FIG. **26**F.

[0552] Referring to FIG. **26**F, the portable device switches the camera mode to the self camera mode, displays the shot image **1502***a* and the camera menu **1502***b* in the second touch screen **14**, and turns off the first touch screen **12** in response to the detection of the touch gesture **1510***d*. When a predetermined touch gesture **1510***e*, for example, two touches (double touch) or two taps (double tap) which are actually generated at the same are detected from the turned off first touch screen **12**, the portable device proceeds to FIG. **26**G.

[0553] Referring to FIG. **26**G, the portable device displays the camera mode menu **1504** including the mode buttons **1504***a*, **1504***b*, **1504***c*, and **1504***d* corresponding to the plurality of camera modes in the first touch screen **12** in response to the detection of the touch screen **1510***e*. When the camera mode menu **1504** is displayed, the camera mode corresponding to the shot image **1502***a* of the second touch screen **14** among the camera mode menu **1504**, that is, the self camera button **1504***d* is highlighted. Similarly, when a tap gesture of the dual camera button **1504***c* or the baby camera button **1504***d* of the camera mode menu **1504** is detected, the portable device displays the shot image and the animation in the corresponding camera mode in the first and second touch screens **12** and **14**.

[0554] FIGS. **26**H to **26**J illustrate a scenario of a timer shooting. Although a scenario in the basic camera mode will be described hereinafter, a count and a shot image can be displayed in a sub screen as well as a main screen in all the camera modes in the timer shooting.

[0555] Referring to FIG. **26**H, the first touch screen **12** displays the shot image **1502***a* and the camera menu **1502***b*, and the second touch screen **14** is turned off. The first panel **2** including the first touch screen **12** and the second panel **4** including the second touch screen **14** may be in a folded state. The camera menu **1502***b* of the first touch screen **12** includes a timer shooting button **1514**. When a tap gesture **1510***f* is detected from a shutter button **1516** in a state where the timer shooting is selected by using the timer shooting button **1514**, the portable device proceeds to FIG. **26**I.

[0556] Referring to FIG. **26**I, the portable device displays a count window **1518***a* in the shot image **1502***a* of the first touch screen **12** in response to the detection of the tap gesture **1510***f*. The portable device simultaneously displays a shot image **1502***e* in the second touch screen **14** and displays a count window **1518***b* on the shot image **1502***a*. Initially, the two count windows **1518***a* and **1518***b* display a preset maximum timer value N, for example, 5. As illustrated in FIG. **26**J, the count windows **1518***a* and **1518***b* of the first and second touch screens **12** and **14** reduce the timer value one by one in the predetermined unit (for example, one second). When the timer value reaches 0 after N seconds, the portable device automatically performs the shooting by driving the camera module while feeding back a shooting effect sound. At this time, the timer value 0 may not be displayed.

[0557] Although not illustrated, a save screen may be displayed in the first and second touch screens **12** and **14** while a picture image shot just after the shooting is stored in a memory of the portable device. When the storage is quickly performed, a display of the save screen may be omitted. As illustrated in FIG. **26**K, after the picture image is stored, the portable device returns the first and second touch screens **12** and **14** to a state before the shooting as illustrated in FIG. **26**H. At this time, a thumbnail image **1502***f* miniaturized from the just previously shot picture image may be included in the camera menu **1502***b* in the first touch screen **12**.

[0558] FIGS. **27**A to **27**Q illustrate examples of changing a view mode according to physical motion of the portable device according to one or more exemplary embodiments.

[0559] FIGS. **27**A to **27**C illustrate a scenario when the folded portable device is unfolded.

[0560] Referring to FIG. **27**A, the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are in the folded state, that is, a state where a relative angle is 0 degrees, wherein the first touch screen **12** displays a first application, for example, a photo gallery application and the second touch screen **14** is turned off. Only the first touch screen **12** is displayed until the relative angle increases to be a threshold angle, for example, 60 degrees as the first and second panels **2** and **4** are slightly unfolded. When the relative angle reaches 60 degrees as the first and second panels **2** and **4** are further unfolded **1600***a*, the portable device proceeds to FIG. **27**B.

[0561] Referring to FIG. **27**B, the portable device displays a running second application **1604**, for example, a music play

application in the second touch screen **14** in response to the unfolding **1600***a* between the first and second panels **2** and **4**. When there is no another running application even though the portable device detects the unfolding **1600***a* between the first and second panels **2** and **4**, the portable device displays a first page **1606***a* of the home screen and a dock area **1606***b* in the second touch screen **14** as illustrated in FIG. **27**C.

[0562] FIGS. **27**D to **27**E illustrate a scenario when the unfolded portable device is folded.

[0563] Referring to FIG. **27**D, the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are in the unfolded state, that is, a state where a relative angle is actually 180 degrees, wherein the first touch screen **12** displays a first task screen **1604***a* of the second application and the second touch screen **14** displays a second task screen **1604** of the second application. Here, the second task screen **1604** is a screen designated to have a final depth of the second application. As one example, the second application is the music play application, the first task screen **1604***a* is a music list screen, and the second task screen **1604** is a music play screen. When the relative angle decreases to be a threshold angle, for example, an angle smaller than 60 degrees as the first and second panels **2** and **4** are folded **1600***b*, the portable device proceeds to FIG. **27**E.

[0564] Referring to FIG. **27**E, the portable device turns off the second touch screen **14** and displays the task screen **1604** designated to have the final depth of the running second application in the first touch screen **12** in response to the folding **1600***b* between the first and second panels **2** and **4**. After the relative angle between the first and second panels **2** and **4** becomes smaller than 60 degrees, the first and second touch screens **12** and **14** are maintained until the relative angle reaches 0 degrees.

[0565] FIGS. **27**F to **27**G illustrate another scenario when the unfolded portable device is folded.

[0566] Referring to FIG. **27**F, the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are in the unfolded state, that is, a state where the relative angle is actually 180 degrees, wherein the first touch screen **12** displays a third application **1608** and the second touch screen **14** displays the second application **1604**. For example, the third application **1608** is a game application and the second application **1604** is the music play application. When the relative angle decreases to be a threshold angle, for example, an angle smaller than 60 degrees as the first and second panels **2** and **4** are folded **1600***c*, the portable device proceeds to FIG. **27**G.

[0567] Referring to FIG. **27**G, the portable device turns off the second touch screen **14** and maintains the running third application **1608** in the first touch screen **12** in response to the folding **1600***c* between the first and second panels **2** and **4**. After the relative angle between the first and second panels **2** and **4** becomes smaller than 60 degrees, the first and second touch screens **12** and **14** are maintained until the relative reaches 0 degrees.

[0568] FIGS. **27**H and **27**I illustrate a scenario when the folded portable device is unfolded in a landscape view mode in which the portable device is rotated by 90 degrees in a left direction.

[0569] Referring to FIG. **27**H, the first and second panels **2** and **4** including the first and second touch screens **12** and **14** is in the folded state, that is, a state in which the relative angle is 0 degrees. In the landscape view mode, the first touch screen **12** displays the first application **1602**, for example, a photo gallery application and the second touch screen **14** is turned off. Only the first touch screen **12** is displayed until the relative angle increases to be a predetermined threshold angle, for example, 60 degrees as the first and second panels **2** and **4** are slightly unfolded. When the relative angle becomes larger than 60 degrees and smaller than 180 degrees as the first and second panels **2** and **4** are further unfolded **1600***d*, the portable device proceeds to FIG. **27**I.

[0570] Referring to FIG. **27**I, the portable device displays the running second application **1604**, for example, the music play application in the second touch screen **14** in response to the unfolding **1600***d* between the first and second panels **2** and **4**. When there is no other running application even though the portable device detects the unfolding **1600***d* between the first and second panels **2** and **4**, the portable device displays a first page **1606***a* of the home screen and a dock area **1606***b* in the second touch screen **14** as illustrated in FIG. **27**J.

[0571] FIGS. **27**K to **27**M illustrate a scenario when the folded portable device is unfolded in the landscape view mode in which the portable device is rotated by 90 degrees in a right direction.

[0572] Referring to FIG. **27**K, the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are in the folded state, that is, the state where the relative angle is 0 degrees. In the landscape view mode, the first touch screen **12** displays the first application **1602**, for example, the photo gallery application and the second touch screen **14** is turned off. Only the first touch screen **12** is displayed until the relative angle increases to be a threshold angle, for example, 60 degrees as the first and second panels **2** and **4** are slightly unfolded. When the relative angle becomes larger than 60 degrees and smaller than 180 degrees as the first and second panels **2** and **4** are further unfolded **1600***e*, the portable device proceeds to FIG. **27**L.

[0573] Referring to FIG. **27**L, the portable device displays the running second application **1604**, for example, the music play application in the second touch screen **14** in response to the unfolding **1600***e* between the first and second panels **2** and **4**. When there is no other running application even though the portable device detects the unfolding **1600***e* between the first and second panels **2** and **4**, the portable device displays the first page **1606***a* of the home screen and the dock area **1606***b* in the second touch screen **14** as illustrated in FIG. **27**M.

[0574] FIGS. **27**N to **27**P illustrate a scenario when the unfolded portable device is folded in the landscape view mode.

[0575] Referring to FIG. **27**N, the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are in the unfolded state, that is, the state where the relative angle is actually 180 degrees, wherein the first touch screen **12** displays the first task screen **1604** of the second application and the second touch screen **14** displays the second task screen **1604***a* of the second application. Here, the first task screen **1604** is a screen designated to have a final depth of the second application. For example, the second application is the music play application, the first task screen **1604** is the music play screen, and the second task screen **1604***a* is the music list screen. When the relative angle decreases to be a threshold angle, for example, 60 degrees as the first and second panels **2** and **4** are folded **1600***f*, the portable device proceeds to FIG. **27**O.

[0576] Referring to FIG. **27**O, the portable device turns off the second touch screen **14** and displays the task screen **1604** designated to have the final depth of the running second

application in the first touch screen **12** in response to the folding **1600***f* between the first and second panels **2** and **4**. After the relative angle between the first and second panels **2** and **4** becomes smaller than 60 degrees, the first and second touch screens **12** and **14** are maintained until the relative angle reaches 0 degrees.

[0577] FIGS. **27**P and **27**Q illustrate another scenario when the unfolded portable device is folded in the landscape view mode.

[0578] Referring to FIG. **27**P, the first and second panels **2** and **4** including the first and second touch screens **12** and **14** are in the unfolded state, that is, the state in which the relative angle is actually 180 degrees, wherein the first touch screen **12** displays the first application **1602** and the second touch screen **14** displays the second application **1604**. For example, the first application **1602** is the photo gallery application and the second application **1604** is the music play application. When the relative angle decreases to be a threshold angle, for example, 60 degrees as the first and second panels **2** and **4** are folded **1600***g*, the portable device proceeds to FIG. **27**Q.

[0579] Referring to FIG. **27**Q, the portable device turns off the second touch screen **14** and maintains the running first application **1602** in the first touch screen **12** in response to the folding **1600***g* between the first and second panels **2** and **4**. After the relative angle between the first and second panels **2** and **4** becomes smaller than 60 degrees, the first and second touch screens **12** and **14** maintain displayed information until the relative angle reaches 0 degrees.

[0580] While the detailed description of the present invention has described the concrete embodiments, the embodiments can be modified without departing from the scope of the present invention. Therefore, the scope of the present invention should not be limited to the described embodiments, but should be defined by the appended claims and the equivalents thereof.

1.-**191**. (canceled)

192. A method of controlling a portable device comprising a first touch screen and a second touch screen, the method comprising:

displaying first information on the first touch screen and detecting an outgoing call request while second information is displayed on the second touch screen;

replacing the first information displayed on the first touch screen with an outgoing call screen by displaying the outgoing call screen in response to the detecting the outgoing call request,

wherein the outgoing call screen comprises at least one of a number display area displaying a dialed number, a call key, a video call key, and a message sending key, and the second touch screen maintains the second information while the outgoing call screen is displayed on the first touch screen;

receiving a phone number input through the keypad area and detecting a first tap gesture from the call key;

replacing the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen in response to the detecting the first tap gesture,

wherein the dialing screen comprises a call participant identification area indicating a counterpart call participant corresponding to the input phone number and a function key area providing mid-call functions;

deactivating the second information of displayed on the second touch screen and displaying, on the second touch screen, a guide message indicating to fold the portable device for the call while the outgoing call screen is displayed;

replacing the dialing screen on the first touch screen with a mid-call screen by displaying the mid-call screen in response to the call being connected with the counterpart call participant; and

removing the guide message displayed on the second touch screen, and displaying the first information on the second touch screen, wherein the mid-call screen comprises a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

193. The method of claim **192**, further comprising:

displaying a dock area comprising a call icon of a call application on at least one of the first touch screen and second touch screens; and

determining that the outgoing call request is detected when the first tap gesture is detected from the call icon of the call application.

194. The method of claim **192**, further comprising connecting a call in a speaker mode when the call is connected with the counterpart call participant in a state where a first panel comprising the first touch screen and a second panel comprising the second touch screen are unfolded.

195. The method of claim **194**, further comprising:

detecting that the first panel and the second panel are folded out such that the first touch screen faces a front side after the call is connected with the counterpart call participant; and

turning off the second touch screen and deactivating the speaker mode in response to the detecting that the first panel and the second panel are folded out.

196. The method of claim **192**, further comprising:

displaying, on the second touch screen, a dock area comprising shortcut icons of frequently used applications together with the second information, in response to at least one of the outgoing call screen and the mid-call screen being displayed on the first touch screen,

wherein the second information displayed in the second touch screen comprises a first page designated as a home screen.

197. The method of claim **196**, further comprising:

detecting that the first panel and the second panels are folded out such that the first touch screen faces a front side while the mid-call screen is displayed on the first touch screen, and the first page of the home screen and the dock area are displayed on the second touch screen;

turning off the second touch screen and maintaining the mid-call screen on the first touch screen in response to the detecting that the first panel and second panel are folded out; and

replacing the mid-call screen displayed on the first touch screen with the first page of the home screen and the dock area by displaying, on the first touch screen, the first page and dock area in response to the call with the counterpart call participant ending.

198. (canceled)

199. A portable device comprising:

a first touch screen and a second touch screen; and

at least one processor that is configured to:

display first information on the first touch screen and detect an outgoing call request while second information is displayed on the second touch screen,

replace the first information displayed on the first touch screen with an outgoing call screen by displaying the outgoing call screen on the first touch screen in response to the detection of the outgoing call request,

wherein the outgoing call screen comprises at least one of a number display area displaying a dialed number, a call key, a video call key, and a message sending key, and the second touch screen maintains the second information while the outgoing call screen is displayed on the first touch screen,

receive a phone number input through the keypad area and detect a first tap gesture from the call key,

replace the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen on the first touch screen in response to the detection of the first tap gesture, and display, on the second touch screen, a guide message indicating to fold the portable device for a call, wherein the dialing screen comprises a call participant identification area indicating a counterpart call participant corresponding to the input phone number and a function key area providing mid-call functions,

replace the dialing screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the call being connected with the counterpart call participant, and

remove the guide message on the second touch screen, and displaying the first information on the second touch screen, wherein the mid-call screen comprises a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

200. (canceled)

201. A non-transitory computer-readable medium storing a program executable by a computer to perform a method of controlling a portable device comprising a first touch screen and a second touch screen, the method comprising:

displaying first information on the first touch screen and detecting an outgoing call request while second information is displayed on the second touch screen;

replacing the first information displayed on the first touch screen with an outgoing call screen by displaying the outgoing call screen in response to the detecting the outgoing call request,

wherein the outgoing call screen comprises at least one of a number display area displaying a dialed number, a call key, a video call key, and a message sending key, and the second touch screen maintains the second information while the outgoing call screen is displayed on the first touch screen;

receiving a phone number through the keypad area and detecting a first tap gesture from the call key;

replacing the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen on the first touch screen in response to the detecting the first tap gesture, and display, on the second touch screen, a guide message indicating to fold the portable device for a call, wherein the dialing screen comprises a call participant identification area indicating a counterpart call participant corresponding to the input phone number and a function key area providing mid-call functions;

replacing the dialing screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the call being connected with the counterpart call participant; and

removing the guide message displayed on the second touch screen, and displaying the first information, wherein the mid-call screen comprises a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

202. (canceled)

203. A method of controlling a portable device comprising a first touch screen and a second touch screen, the method comprising:

detecting a first incoming call while displaying first information on the first touch screen and displaying second information on the second touch screen;

replacing the first information displayed on the first touch screen with a first incoming call screen related to the first incoming call by displaying the first incoming call screen on the first touch screen in response to the detecting the first incoming call, wherein the first incoming call screen comprises at least one of a call participant identification area indicating a counterpart call participant corresponding to the first incoming call, an incoming key, and a rejection message key;

deactivating the second information displayed on the second touch screen and displaying a guide message indicating to fold the portable device for a call while displaying the first incoming call screen;

detecting a pre-designated first touch gesture from the incoming key within the first incoming call screen; and

replacing the first incoming call screen of displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the detecting the first touch gesture, and removing the guide message displayed on the second touch screen, wherein the mid-call screen comprises a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

204. The method of claim **203**, further comprising replacing the mid-call screen of displayed on the first touch screen with the first information by displaying the first information on the first touch screen in response to the first incoming call ending.

205. The method of claim **203**, further comprising connecting the call in a speakerphone mode when the first touch gesture is detected in a state where the first and second panels are unfolded.

206. The method of claim **203**, further comprising displaying the first information in the second touch screen in response to the detecting the first touch gesture when the first information comprises a text input area of a first application.

207. The method of claim **203**, further comprising:

detecting an input from a home button corresponding to a physical buttons arranged on the second panel while the mid-call screen is displayed on the first touch screen and the second information is displayed on the second touch screen; and

replacing the second information displayed on the second touch screen with a first page comprising at least one widget area designated as a home screen and an icon

related to at least one application and a dock area comprising icons of frequently used applications by displaying the first page and the dock area on the second touch screen in response to the input from the home button.

208. The method of claim **203**, further comprising:

detecting a pre-designated second touch gesture from the rejection message key of the first incoming call screen while the first incoming call screen is displayed on the first touch screen and the guide message is displayed on the second touch screen;

replacing the first incoming call screen displayed on the first touch screen with a rejection message screen by displaying the rejection message screen on the first touch screen in response to the detecting the second touch gesture, and replacing the guide message displayed on the second touch screen with a text input area for inputting a rejection message and a virtual keypad by displaying the text input area and the virtual keypad on the second touch screen, wherein the rejection message screen comprises a plurality of pre-stored rejection messages and sending keys for the rejection messages;

sending a corresponding pre-stored rejection message to a counterpart call participant of the first incoming call when a tap gesture is detected from one of the sending keys;

in response to a rejection message being input through the virtual keypad a tap gesture that is detected from the sending key included in the text input area, sending the input rejection message to the counterpart call participant of the first incoming call; and

displaying the first information and the second information on the first touch screen and the second touch screens after sending at least one of the pre-stored rejection message and the input rejection message.

209. The method of claim **203**, further comprising:

detecting a second incoming call while the mid-call screen is displayed on the first touch screen and the second information is displayed on the second touch screen;

replacing the mid-call screen displayed on the first touch screen with a second incoming call screen related to the second incoming call in response to the detecting the second incoming call, wherein the second incoming call screen comprises at least one of a call participant identification area indicating a counterpart call participant related to the second incoming call, an incoming key, and a rejection message key;

detecting a pre-designated second touch gesture from the incoming key within the second incoming call screen; and

displaying a multi incoming selection menu window in the second incoming call screen displayed on the first touch screen in response to the detecting the second touch gesture, wherein the multi incoming selection menu window comprises a waiting key for the first incoming call and an end key; and

connecting the second incoming call and having the first incoming call wait in response to a tap gesture being detected from the waiting key, and replacing the second incoming call screen displayed on the first touch screen with a multi mid-call screen by displaying the multi call screen on the first touch screen, wherein the multi call screen comprises call participant identification areas for call participants of the first and second incoming calls, a call swap key, a merge key, and a function key area providing mid-call functions,

wherein the second touch screen continuously displays the second information while one of the second incoming call screen and the multi mid-call screen is displayed in the first touch screen.

210. The method of claim **203**, further comprising:

displaying first information on the first touch screen and detecting a second incoming call while the second touch screen is turned off in a state where a first panel comprising the first touch screen and a second panel comprising the second touch screen are folded such that the first touch screen faces a front side;

replacing the first information displayed on the first touch screen with a second incoming call screen related to the second incoming call provided by a call application in response to the detecting the second incoming call, wherein the second incoming call screen comprises at least one of a call participant identification area indicating a counterpart call participant related to the second incoming call, an incoming key, and a rejection message key;

detecting the folded first and second panels are overturned such that the second touch screen faces the front side; and

turning off the first touch screen and displaying a rejection message screen on the second touch screen in response to the detecting the folded first and second panels are overturned, wherein the rejection message screen comprises a plurality of pre-stored rejection messages and sending keys for the rejection messages.

211. The method of claim **210**, further comprising:

detecting that the first and second touch panels are unfolded while the rejection message screen is displayed on the second touch screen;

displaying the rejection message screen on the first touch screen, and replacing the rejection message screen displayed on the second touch screen with a text input area for inputting a rejection message and a virtual keypad by displaying the text input area and the virtual keypad on the first touch screen in response to the detecting that the first and second touch panels are unfolded, wherein the rejection message screen comprises a plurality of pre-stored rejection messages and sending keys for the rejection messages;

sending a corresponding pre-stored rejection message to a counterpart call participant of the second incoming call in response to a tap gesture being detected from one of the sending keys; and

in response to a rejection message being input through the virtual keypad and a tap gesture being detected from a sending key included in the text input area, sending the input rejection message to the counterpart call participant of the second incoming call.

212. (canceled)

213. A portable device comprising:

at least one foldable panel;

a first touch screen and a second touch screen arranged on the at least one foldable panel; and

at least one processor that is configured to:

display, on the first touch screen, first information and detect a generation of a first incoming call while second information is displayed on the second touch screen in a state where a first panel of the at least one foldable panel

comprises the first touch screen, a second panel of the at least one foldable panel comprises the second touch screen, and the first and second touch screens are unfolded,

replace the first information displayed on the first touch screen with a first incoming call screen related to the first incoming call provided by a call application by displaying the first incoming call screen on the first touch screen in response to the generation of the first incoming call, wherein the first incoming call screen comprises at least one of a call participant identification area indicating a counterpart call participant, an incoming key, and a rejection message keys,

deactivate the second information displayed on the second touch screen and display a guide message indicating to fold the portable device for a call while displaying the first incoming call screen,

detect a pre-designated first touch gesture from the incoming key within the first incoming call screen,

replace the incoming call screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the detection of the first touch gesture, and remove the guide message on the second touch screen, wherein the mid-call screen comprises a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions, and

replace the mid-call screen on the first touch screen with the first information by displaying the first information on the first touch screen in response to the first incoming call ending.

214. (canceled)

215. A non-transitory computer-readable medium storing a program executable by a computer to perform a method of controlling portable device comprising a first touch screen and a second touch screen arranged on at least one foldable panel, the method comprising:

displaying, on the first touch screen, a first page comprising at least one of a widget area designated as a home screen and an icon related to at least one application or and displaying a dock area a call icon of a call application;

displaying, on the second touch screen, first information in a state where a first panel of the at least one foldable panel comprises the first touch screen, a second panel of the at least one foldable panel comprises the second touch screen are unfolded;

detecting a first tap gesture from that selects the call icon;

replacing the first page and the dock area on the first touch screen with an outgoing call screen provided by the call application by displaying the outgoing call screen on the first touch screen in response to a detection of the first tap gesture,

wherein the outgoing call screen comprises at least one of a number display area, a keypad area, a call key, a video call key, and a message sending key, and the second touch screen maintains the first information while the outgoing call screen is displayed in the first touch screen;

receiving a phone number through the keypad area and detecting a second tap gesture from the call key;

replacing the outgoing call screen displayed on the first touch screen with a dialing screen by displaying the dialing screen on the first touch screen in response to the detecting the second tap gesture, and displaying, on the second touch screen, a guide message indicating to fold the portable device for a call, wherein the dialing screen comprises a call participant identification area indicating a counterpart call participant and a function key area providing mid-call functions;

replacing the dialing screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the call being connected with the counterpart call participant; and

removing the guide message displayed on the second touch screen, and displaying the first information, wherein the mid-call screen comprises a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

216. A non-transitory computer-readable medium storing a program executable by a computer to perform a method of controlling a portable device comprising a first touch screen and a second touch screen arranged on at least one foldable panel, the method comprising:

displaying first information on a first touch screen and detecting a generation of a first incoming call while second information is displayed on a second touch screen in a state where a first panel of the at least one foldable panel comprises the first touch screen, a second panel of the at least one foldable panel comprises the second touch screen, and the first and second panels are unfolded;

replacing the first information displayed on the first touch screen with a first incoming call screen related to the first incoming call provided by a call application by displaying the first incoming call screen on the first touch screen in response to the generation of the first incoming call,

wherein the first incoming call screen comprises at least one of a call participant identification area indicating a counterpart call participant, an incoming key, and a rejection message key;

deactivating the second information displayed on the second touch screen and displaying a guide message indicating to fold the portable device for a call while displaying the first incoming call screen;

detecting a pre-designated first touch gesture from the incoming key within the first incoming call screen;

replacing the incoming call screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the detecting the first touch gesture;

removing the guide message displayed on the second touch screen, wherein the mid-call screen comprises a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions; and

replacing the mid-call screen of displayed on the first touch screen with the first information by displaying the first information on the first touch screen in response to the first incoming call ending.

217. A non-transitory computer-readable medium storing a program executable by a computer to perform a method of controlling portable device comprising a first touch screen and a second touch screen arranged on at least one foldable panel, the method comprising:

detecting a first incoming call while displaying first information on the first touch screen and displaying second information on the second touch screen;

replacing the first information displayed on the first touch screen with a first incoming call screen related to the first incoming call by displaying the first incoming call screen on the first touch screen in response to the detecting the first incoming call, wherein the first incoming call screen comprises at least one of a call participant identification area indicating a counterpart call participant corresponding to the first incoming call, an incoming key, and a rejection message key;

deactivating the second information displayed on the second touch screen and displaying a guide message indicating to fold the portable device for a call while displaying the first incoming call screen;

detecting a pre-designated first touch gesture from the incoming key within the first incoming call screen; and

replacing the first incoming call screen displayed on the first touch screen with a mid-call screen by displaying the mid-call screen on the first touch screen in response to the detecting the first touch gesture, and removing the guide message displayed on the second touch screen, wherein the mid-call screen comprises a call participant identification area indicating the counterpart call participant and a function key area providing a call duration time and mid-call functions.

218.-**228**. (canceled)

* * * * *